

# Teknisk rapport

## SIS-ISO/TR 10982:2014

Publicerad/Published: 2014-01-24  
Utgåva/Edition: 1  
Språk/Language: engelska/English  
ICS: 43.100

---

### **Vägfordon – Metod för provning av interaktion mellan airbag och felplacerad passagerare (ISO/TR 10982:2013, IDT)**

### **Road vehicles – Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags (ISO/TR 10982:2013, IDT)**

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-100708>

# Standarder får världen att fungera

*SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.*

## Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.



## Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

## Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

**Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på [www.sis.se](http://www.sis.se) eller ta kontakt med oss på tel 08-555 523 00.**



# Standards make the world go round

*SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.*

## Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

## Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

## Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

**If you want to know more about SIS, or how standards can streamline your organisation, please visit [www.sis.se](http://www.sis.se) or contact us on phone +46 (0)8-555 523 00**



Denna tekniska rapport är inte en svensk standard. Detta dokument innehåller den engelska språkversionen av ISO/TR 10982:2013.

This Technical Report is not a Swedish Standard. This document contains the English version of ISO/TR 10982:2013.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

*Uppllysningar om sakinnehållet i detta dokument lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om nationell och internationell standard.*

*Information about the content of this document is available from the SIS, Swedish Standards Institute, telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about national and international standards.*

Dokumentet är framtaget av kommittén för Fordonssäkerhet, SIS/TK 237.

Har du synpunkter på innehållet i det här dokumentet, vill du delta i ett kommande revideringsarbete eller vara med och ta fram standarder inom området? Gå in på [www.sis.se](http://www.sis.se) - där hittar du mer information.



# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Test drive</b> .....	<b>1</b>
4.1 General.....	1
4.2 50th percentile male Hybrid III dummy.....	2
4.3 “Small female” Hybrid III dummy.....	2
4.4 Three-year-old child Hybrid III dummy.....	2
<b>5 Instrumentation</b> .....	<b>2</b>
5.1 Adult size dummy.....	2
5.2 Three-year-old child dummy.....	2
5.3 Data requirements.....	3
5.4 Dummy test temperature.....	3
<b>6 Sled pulses</b> .....	<b>3</b>
6.1 General.....	3
6.2 Mild severity crash pulse.....	3
6.3 Moderate severity crash pulse.....	3
<b>7 Static and dynamic test for driver air bag systems</b> .....	<b>6</b>
7.1 Test set-up.....	6
7.2 Prepositioned driver tests.....	6
7.3 Acceleration-induced out-of-position driver dynamic tests.....	7
<b>8 Static and dynamic tests for passenger air bag systems, using child dummy</b> .....	<b>8</b>
8.1 General.....	8
8.2 Test set-up.....	8
8.3 Child dummy test positions.....	8
8.4 Child dummy static tests for passenger air bag systems.....	10
8.5 Child dummy dynamic tests for passenger air bag systems.....	10
<b>9 Static and dynamic tests for passenger air bag systems using adult dummies</b> .....	<b>10</b>
9.1 General.....	10
9.2 Test set-up.....	10
9.3 Adult dummy positions near instrument panel.....	11
9.4 Adult dummy static tests for passenger air bag systems.....	11
9.5 Adult dynamic tests for passenger air bag systems.....	11
<b>Bibliography</b> .....	<b>13</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 10, *Impact test procedures*.

This second edition cancels and replaces the first edition (ISO/TR 10982:1998), which has been technically revised.

Annex A of this Technical Report is for information only.

## Introduction

Although laws concerning the mandatory use of seat belts and child restraints have been enacted in most ISO member countries, surveys and accident statistics indicate that between 10 % and 50 % of front seat occupants involved in accidents had not used these restraint systems. Most, if not all, new vehicles marketed with air bags in ISO member countries specify that the air bag is supplemental to the existing belt/child seat restraint systems. However, front seat occupants may not comply with manufacturer's recommendations and laws. Hence, they may be near or against deploying driver and/or passenger air bag modules during collisions. Some data indicate that small, unrestrained children may get into such positions due to voluntary precrash riding positions<sup>[1]</sup> and/or due to preimpact braking and/or collision forces.<sup>[2]</sup> These factors may also cause some adults to be near the air bag modules, but preimpact braking is likely to have less effect on adults.

During the inflation process, an air bag generates a considerable amount of kinetic energy and as a result substantial forces can be developed between the deploying air bag and the out-of-position occupant. Accident data and laboratory test results<sup>[4][9]</sup> have indicated that these forces could cause injuries to the head, neck, thorax, abdomen and legs.

Both mild and moderate severity crash pulses are described in this Technical Report. These pulses represent general deceleration-time histories. The mild severity crash pulse is near the threshold of many air bag deployments and represents a frequent accident event. This pulse can be used for child testing, since they are more likely than adults to be near the air bag modules in threshold deployment collisions. Since preimpact braking has much less of an effect on adults, the moderate severity crash pulse can be used for adult testing. These described pulses or other vehicle-specific pulses may be used.

This Technical Report describes the more common interactions, recognizing that the range of possible interactions is essentially limitless.

This document is published as a Technical Report, rather than as an International Standard, because of the general inexperience in air bag testing and lack of real-world accident data correlation. When sufficient real-world data are available and/or there is sufficient testing experience, it may be appropriate to develop an International Standard.





# Road vehicles — Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags

## 1 Scope

This Technical Report outlines a number of test procedures that can be used for investigating the interactions that could occur between the deploying air bag and the occupant who is near the module at the time of deployment. Static and dynamic tests to investigate both driver and passenger systems are described. Comparative evaluation of the designs can be conducted using static tests. Favourable systems may be evaluated, if deemed necessary, by appropriate dynamic tests.

Children and infants restrained in child or infants seats are the subject of another Technical Report.<sup>[20]</sup>

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6487:2012, *Road vehicles — Measurement techniques in impact tests — Instrumentation*

SAE J211, *Part-1 Instrumentation for impact test*

## 3 Terms and definitions

For the purposes of this document, the following definitions apply.

### 3.1

#### **passenger air bag module location**

<low mounted> rearward deploying module location in the area of the instrument panel, normally used for knee bolsters

### 3.2

#### **passenger air bag module location**

<mid mounted> rearward deploying module location above the knee bolster area in the instrument panel

### 3.3

#### **passenger air bag module location**

<top mounted> air bag system that deploys through the top surface of the instrument panel

### 3.4

#### **out-of-position occupant**

vehicle occupant who is near the air bag module at the time of deployment

## 4 Test drive

### 4.1 General

Two sizes of adult dummies and one child size dummy are available for out-of-position occupant investigations. It is suggested that the adult dummies be equipped with an optional neck cover to give a more humanlike shape to the neck and neck-head junction.

## 4.2 50th percentile male Hybrid III dummy

This dummy is specified in FMVSS part 572, subpart E.

## 4.3 “Small female” Hybrid III dummy

The small female dummy is a scaled-down version of the Hybrid III 50th percentile male dummy. The size, shape, response and measurement capability were defined by a task force of the SAE Human Biomechanics and Simulation Standards Committee.<sup>[11]</sup> This dummy is specified in FMVSS part 572, subpart O.

## 4.4 Three-year-old child Hybrid III dummy

This dummy was developed for passenger air bag testing<sup>[12]</sup> by a task force of the SAE Human Biomechanics and Simulation Standards Committee and is commercially available. This dummy is specified in FMVSS part 572, subpart P.

# 5 Instrumentation

## 5.1 Adult size dummy

Measurements that can be made or calculated using these test devices are listed below:

- facial forces;<sup>[19]</sup>
- head triaxial acceleration (three channels);
- head angular acceleration in sagittal plane (at least one channel for an extra linear accelerometer);
- upper neck (C-1: occipital condyles) forces and moments (six channels);
- lower neck (C-7, T-1) forces and moments (six channels);
- chest triaxial acceleration (three channels);
- mid-sternum to thoracic spine deflection (one channel);
- mid-sternum acceleration (one channel);
- upper and lower ribcage deflection<sup>1)</sup> (five channels);
- lower thoracic spine (T-12) forces and moments<sup>2)</sup> (five to six channels);
- pelvis triaxial acceleration (three channels);
- for systems using inflatable knee restraints, the full spectrum of Hybrid III multi-channel femur and tibia load cells and knee displacement transducers can be used to measure leg loading.

## 5.2 Three-year-old child dummy

Measurements that can be made or calculated using the child dummy are listed below:

- head triaxial acceleration (three channels);
- head angular acceleration in sagittal plane (at least one channel for an extra linear accelerometer);
- upper neck (C-1) forces and moments (six channels);

---

1) Instrumentation for measurements is being developed and is expected to be available for both dummies at a later date.

2) Only available for the small female.

- lower neck (C-1/T-1) forces and moments (six channels);
- shoulder forces ( $F_x, F_z$ ; four channels);
- sternal acceleration ( $a_x$ ; two channels);
- sternal deflection (one channel);
- spine triaxial accelerations (T-1, T-4, T-12; nine channels);
- lumbar forces and moments (six channels);
- pubic forces ( $F_x, F_z$ ; two channels);
- pelvis triaxial acceleration (three channels).

### 5.3 Data requirements

All measurements should be recorded and filtered according to ISO 6487 and SAE J211 for body regions. These measurements should be continuous functions of time so other quantities, such as those found in references[8],[9],[13]-[17] may be derived.

### 5.4 Dummy test temperature

The test dummy temperature should be within the range of 20,6 °C to 22,2 °C (69 °F to 72 °F) at a relative humidity of 10 % to 70 % after a soak period of at least four hours prior to its application in a test.

## 6 Sled pulses

### 6.1 General

Mild severity and moderate severity crash pulses are defined in 6.2 and 6.3. The out-of-position child may be exposed to a pulse similar to the mild severity crash pulse since collisions of similar severity occur most often, and preimpact braking will cause the child to be out-of-position more often than the collision dynamics.

### 6.2 Mild severity crash pulse

This pulse is a half sine type with a peak acceleration occurring near the centre of the time duration of  $(8 \pm 1)g^3)$  between 40 ms to 100 ms, a velocity change of  $(27 \pm 2)$  km/h, and a  $(150 \pm 5)$  ms pulse duration. Typical acceleration-time and velocity-time curves, and nominal acceleration are shown in [Figures 1](#) and [2](#).

### 6.3 Moderate severity crash pulse

This pulse is a half sine type with a peak acceleration occurring near the centre of the time duration of  $(13 \pm 1)g$  between 40 ms to 80 ms, a velocity change of  $(29 \pm 2)$  km/h, and a  $(110 \pm 5)$  ms pulse duration. Typical acceleration-time and velocity-time curves, and nominal acceleration are shown in [Figures 3](#) and [4](#).

---

3)  $g = 9,806\ 65\ \text{m/s}^2$