

SVENSK STANDARD


SS-EN ISO 11275:2014



Fastställt/Approved: 2014-03-30
Publicerad/Published: 2014-03-31
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 13.080.40

Markundersökningar – Bestämning av omättad konduktivitet och vattenhållande förmåga – Winds avdunstningsmetod (ISO 11275:2004)

Soil quality – Determination of unsaturated hydraulic conductivity and water-retention characteristic – Wind's evaporation method (ISO 11275:2004)



Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.


Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Europastandarden EN ISO 11275:2014 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN ISO 11275:2014.

Denna standard ersätter SS-ISO 11275:2005, utgåva 1.

The European Standard EN ISO 11275:2014 has the status of a Swedish Standard. This document contains the official version of EN ISO 11275:2014.

This standard supersedes the Swedish Standard SS-ISO 11275:2005, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Karaktärisering av avfall, mark och slam, SIS/TK 535.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

EUROPEAN STANDARD

EN ISO 11275

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2014

ICS 13.080.40

English Version

**Soil quality - Determination of unsaturated hydraulic conductivity
and water-retention characteristic - Wind's evaporation method
(ISO 11275:2004)**

Qualité du sol - Détermination de la conductivité
hydraulique en milieu non saturé et de la caractéristique de
rétention en eau - Méthode par évaporation de Wind (ISO
11275:2004)

Bodenbeschaffenheit - Bestimmung der ungesättigten
hydraulischen Leitfähigkeit und des
Wasserrückhaltevermögens - Verdunstungsverfahren nach
Wind (ISO 11275:2004)

This European Standard was approved by CEN on 13 March 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		Page
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
5	Principle	3
6	Apparatus	3
7	Procedure	4
8	Expression of results	9
9	Accuracy	9
10	Test report	9
	Bibliography	11

Foreword

The text of ISO 11275:2004 has been prepared by Technical Committee ISO/TC 190 "Soil quality" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 11275:2014 by Technical Committee CEN/TC 345 "Characterization of soils" the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2014, and conflicting national standards shall be withdrawn at the latest by September 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 11275:2004 has been approved by CEN as EN ISO 11275:2014 without any modification.

Introduction

Soil water content and matric pressure are related to each other and determine the water-retention characteristics of a soil. Soil water, which is in equilibrium with free water, is at zero matric pressure (or suction) and either the soil is saturated or the gaseous phase occurs only as small bubbles. As a saturated soil dries, the matric pressure decreases (i.e. becomes more negative), and the largest pores empty of water. Progressive decreases in matric pressure will continue to empty finer pores until eventually water is held in only the finest pores. Not only is water removed from soil pores, but the films of water held around soil particles are reduced in thickness. Therefore, a decreasing matric pressure is associated with decreasing soil water content^{[8],[9]}. Laboratory or field measurements of these two parameters can be made; and the relationship (which can be reported graphically, in tabular form, or possibly as an equation) is called the soil water-retention characteristic. The relationship extends from saturated soil to oven-dry soil (approximately 0 kPa to about -10^6 kPa matric pressure).

The soil water-retention characteristic is different for each soil type. The shape and position of the curve relative to the axes depend on soil properties such as texture, density and hysteresis associated with the wetting and drying history. Individual points on the water-retention characteristic curve may be defined for specific purposes.

The hydraulic conductivity is a measure of the rate at which liquid water can move through the soil under the influence of variations in matric pressure from point to point within the soil. The hydraulic conductivity of unsaturated soil depends on the same factors as does the soil water-retention characteristic, also showing hysteresis. As a saturated soil dries, the hydraulic conductivity decreases, and it is convenient to express the hydraulic conductivity corresponding to the soil water-retention characteristic as a function of the decreasing matrix pressure.

The results obtained using these methods can be used, for example:

- to provide an assessment of the equivalent pore-size distribution (e.g. identification of macro- and micro-pores);
- to determine indices of plant-available water in the soil and to classify soil accordingly (e.g. for irrigation purposes);
- to determine the drainable pore space (e.g. for drainage design, pollution risk assessments);
- to monitor changes in the structure of a soil (caused by e.g. tillage, compaction or addition of organic matter or synthetic soil conditioners);
- to ascertain the relationship between the negative matric pressure and other soil physical properties (e.g. hydraulic conductivity, thermal conductivity);
- to determine water content at specific negative matric pressures (e.g. for microbiological degradation studies);
- to estimate other soil physical properties.

Soil quality — Determination of unsaturated hydraulic conductivity and water-retention characteristic — Wind's evaporation method

1 Scope

This International Standard specifies a laboratory method for the simultaneous determination in soils of the unsaturated hydraulic conductivity and of the soil water-retention characteristic. It is applicable only to measurement of the drying or desorption curve. Application of the method is restricted to soil samples which are, as far as possible, homogeneous. The method is not applicable to soils which shrink in the range of matric head $h_m = 0$ cm to $h_m = -800$ cm.

The range of the determination of the conductivity depends on the soil type. It lies between matric heads of approximately $h_m = -50$ cm and $h_m = -700$ cm.

The range of the determination of the water-retention characteristic lies between matric heads of approximately $h_m = 0$ cm and $h_m = -800$ cm.

NOTE 1 An infiltrometer method can be used to determine hydraulic conductivities near saturation.

NOTE 2 ISO 11274 gives methods to determine the water-retention characteristic for matric heads between 0 cm and $-15\,000$ cm.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10381-1, *Soil quality — Sampling — Part 1: Guidance on the design of sampling programmes*

ISO 10381-4, *Soil quality — Sampling — Part 4: Guidance on the procedure for investigation of natural, near-natural and cultivated sites*

ISO 11274, *Soil quality — Determination of the water-retention characteristic — Laboratory methods*

ISO 11276, *Soil quality — Determination of pore water pressure — Tensiometer method*

ISO 11461, *Soil quality — Determination of soil water content as a volume fraction using coring sleeves — Gravimetric method*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

SS-EN ISO 11275:2014 (E)

3.1 hydraulic conductivity
K
 factor of proportionality between the soil water flux density, v , and the hydraulic gradient ∇h_h in Darcy's equation, assuming isotropic conditions, i.e.

$$v = -K\nabla h_h$$

NOTE For the purposes of this document, conductivity is used synonymously for unsaturated hydraulic conductivity.

3.2 soil water-retention characteristic retention characteristic
 relation between soil water content and soil matric head of a given soil (sample)

3.3 gravitational head
 amount of work that must be done in order to transport reversibly and isothermally an infinitesimal quantity of water, identical in composition to the soil water, from a pool at a specified elevation and at atmospheric pressure, to a similar pool at the elevation of the point under consideration, divided by the mass of water transported

3.4 matric head
 amount of work that must be done in order to transport reversibly and isothermally an infinitesimal quantity of water, identical in composition to the soil water, from a pool at the elevation and the external gas pressure of the point under consideration, to the soil water at the point under consideration, divided by the mass of water transported

3.5 pneumatic head
 amount of work that must be done in order to transport reversibly and isothermally an infinitesimal quantity of water, identical in composition to the soil water, from a pool at atmospheric pressure and at the elevation of the point under consideration, to a similar pool at the external gas pressure of the point under consideration, divided by the mass of water transported

3.6 pressure head tensiometer head
 sum of the matric and pneumatic heads

NOTE The pneumatic head is assumed to be zero for the purposes of this method. On this basis, the pressure head equals the matric head.

3.7 hydraulic head
 sum of the matric, pneumatic and gravitational heads

4 Symbols

- a height, in centimetres;
 h_a pneumatic head, in centimetres;
 h_h hydraulic head = $h_a + h_g + h_m$, in centimetres;
 h_g gravitational head, in centimetres;
 h_m matric head, in centimetres;

h_p	pressure head = tensiometer head $h_a + h_m$, in centimetres;
i	compartment and tensiometer index;
j	time and measurement interval index;
k	compartment index;
K	unsaturated hydraulic conductivity, in centimetres per day ($\text{cm}\cdot\text{d}^{-1}$);
m	mass, in kilograms;
m_e	mass of soil sample at the end of the test, in kilograms;
t	time, in days (d)
v	soil water volume flux density, in centimetres per day ($\text{cm}\cdot\text{d}^{-1}$);
V	volume, in cubic metres;
z	vertical coordinate, in centimetres;
φ	water content as volume fraction;
ρ_w	density of water, in kilograms per cubic metre.

5 Principle

Undisturbed samples of soil are taken from the field in accordance with ISO 10381-1. Each soil sample is first wetted to near saturation in the laboratory. Then the sample is allowed to dry by evaporation from the top surface; at known times during this period, pressure heads are measured at different depths in the sample using tensiometers, and the mass of the sample is measured. These measurements are continued until air enters any of the tensiometers. This can take a few days to two weeks depending on the type of soil. At the end of the test, after completing these measurements, the sample is dried and weighed, and its water content is calculated for each of the measurement times.

The sample is considered as two or more compartments (sub-samples), one for each tensiometer. For each of the measurement times, the water content of each compartment is calculated from the water content of the whole sample and the tensiometer readings. The soil water-retention characteristic and the unsaturated hydraulic conductivity are calculated from these data using an adaptation^[1] of Wind's evaporation method^[2]. The method treats the soil sample as being homogeneous in its hydraulic properties and assumes one-dimensional flow.

6 Apparatus

6.1 Equipment for sampling undisturbed soil.

Usually metal or plastic sleeves of known dimensions are used, together with equipment to push the sleeves into the soil. Usually the sampling sleeves are used to retain the sample throughout the test, and therefore it is necessary to pre-drill holes for the tensiometers. The dimensions of the soil samples are dependent on the soil type and the purpose of the investigation. The height of a sample shall be less than or equal to its diameter, to prevent the acquisition of redundant data. In most cases a height of 8 cm and a diameter of 10 cm are suitable for stone-free soils.

The height shall be large enough to accommodate 2 to 4 tensiometers. However, larger heights delay the drying of the lower compartments unduly, so that the determination may take too long, and may require an increase in the number of measurement times. The ratio of the diameter to the height should be just above unity, e.g. 10:8, to provide reasonably uniform conditions across the sample without requiring too broad a sample.