

Vägfordon – Dragkopplingar och dragöglor för stela dragstänger –

Del 1: Hållfasthetsprovning för kärror i normalutförande (ISO 12357-1:1999, IDT)

Commercial road vehicles – Drawbar couplings and eyes for rigid drawbars –

Part 1: Strength tests for general cargo centre-axle trailers (ISO 12357-1:1999, IDT)

Den internationella standarden ISO 12357-1:1999 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 12357-1:1999.

The International Standard ISO 12357-1:1999 has the status of a Swedish Standard. This document contains the official English version of ISO 12357-1:1999.

Upplýsingar om **sakinnehållet** i standarden lämnas av SIS, Swedish Standards Institute, telefon 08 - 555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar **allmänna upplýsingar** om svensk och utländsk standard.

Postadress: SIS Förlag AB, 118 80 STOCKHOLM
Telefon: 08 - 555 523 10. *Telefax:* 08 - 555 523 11
E-post: sis.sales@sis.se. *Internet:* www.sis.se

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 12357 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 15, *Interchangeability of components of commercial vehicles and buses*.

Commercial road vehicles — Drawbar couplings and eyes for rigid drawbars — Strength tests

1 Scope

This International Standard specifies the test conditions and strength requirements to be met by drawbar couplings (see ISO 3584) and the corresponding drawbar eyes (see ISO 1102 and ISO 8755) for rigid drawbars, which are provided for use with centre-axle trailers with a technical maximum mass C exceeding 3,5 t (tonnes).

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this International Standard. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 1102, *Commercial road vehicles — Mechanical connections between towing vehicles and trailers — 50 mm drawbar couplings*.

ISO 1176, *Road vehicles — Masses — Vocabulary and codes*.

ISO 3584, *Road vehicles — Mounting of mechanical coupling devices on rear cross members of trucks*.

ISO 8755, *Commercial road vehicles — Mechanical connections between towing vehicles and trailers — 40 mm drawbar coupling*.

3 Terms and definitions

For the purposes of this International Standard, the following terms and definitions apply.

3.1

S-value

mass imposed vertically on the coupling under static conditions by the centre-axle trailer loaded to its maximum design total mass

3.2

centre-axle trailer

towed vehicle equipped with a towing device which cannot move vertically (in relation to the trailer), and in which the axle(s) is(are) positioned close to the centre of gravity of the vehicle (when uniformly loaded) such that only a small static vertical load, not exceeding 10 % of the load corresponding to the maximum design total mass of the trailer or load of 10 kN (whichever is the smaller), is transmitted to the drawing vehicle

4 General test requirements

4.1 The test shall be carried out with drawbar couplings and drawbar eyes having corresponding functional dimensions.

4.2 The strength tests described in this International Standard are static and dynamic tests to be performed on a test bed.

4.3 The fixing arrangements for the drawbar coupling and the drawbar eye on the test bed shall be the same as for its attachment to the vehicle, and shall be in accordance with the manufacturer's fitting instructions.

4.4 Drawbar couplings and drawbar eyes can be tested separately or together.

4.5 Preferably, couplings should be tested in the original condition as designed for road use. At the discretion of the manufacturer and in agreement with the test laboratory, flexible components may be neutralized if this is necessary for the test procedure and if there is no concern about unrealistic influence on the test result.

4.6 Flexible components which appear to be overstressed due to this accelerated test procedure may be replaced during the dynamic test.

4.7 The test loads may be applied by means of special slack-free devices.

5 Determination of D_c - and V -values

5.1 The D_c -value is a comparative value determined by calculation of the longitudinal forces occurring between the towing vehicle and the trailer. It is expressed in kilonewtons, and calculated from the following equation:

$$D_c = g \cdot \frac{T \cdot C}{T + C}$$

where

T is the maximum design total mass, in tonnes, of the towing vehicle, including S (see 3.1), to which the drawbar coupling is to be attached;

C is the mass, in tonnes, transmitted to the ground by the axle or axles of the centre-axle trailer loaded to its maximum design total mass;

g is the acceleration due to gravity:

$$g = 9,81 \text{ m/s}^2$$

Terminology for the different masses shall be in accordance with the definitions in ISO 1176.

5.2 The V -value is a comparative value determined by calculation of the vertical forces occurring between the towing vehicle and the trailer. It is expressed in kilonewtons, and calculated from the following equation:

$$V = a \cdot \frac{x^2}{L^2} \cdot C$$

where

a is an equivalent vertical acceleration in the coupling point, depending on the type of suspension on the rear axle(s) of the towing vehicle, including a constant factor:

$a = 1,8 \text{ m/s}^2$ for vehicles with air suspension (or systems with equivalent damping characteristics),

$a = 2,4 \text{ m/s}^2$ for vehicles with other types of suspension systems;