

**Grafisk teknik - Processtyrning vid framställning
av färgseparationer, provtryck och upplagetryck -
Del 3: Coldset offsettryckning (ISO 12647-3:2005, IDT)**

**Graphic technology – Process control for the
production of half-tone colour separations,
proofs and production prints –
Part 3: Coldset offset lithography on newsprint
(ISO 12647-3:2005, IDT)**

ICS 37.100.01

Språk: engelska

Publicerad: november 2005

Den internationella standarden ISO 12647-3:2005 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 12647-3:2005.

The International Standard ISO 12647-3:2005 has the status of a Swedish Standard. This document contains the official English version of ISO 12647-3:2005.

Upplysningar om **sakinnehållet** i standarden lämnas av SIS, Swedish Standards Institute, telefon 08 - 555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar **allmänna upplysningar** om svensk och utländsk standard.

Postadress: SIS Förlag AB, 118 80 STOCKHOLM
Telefon: 08 - 555 523 10. *Telefax:* 08 - 555 523 11
E-post: sis.sales@sis.se. *Internet:* www.sis.se

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Requirements	2
4.1 General	2
4.2 Data file, colour separation films and printing formes	2
4.3 Proof or production print	4
4.4 Additional requirements for single-colour reproduction and printing	10
5 Test method: tone value and tone value increase of a print	10
Annex A (informative) Tolerances for the secondary colour solids	11
Annex B (informative) Densities of ink set colours	12
Annex C (informative) Characterization data for 26 % and 30 % tone value increase	13
Annex D (informative) Grey balance	14
Bibliography	15

SS-ISO 12647-3:2005

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12647-3 was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

This second edition cancels and replaces the first edition (ISO 12467-3:1998) which has been technically revised, in particular the tone value increase values specified, as borne out by the print characteristic curves of Figure 3. Parameters of all process steps have to be adjusted to achieve these curves; they apply irrespective of whether a positive or a negative acting plate making process is used. The reference to letterpress has been removed completely. Some solid colour CIELAB values have been changed slightly in response to demands from the field.

ISO 12647 consists of the following parts, under the general title *Graphic technology — Process control for the production of half-tone colour separations, proofs and production prints*:

- *Part 1: Parameters and measurement methods*
- *Part 2: Offset lithographic processes*
- *Part 3: Coldset offset lithography on newsprint*
- *Part 4: Publication gravure printing*
- *Part 5: Screen printing*
- *Part 6: Flexographic printing*

Introduction

When producing a half-tone colour reproduction it is important that the colour separator, proofer and printer have previously specified a minimum set of parameters that uniquely define the visual characteristics and other technical properties of the planned print product. Such an agreement enables the correct production of suitable separations (without recourse to "trial-and-error") and subsequent production of off-press or on-press proof prints from these separations whose purpose is to simulate the visual characteristics of the finished print product as closely as possible.

For more information on the technical background refer to ISO 12647-1.

It is the purpose of this part of ISO 12647 to list and explain the minimum set of process parameters required to uniquely define the visual characteristics and related technical properties of a half-tone proof or production print produced by coldset offset lithography on newsprint, or half-tone proof designed to simulate this, from a set of half-tone separation films.

It is a further purpose of this part of ISO 12647 to list values or sets of values of the primary parameters specified in ISO 12647-1 and related technical properties of a half-tone newspaper print or proof produced from a set of half-tone colour separation films. Where deemed useful, secondary parameters are also recommended for specification.

Since non-periodic screening and direct-to-plate techniques are common practice within newspaper printing, information on some of the pertinent parameters has been included.

Graphic technology — Process control for the production of half-tone colour separations, proofs and production prints —

Part 3: Coldset offset lithography on newsprint

1 Scope

This part of ISO 12647 specifies a number of process parameters and their values to be applied when preparing colour separations for newspaper single or four-colour printing and proofing. The parameters and values are chosen in consideration of the complete process, covering the process stages: “colour separation”, “film setting”, “making of the printing forme”, “proof production” and “production printing”.

This part of ISO 12647 is applicable:

- to coldset offset proof and production printing and off-press proof printing processes on newsprint that use colour separation films rather than digital data;
- by analogy to press printing from printing surfaces produced by direct imaging methods and the corresponding proof printing processes.
- It is not applicable:
- to line screens and non-periodic screens although certain parameters given can be applied by analogy. In particular, the tone value increases specified, apply directly because they refer to control patches that contain periodic screen half-tones;
- to flexo and letterpress production printing although a number of parameters can be applied by analogy.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5-3, *Photography — Density measurements — Part 3: Spectral conditions*

ISO 8254-1, *Paper and board — Measurement of specular gloss — Part 1: 75 degree gloss with a converging beam, TAPPI method*

ISO 12647-1:2004, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 1: Parameters and measurement methods*

ISO 15930-4, *Graphic technology — Prepress digital data exchange using PDF — Part 4: Complete exchange of CMYK and spot colour printing data using PDF 1.4 (PDF/X-1a)*

ISO 15930-6, *Graphic technology — Prepress digital data exchange using PDF — Part 6: Complete exchange of printing data suitable for colour-managed workflows using PDF 1.4 (PDF/X-3)*

SS-ISO 12647-3:2005

3 Terms and definitions

For the purposes of this document the definitions given in ISO 12647-1 and the following apply.

3.1

coldset offset lithography

method of offset lithographic printing where the inks set ("dry") primarily by absorption into the print substrate

4 Requirements

4.1 General

The following subclauses are arranged according to the order set out in ISO 12647-1. They also depend on it for the definition of the parameters and test methods.

If data files or colour separation film sets are supplied for printing they should be accompanied by a proof print that simulates the intended production printing condition to a sufficient degree. This fact shall be verifiable by measuring a well-known control strip or a similar control device that is printed on the proof print along with the subject.

4.2 Data file, colour separation films and printing formes

4.2.1 General

Electronic data should be delivered as PDF/X-1 or PDF/X-3 data files as defined in ISO 15930-4 or ISO 15930-6. Where film is supplied, the intended receiver of the film shall specify the tone value curve for which the film shall be prepared.

4.2.2 Film or printing forme quality

The tone values for film and printing formes shall be adjusted such that, for all primary colours, the tone value increase from data to paper conforms to one of the two curves specified in 4.3.4.1. Within an ink set, the printed characteristics of all the primary printing ink colours shall conform to the same tone value curve.

NOTE 1 Data sender and receiver need to agree on which of the two curves specified in Table 5 and shown in Figure 3 will be used. The choice of the appropriate curve for common use is generally made by national or international trade associations.

NOTE 2 Methods for tone value adjustments include setting of the RIP look-up table, choosing a suitable blanket type, suitable setting of the plate to blanket pressure and adjustment of the ink rheology.

EXAMPLE 1 Conventional plate making with negative film produces a tone value increase of 33 % in the mid tone. In order to achieve 26 %, the RIP look-up table was adjusted by - 4 % and the choice of a different ink generated a 3 % lower tone value increase. These two adjustments lowered the tone value increase to 26 %. If 30 % is to be achieved, less adjustments are necessary to reach the correct tone value increase.

EXAMPLE 2 With a given CTP system the tone value increase was found to be 22 %. An increased blanket to plate pressure yielded + 2 %, the remaining + 2 % were introduced at the RIP look-up table; 26 % tone value increase was achieved.

The resolution of the film or plate setter should be set to 500 cm^{-1} and shall not be set to a lower value than 472 cm^{-1} in order to assure a sufficient number of generated tone value steps.

The deviation of tone values over the complete printing forme shall not exceed $\pm 2 \%$. The deviation range of the measuring device (densitometer or camera-based device) shall be added to this value.