

# SVENSK STANDARD

## SS-EN 1993-1-8:2005/AC:2007

Fastställt/Approved: 2007-09-12

Publicerad/Published: 2008-11-03

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 91.010.30; 91.070.03; 91.070.50; 91.070.60; 91.080.10

---

### **Eurokod 3: Dimensionering av stålkonstruktioner – Del 1-8: Dimensionering av knutpunkter och förband**

### **Eurocode 3: Design of steel structures – Part 1-8 : Design of joints**



SWEDISH  
STANDARDS  
INSTITUTE

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.  
E-mail: [sis.sales@sis.se](mailto:sis.sales@sis.se) Internet: [www.sis.se](http://www.sis.se)

Europastandarden EN 1993-1-8:2005/AC:2005 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 1993-1-8:2005/AC:2005.

The European Standard EN 1993-1-8:2005/AC:2005 has the status of a Swedish Standard. This document contains the official English version of EN 1993-1-8:2005/AC:2005.



EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 1993-1-8:2005/AC**

December 2005

---

ICS 91.010.30

English version

Eurocode 3: Design of steel structures - Part 1-8: Design of joints

Eurocode 3: Calcul des structures en acier  
- Partie 1-8: Calcul des assemblages

Eurocode 3: Bemessung und Konstruktion  
von Stahlbauten - Teil 1-8: Bemessung von  
Anschlüssen

This corrigendum becomes effective on 21 December 2005 for incorporation in the three official language versions of the EN.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: rue de Stassart, 36 B-1050 Brussels**

## English version

The corrections are to add a 'P' after the clause number and change "should" to "shall" where appropriate. The corrections are underlined as shown.

### 2.2 General requirements

- (1)P All joints shall have a design resistance such that the structure is capable of satisfying all the basic design requirements given in this Standard and in EN 1993-1-1.
- (3)P Joints subject to fatigue shall also satisfy the principles given in EN 1993-1-9.

### 2.3 Applied forces and moments

- (1)P The forces and moments applied to joints at the ultimate limit state shall be determined according to the principles in EN 1993-1-1.

### 2.5 Design assumptions

- (1)P Joints shall be designed on the basis of a realistic assumption of the distribution of internal forces and moments. The following assumptions shall be used to determine the distribution of forces:
- (d) the assumed distribution of internal forces shall be realistic with regard to relative stiffnesses within the joint,

### 4.1 General

- (2)P Welds subject to fatigue shall also satisfy the principles given in EN 1993-1-9.

#### 6.4.1 General

- (1)P In the case of rigid plastic global analysis, a joint at a plastic hinge location shall have sufficient rotation capacity.

#### 7.2.1 General

- (1)P The design values of the internal axial forces both in the brace members and in the chords at the ultimate limit state shall not exceed the design resistances of the members determined from EN 1993-1-1.
- (2)P The design values of the internal axial forces in the brace members at the ultimate limit state shall also not exceed the design resistances of the joints given in 7.4, 7.5, 7.6 or 7.7 as appropriate.

#### 7.3.1 Design resistance

- (1)P The welds connecting the brace members to the chords shall be designed to have sufficient resistance to allow for non-uniform stress-distributions and sufficient deformation capacity to allow for redistribution of bending moments.

#### 7.4.2 Uniplanar joints

- (1)P In brace member connections subject only to axial forces, the design internal axial force  $N_{i,Ed}$  shall not exceed the design axial resistance of the welded joint  $N_{i,Rd}$  obtained from Table 7.2, Table 7.3 or Table 7.4 as appropriate.