

# SVENSK STANDARD

## SS-ISO 12640-3:2007

Fastställt/Approved: 2007-11-21

Publicerad/Published: 2007-12-13

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 37.100.99

---

### **Grafisk teknik – Överföring av prepressdata – Del 3: CIELAB standarddata för färgbilder (CIELAB/SCID) (ISO 12640-3:2007, IDT)**

### **Graphic technology – Prepress digital data exchange – Part 3: CIELAB standard colour image data (CIELAB/SCID) (ISO 12640-3:2007, IDT)**

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-63932>



SWEDISH  
STANDARDS  
INSTITUTE

# Hitta rätt produkt och ett leveranssätt som passar dig

## Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

## Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på. På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

## Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

## Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på [sis.se](http://sis.se) och ger dig en bra bild över hur olika produkter hör ihop.

## Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

# Find the right product and the type of delivery that suits you

## Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

## Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

## Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

## Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at [sis.se](http://sis.se), provide an overview of which publications belong together.

## Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Den internationella standarden ISO 12640-3:2007 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 12640-3:2007.

The International Standard ISO 12640-3:2007 has the status of a Swedish Standard. This document contains the official English version of ISO 12640-3:2007 .

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00.

Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.

E-mail: [sis.sales@sis.se](mailto:sis.sales@sis.se) Internet: [www.sis.se](http://www.sis.se)

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>v</b>
<b>Introduction</b> .....	<b>vi</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Requirements</b> .....	<b>2</b>
<b>5 Data description and definition</b> .....	<b>3</b>
<b>5.1 Data set definition</b> .....	<b>3</b>
<b>5.2 Colour encoding used in this part of ISO 12640</b> .....	<b>3</b>
<b>5.3 Natural images</b> .....	<b>4</b>
<b>5.4 Synthetic images</b> .....	<b>7</b>
<b>6 Electronic data</b> .....	<b>11</b>
<b>6.1 Image file characteristics</b> .....	<b>11</b>
<b>6.2 Image file formats</b> .....	<b>11</b>
<b>Annex A (normative) Guidance for use of digital data</b> .....	<b>12</b>
<b>Annex B (informative) Definition of the reference colour gamut</b> .....	<b>14</b>
<b>Annex C (normative) Check-sum data</b> .....	<b>21</b>
<b>Annex D (informative) Typical TIFF file headers used for image data</b> .....	<b>22</b>
<b>Annex E (informative) Text insertion</b> .....	<b>24</b>
<b>Annex F (informative) Histogram and gamut plots</b> .....	<b>25</b>
<b>Annex G (informative) CIELAB values in colour charts</b> .....	<b>29</b>
<b>Bibliography</b> .....	<b>33</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12640-3 was prepared by Technical Committee ISO/TC 130, *Graphic technology*.

ISO 12640 consists of the following parts, under the general title *Graphic technology — Prepress digital data exchange*:

- *Part 1: CMYK standard colour image data (CMYK/SCID)*
- *Part 2: XYZ/sRGB encoded standard colour image data (XYZ/SCID)*
- *Part 3: CIELAB standard colour image data (CIELAB/SCID)*

The following parts are under preparation:

- *Part 4: Wide gamut display-referred standard colour image data (TBDencoded/SCID)*
- *Part 5: Scene-referred standard colour image data (RIMM/SCID)*

## Introduction

### 0.1 Need for standard digital test images

Standard test images provide a set of data that can be used for any of the following tasks:

- evaluating the colour reproduction of imaging systems;
- evaluating colour image output devices;
- evaluating the effect of image processing algorithms applied to the images;
- evaluating the coding technologies necessary for the storage and transmission of high-definition image data.

Because they exist as standard, well-defined, high-quality image data sets, typical of the range of image content commonly encountered, they enable users to be confident that the images will produce good quality reproductions, if properly rendered, and that they provide a reasonable test of the evaluation task being undertaken. No limited set of images can fully test any system, but the sets provided give as reasonable a test as can be expected from a limited image set. Furthermore, the existence of a standard image data set enables users in different locations to produce comparisons without the need to exchange images prior to reproduction.

However, different applications require that the standard image data be provided in different image states using different image encodings (see ISO 22028-1). The user needs to select those appropriate to the evaluation task being undertaken. Whilst transformation of the image data to another image state is always possible, there is, in general, no agreement amongst experts as to how this is best done. Thus, it has been considered preferable to provide data in three different image states in the various parts of ISO 12640.

Part 1 of ISO 12640 provides a set of 8-bits-per-channel data that is defined in terms of CMYK dot percentages. The colours resulting from reproduction of CMYK data are strictly defined only at the time of printing and, as such, the data are only applicable to evaluation of CMYK printing applications. Transformations to other image states and colour encodings are not necessarily well defined. In fact, the data might not even be useful for CMYK printing processes different from those typically found in traditional graphic arts applications as the image data are defined to produce “pleasing” images when reproduced on systems using “typical” inks and producing “typical” tone value rendering. Printing systems that use inks of a distinctly different colour, or produce a very different tone value rendering, will not reproduce them as pleasing images without a well-defined colour transformation. Moreover, with a bit depth of only 8 bits per channel, any colour transformation employed will probably introduce artefacts.

Part 2 of ISO 12640 provides a set of test image data encoded both as XYZ tristimulus values with a depth of 16 bits per channel and as sRGB (defined in IEC 61966-2-1) with a bit depth of 8 bits per channel. (The higher bit depth for the XYZ encoding is necessary because of the perceptual non-uniformity of the XYZ colour space.) Both sets of data are optimized for viewing on a reference sRGB CRT display in the reference sRGB viewing environment, and relative to CIE standard illuminant D65 for which the XYZ values were computed. The images are mainly designed to be used on systems utilizing sRGB as the reference encoding, and as such are mainly applicable to the consumer market and those systems for which the colour monitor is the “hub” device. Although such systems are used for some applications in the graphic arts industry, sRGB is by no means the most common image encoding. Furthermore, a particular drawback is the fact that the sRGB colour gamut is quite different in shape than the colour gamut of typical offset printing. This difference can necessitate fairly aggressive colour re-rendering to produce optimal prints from sRGB image data.

In order to be useful for applications where large, print-referred output gamuts are encountered, common in graphic technology and photography, it was felt that it would be desirable to produce an image set in which some colours are permitted to be encoded close to the boundary of the full colour gamut attainable with

surface colours. Furthermore, from the perspective of colour management it is advantageous if the images are referenced to illuminant D50, which is the predominant reference illuminant used in graphic arts and photography, both for viewing and measurement. For this reason it has also become the predominant reference illuminant for most colour management applications.

The purpose of this part of ISO 12640 is, therefore, to provide a test image data set with a large colour gamut related to illuminant D50. The bit depth of the natural images is 16 bits per channel, while the colour charts and vignettes are 8 bits per channel.

## 0.2 Definition of the reference colour gamut

The reference colour gamut defined for this part of ISO 12640 originated from three quite separate sources. However, it was noted that there was considerable similarity between the three. One definition came from work within ISO/TC 130 itself, and this arose by consideration of various sets of published data, which together were taken to define the colour gamut of surface colours. The other definitions arose from work within Hewlett-Packard, which was focused on the colour gamuts obtainable by printing, and that of a group of German photographic printing experts. The similarity of these led to the conclusion that it would be desirable to reconcile them into a single gamut that would be taken as the reference colour gamut for this part of ISO 12640. Full details of the reference colour gamut and its derivation are given in Annex B.

## 0.3 Characteristics of the test images

The performance of any colour reproduction system is normally evaluated both subjectively (by viewing the final output image) and objectively (by measurement of control elements). This requirement dictated that the test images include both natural scenes (pictures) and synthetic images (colour charts and colour vignettes). Because the results of subjective image evaluation are strongly affected by the image content, it was important to ensure that the natural images were of high quality and contained diverse subject matter. However, by requiring images to look natural, it is difficult within a single, relatively small sample set to produce elements in the scene that contain the subtle colour differences required in such test images and that cover the full reference colour gamut defined. It is also important to have some images that contain subtle differences in near-neutral colours. Thus, while most images contain colours that extend to the gamut boundary, this is often only for a limited range of hues in each image. The full reference colour gamut can only be explored by utilizing the synthetic colour chart.

A survey was conducted of all ISO/TC 130 member countries to identify desirable image content and to solicit submission of suitable images for consideration. The image set that resulted consists of eight natural images, eight colour charts and two colour vignettes. The natural images include flesh tones, images with detail in the extreme highlights or shadows, neutral colours, brown and wood-tone colours that are often difficult to reproduce, memory colours, complicated geometric shapes, fine detail, and highlight and shadow vignettes. The colour charts and colour vignettes show the reference colour gamut (in CIE Lab colour space) in cross-sections for 16 and 8 hue angles, respectively.

## 0.4 File format of the digital test images

All of the images consist of pixel interleaved data ( $L^*$  then  $a^*$  then  $b^*$ ) with the data origin at the upper left of the image, as viewed naturally, and organized by rows. These data are available as individual files, which are a normative part of this part of this part of ISO 12640. The image file format is as specified in ISO 12639:2004, Annex H, with BitsPerSample set to 16, 16, 16. The images can be imported and manipulated as necessary by a wide variety of imaging software tools and platforms commonly in general use in the industry. (See Annex D for details of the TIFF header.)

All colour charts and vignettes consist of files in Adobe® PDF format.

**SS-ISO 12640-3:2007 (E)**

# Graphic technology — Prepress digital data exchange —

## Part 3: CIELAB standard colour image data (CIELAB/SCID)

### 1 Scope

This part of ISO 12640 specifies a set of standard large gamut colour images (encoded as 16-bit CIELAB digital data) that can be used for the evaluation of changes in image quality during coding, image processing (including transformation, compression and decompression), displaying on a colour monitor and printing. These images can be used for research, testing and assessing of output systems such as printers, colour management systems and colour profiles.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3664, *Viewing conditions — Graphic technology and photography*

ISO 12639:2004, *Graphic technology — Prepress digital data exchange — Tag image file format for image technology (TIFF/IT)*

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ISO 22028-1, *Photography and graphic technology — Extended colour encodings for digital image storage, manipulation and interchange — Part 1: Architecture and requirements*

CIE Publication 15:2004, *Colorimetry*

ICC.1:2004-04, *Image technology colour management — Architecture, profile format, and data structure*

*TIFF, Revision 6.0 Final*, Aldus Corporation (now Adobe Systems Incorporated), June 3, 1992

*PDF Reference: Adobe Portable Document Format, Version 1.4* 3rd edn., Adobe Systems Incorporated, (ISBN 0-201-75839-3)

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

##### check sum

sum of the digits in a file that can be used to check if a file has been transferred properly

NOTE Often, only the least significant bits are summed.

## SS-ISO 12640-3:2007 (E)

**3.2 colour gamut**  
solid in a colour space, consisting of all those colours that are present in a specific scene, artwork, photograph, photomechanical or other reproduction; or are capable of being created using a particular output device and/or medium

[ISO 12231]

**3.3 colour sequence**  
order in which the colours are stored in a data file

**3.4 colour space**  
geometric representation of colours in space, usually of three dimensions

[CIE Publication 17-1987 (845-03-25)]

**3.5 colour value**  
numeric values associated with each of the pixels

**3.6 data range**  
range of integers for a given variable in between a minimal and maximal value

**3.7 global colour change**  
change to the colours in an image (often selectively by colour region) applied consistently to all parts of the image

NOTE This is in contrast to a local colour change where selected spatial areas of an image are changed separately from the rest of the image area.

**3.8 orientation**  
specifies the origin and direction of the first line of data with respect to the image content as viewed by the end user

NOTE The codes used to specify orientation are contained in ISO 12639:2004.

**3.9 pixel**  
smallest discrete picture element in a digital image file

**3.10 pixel interleaving**  
colour data organized such that the  $L^*$ ,  $a^*$  and  $b^*$  colour space values for one pixel are followed by the same sequence of colour values for the next pixel; the specific order of colour components is determined by the ColorSequence tag as defined in ISO 12639

NOTE Other forms of colour data interleaving are line and plane.

## 4 Requirements

This part of ISO 12640 consists of the images contained in the 18 image data files which are part of this part of ISO 12640. Their file names are listed in Table 4. The image characteristics of these data are described in Clause 5 and the electronic data structure in Clause 6.

## 5 Data description and definition

### 5.1 Data set definition

The set of standard colour image data consists of eight natural (photographed) images and ten synthetic images created digitally on a computer. The synthetic images consist of eight colour charts consisting of various patches, each 10 mm square, and two colour vignettes. The natural images are identified as N1 to N8, and each of them also has a descriptive name derived from the picture content (e.g. bride and groom). The synthetic images are identified as CC1 to CC8, CV1 and CV2.

The images are identified by the designation CIELAB/SCID. The co-ordinates of the text insertion are provided in Annex E.

**NOTE** The image set defined in this part of ISO 12640 is based on the large gamut defined in Annex B. Image sets contained in other parts of ISO 12640 are based on different gamuts and can be more suitable for use in evaluation of other applications.

### 5.2 Colour encoding used in this part of ISO 12640

#### 5.2.1 Image data encoding

The image data encoding is defined in accordance with ISO 22028-1 requirements as follows.

The image data are the desired CIELAB colorimetry as defined by CIE Publication 15, and measured in accordance with ISO 13655, of reproductions of the images on the reference medium, with the reference medium white point selected as the colour space white point. The image data are output-referred, having been rendered to the reference medium of the ICC.1:2004-04 perceptual rendering intent, which is defined as a hypothetical print on a substrate specified to have a neutral reflectance of 89 % (the reference medium white point) and the darkest printable colour on this medium is assumed to have a neutral reflectance of 0,347 31 % of the substrate reflectance (the reference medium black point). The rendering target colour gamut for the reference medium is specified in Annex B. The reference viewing environment is based on standard viewing condition P2, as specified for graphic arts and photography in ISO 3664, but extended in the following way: the surfaces immediately surrounding the image are assumed to be a uniform matt grey with a reflectance of 20 %. The reference viewing environment is also assumed to have a viewing flare of 0,75 % of the luminance of the reference white. The CIELAB image data are encoded as specified in 5.2.3 and 5.2.4.

#### 5.2.2 Image data arrangement

The image data are pixel-interleaved in the colour sequence of  $L^*$  then  $a^*$  then  $b^*$  (16 bits) for the natural images and  $L^*$  then  $a^*$  then  $b^*$  (8 bits) for the colour charts and the vignettes. The arrangement of data follows the scanning of each image from the upper left corner to the upper right, then moving to the next lower horizontal line. The resolution is 12 pixels/mm for every natural image.

#### 5.2.3 CIELAB image data (16 bits per channel)

The CIELAB data for the natural images are encoded as 16-bit integers per channel, derived by multiplying the  $L^*$ ,  $a^*$  and  $b^*$  values for each pixel with the corresponding value for the data range.

$$\begin{aligned}
 L^*_{16\text{bit}} &= \text{round} \left( 65\,535 \times \frac{L^*}{100} \right) \\
 a^*_{16\text{bit}} &= \text{round} (256 \times a^*) \\
 b^*_{16\text{bit}} &= \text{round} (256 \times b^*)
 \end{aligned} \tag{1}$$

where  $L^*_{16\text{bit}}$ ,  $a^*_{16\text{bit}}$  and  $b^*_{16\text{bit}}$  represent normalised 16-bit values of  $L^*$ ,  $a^*$  and  $b^*$ .