

# SVENSK STANDARD

## SS-ISO 3739-3:2008

Fastställt/Approved: 2008-02-08

Publicerad/Published: 2008-03-10

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 53.060

---

### **Industridäck och -fälgar – Del 3: Fälgar (ISO 3739-3:2008, IDT)**

### **Industrial tyres and rims – Part 3: Rims (ISO 3739-3:2008, IDT)**

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-64983>

# Hitta rätt produkt och ett leveranssätt som passar dig

## Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

## Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på. På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

## Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

## Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på [sis.se](http://sis.se) och ger dig en bra bild över hur olika produkter hör ihop.

## Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

# Find the right product and the type of delivery that suits you

## Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

## Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

## Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

## Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at [sis.se](http://sis.se), provide an overview of which publications belong together.

## Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Den internationella standarden ISO 3739-3:2008 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 3739-3:2008.

The International Standard ISO 3739-3:2008 has the status of a Swedish Standard. This document contains the official English version of ISO 3739-3:2008.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00.

Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.

E-mail: [sis.sales@sis.se](mailto:sis.sales@sis.se) Internet: [www.sis.se](http://www.sis.se)

| <b>Contents</b>  |                                      | Page       |
|--|--------------------------------------|------------|
| <b>Foreword</b> .....  |                                      | <b>iii</b> |
| <b>1</b>   | <b>Scope</b> .....                   | <b>1</b>   |
| <b>2</b>   | <b>Normative references</b> .....    | <b>1</b>   |
| <b>3</b>   | <b>Terms and definitions</b> .....   | <b>1</b>   |
| <b>4</b>   | <b>Designation and marking</b> ..... | <b>1</b>   |
| <b>5</b>   | <b>Rim profiles</b> .....            | <b>1</b>   |
| <b>Annex A (normative) Size range of existing rims</b> ..... |                                      | <b>4</b>   |
| <b>Bibliography</b> .....                                    |                                      | <b>8</b>   |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3739-3 was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 7, *Industrial tyres and rims*.

This second edition cancels and replaces the first edition (ISO 3739-3:1995), which has been technically revised.

ISO 3739 consists of the following parts, under the general title *Industrial tyres and rims*:

- *Part 1: Pneumatic tyres (metric series) on 5° tapered or flat base rims — Designation, dimensions and marking*
- *Part 2: Pneumatic tyres (metric series) on 5° tapered or flat base rims — Load ratings*
- *Part 3: Rims*



# Industrial tyres and rims —

## Part 3: Rims

### 1 Scope

This part of ISO 3739 specifies the main requirements, including size designation and marking, of 5° tapered and flat base rims, with diameters not exceeding rim diameter code 15 for pneumatic tyres and for solid tyres for pneumatic tyre rims, primarily intended for industrial vehicles for use on prepared surfaces.

ISO 3739-1 gives the designation, dimensions and marking, and ISO 3739-2 gives the load ratings, of pneumatic tyres (metric series). ISO 10499-1 covers the designation, dimensions and marking of rubber solid tyres (metric series) for pneumatic tyre rims.

Rim dimensions are specified for size and contour only. The tyre and wheel/rim manufacturers are consulted for confirmation of the suitability of the tyre/rim combinations, particularly with regard to rim profile and wheel strength.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3911:2004, *Wheels and rims for pneumatic tyres — Vocabulary, designation and marking*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3911 apply.

### 4 Designation and marking

Rim designation and marking shall be in accordance with ISO 3911:2004, Annexes A and B.

### 5 Rim profiles

As far as possible, rims shown in Tables 1 and 2 should be used for the metric series of tyres; only if absolutely necessary should new profiles be considered.

All rim profiles shall be independent from the rim diameter, i.e. no change of profile shall be related to the diameter.

The flange widths include edge radius. The portion of the flange beyond the minimum width shall be equal to, or less than, the highest point of the flange.

The rims shall have a 5° tapered bead seat.

The specified rim diameters, *D*, shall be as given in Table 3.

**Table 1 — Index of one-piece and multi-piece rims**

| Rim width code | Existing rims            | Rim profile details are indicated in |               |
|----------------|--------------------------|--------------------------------------|---------------|
|                |                          | Figures                              | Tables        |
| 2.50           | 4 - 2.50 C               | A.1, A.2                             | A.1, A.2      |
|                | 4 × 2.50 C               |                                      |               |
|                | 8 - 2.50 C               |                                      |               |
|                | 8 × 2.50 C               |                                      |               |
| 3.00           | 8 - 3.00 D               | A.3                                  | A.3           |
| 3.25           | 4 - 3.25 I               | A.1                                  | A.1           |
|                | 6 - 3.25 I               |                                      |               |
|                | 8 - 3.25 I               |                                      |               |
| 4.0            | 9 - 4.00 E               | A.1, A.2, A.3                        | A.1, A.2, A.3 |
|                | 9 × 4.00 E               |                                      |               |
| 5.0            | 10 - 5.00 F              | A.1                                  | A.1           |
|                | 10 × 5.00 F              |                                      |               |
|                | 12 IL - 5.00 S           |                                      |               |
|                | 15 TB - 5.0 <sup>a</sup> | A.4                                  | A.4           |
| 6.0            | 9 - 6.00 E               | A.3                                  | A.3           |
| 6.5            | 10 - 6.50 F              | A.1, A.3                             | A.1, A.3      |
|                | 15 - B 6.5               | A.4                                  | A.4           |
|                | 15 - 6.5 <sup>a</sup>    |                                      |               |
| 8.0            | 12 - 8.00 G              | A.3                                  | A.3           |
|                | 15 - 8.0                 | A.4                                  | A.4           |
|                | 15 - B 8.0               |                                      |               |

<sup>a</sup> Rims with identical designation but different dimensions exist.

**Table 2 — Index of drop centre rims**

| Rim width code | Reference standard | Nominal rim diameter code |   |
|----------------|--------------------|---------------------------|---|
|                |                    | 8                         | 9 |
| 2.50 C         | ISO 4251-3         | X                         |   |
| 4.00 E         | ISO 4251-3         |                           | X |