

SVENSK STANDARD

SS-ISO 17572-1:2009

Fastställt/Approved: 2009-03-30

Publicerad/Published: 2009-05-05

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 03.220.01; 35.240.60

Vägtrafikinformatik – Platsreferenser för geografiska databaser –

Del 1: Allmänna krav och begreppsmodell

(ISO 17572-1:2008, IDT)

Intelligent transport systems (ITS) – Location referencing for geographic databases –

Part 1: General requirements and conceptual model

(ISO 17572-1:2008, IDT)



SWEDISH
STANDARDS
INSTITUTE

Hitta rätt produkt och ett leveranssätt som passar dig

Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på.

På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på sis.se och ger dig en bra bild över hur olika produkter hör ihop.

Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

Find the right product and the type of delivery that suits you

Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at sis.se, provide an overview of which publications belong together.

Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Den internationella standarden ISO 17572-1:2008 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 17572-1:2008.

The International Standard ISO 17572-1:2008 has the status of a Swedish Standard. This document contains the official English version of ISO 17572-1:2008.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00.

Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.

E-mail: sis.sales@sis.se Internet: www.sis.se

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Terms and definitions	2
2.1	General terms	2
2.2	UML expressions for diagrams	7
3	Abbreviated terms	8
4	Objectives and requirements for a location referencing method	9
4.1	Objectives for an optimal location referencing method	9
4.2	Requirements of the location referencing method	9
5	Conceptual data model for location referencing methods	11
5.1	Role of conceptual model	11
5.2	Components of conceptual model	11
5.3	Description of the conceptual model	11
5.4	Location categories	12
5.5	Conceptual model of road network	13
5.6	Conceptual model of area locations	14
Annex A (informative) Inventory of location referencing methods		16
Annex B (informative) Examples of location referencing methods in use (mapping to conceptual data model for location referencing systems)		20
Annex C (informative) Description of UML expression elements		22
Annex D (informative) Comparison of definitions with TC 211		24
Annex E (informative) Introduction to the TPEG physical format		28
Bibliography		41

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17572-1 was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*.

ISO 17572 consists of the following parts, under the general title *Intelligent transport systems (ITS) — Location referencing for geographic databases*:

- *Part 1: General requirements and conceptual model*
- *Part 2: Pre-coded location references (pre-coded profile)*
- *Part 3: Dynamic location references (dynamic profile)*

Introduction

A Location Reference (LR) is a unique identification of a geographic object. In a digital world, a real-world geographic object can be represented by a feature in a geographic database. An example of a commonly known Location Reference is a postal address of a house. Examples of object instances include a particular exit ramp on a particular motorway, a road junction or a hotel. For efficiency reasons, Location References are often coded. This is especially significant if the Location Reference is used to define the location for information about various objects between different systems. For Intelligent Transport Systems (ITS), many different types of real-world objects will be addressed. Amongst these, Location Referencing of the road network, or components thereof, is a particular focus.

Communication of a Location Reference for specific geographic phenomena, corresponding to objects in geographic databases, in a standard, unambiguous manner is a vital part of an integrated ITS system in which different applications and sources of geographic data will be used. Location Referencing Methods (LRM, methods of referencing object instances) differ by applications, by the data model used to create the database, or by the enforced object referencing imposed by the specific mapping system used to create and store the database. A standard Location Referencing Method allows for a common and unambiguous identification of object instances representing the same geographic phenomena in different geographic databases produced by different vendors, for varied applications, and operating on multiple hardware/software platforms. If ITS applications using digital map databases are to become widespread, data reference across various applications and systems must be possible. Information prepared on one system, such as traffic messages, must be interpretable by all receiving systems. A standard method to refer to specific object instances is essential to achieving such objectives.

Japan, Korea, Australia, Canada, the US and European ITS bodies are all supporting activities of Location Referencing. Japan has developed a Link Specification for VICS. In Europe, the RDS-TMC traffic messaging system has been developed. In addition, methods have been developed and refined in the EVIDENCE and AGORA projects based on intersections identified by geographic coordinates and other intersection descriptors. In the US, standards for Location Referencing have been developed to accommodate several different Location Referencing Methods.

This International Standard provides specifications for location referencing for ITS systems (although other committees or standardization bodies may subsequently consider extending it to a more generic context). In addition, this edition does not deal with public transport location referencing; this issue will be dealt with in a later edition.

Intelligent transport systems (ITS) — Location referencing for geographic databases —

Part 1: General requirements and conceptual model

1 Scope

This International Standard specifies Location Referencing Methods (LRM) that describe locations in the context of geographic databases and will be used to locate transport-related phenomena in an encoder system as well as in the decoder side. This International Standard defines what is meant by such objects, and describes the reference in detail, including whether or not components of the reference are mandatory or optional, and their characteristics.

This International Standard specifies two different LRMs:

- pre-coded location references (pre-coded profile);
- dynamic location references (dynamic profile).

This International Standard does not define a physical format for implementing the LRM. However, the requirements for physical formats are defined.

This International Standard does not define details of the Location Referencing System (LRS), i.e. how the LRMs are to be implemented in software, hardware, or processes.

This part of ISO 17572 specifies the following general LRM related sections:

- requirements of a Location Referencing Method;
- conceptual Data Model for Location Referencing Methods;
- inventory of Location Referencing Methods;
- examples of Conceptual Data Model Use;
- description of selected UML Elements;
- comparison of Definitions with ISO/TC 211;
- introduction to the TPEG Physical Format.

It is consistent with other International Standards developed by ISO/TC 204 such as ISO 14825, *Intelligent transport systems — Geographic Data Files (GDF) — Overall data specification*.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1 General terms ¹⁾

2.1.1

accuracy

measure of closeness of results of observations, computations or estimates to the true values or the values accepted as being true

2.1.2

area

two-dimensional, geographical region on the surface of the earth

NOTE An area can be represented as an implicit area or an explicit area.

2.1.3

area location

two-dimensional location, representing a geographical region on the surface of the earth

2.1.4

attribute

characteristic property of an entity like a real-world feature

NOTE It allows the identification of that feature by the sum of its attributes. An attribute has a defined type and contains a value. Attributes can be either simple, i.e. consisting of one atomic value, or composite (see composite attribute).

2.1.5

coordinate

one of an ordered set of N numbers designating the position of a point in N -dimensional space

2.1.6

complex intersection

intersection that consists at least of two or more junctions and one or more road elements

2.1.7

composite attribute**complex attribute**

attribute consisting of two or more atomic values and/or attributes

2.1.8

datum

set of parameters and control points used to accurately define the three-dimensional shape of the earth

NOTE The corresponding datum is the basis for a planar coordinate reference system.

2.1.9

descriptor

characteristic of a geographic object, usually stored in an attribute

EXAMPLE Road names or road numbers.

¹⁾ As part of the general intent to harmonize this International Standard with the ISO/TC 211 family of Geographic Information Systems standards, a comparison of terms and definitions between this International Standard and ISO/TC 211 standards is included as Annex D.

2.1.10**digital map database**

structured set of digital and alphanumeric data portraying geographic locations and relationships of spatial features

NOTE Typically, such structures represent, but are not limited to, the digital form of hard copy maps. For example, drawings may be imported into a Geographic Information System (GIS) and considered as a form of digital map.

2.1.11**dynamic location reference**

location reference generated on-the-fly based on geographic properties in a digital map database

2.1.12**explicit area**

two-dimensional face on the surface of the earth, with a specified outline either being a simple geometric figure or an irregular outline/polygon

2.1.13**face**

two-dimensional element bounded by a closed sequence of edges not intersecting themselves

NOTE The face is the atomic two-dimensional element.

2.1.14**implicit area**

selection of road segments to be referenced belonging to a certain area (subnetwork)

NOTE One implicit area can be built up of multiple subnetworks that are geographically connected.

2.1.15**international terrestrial reference frame****ITRF**

realization of the ITRS

NOTE The ITRF94 reference frame is consistent with WGS84 at the 5 cm level, and therefore is equivalent to WGS84 for ITS applications.

2.1.16**international terrestrial reference system****ITRS**

reference system for the earth derived from precise and accurate space geodesy measurements, not restricted to GPS Doppler measurements, which is periodically tracked and revised by the international earth rotation service

2.1.17**intersection**

crossing and/or connection of two or more roads

NOTE 1 In GDF, an intersection is a Level 2 representation of a junction which bounds a road or a ferry. It is a complex feature, composed of one or more Level 1 junctions, road elements and enclosed traffic areas. The definition is different from GDF because the location referencing system refers to real-world objects rather than a database definition as defined in GDF.

NOTE 2 Crossings can be at-grade or grade-separated. Crossings that are grade-separated where no connection between the road segments exist, are excluded from this definition.

2.1.18**junction**

elementary element in the road network, connecting two or more road elements

NOTE In GDF terms, it is a Level 1 feature that bounds a road element or ferry connection. Junctions that represent real crossings are at least trivalent (having three roads connected). A bivalent junction may only be defined in case an attribute change occurs along the road (e.g. road name change). A junction is also coded at the end of a dead-end road, to terminate it.

2.1.19**linear location**

location that has a one-dimensional character

EXAMPLE A road segment.

2.1.20**link****edge**

direct topological connection between two nodes that has a unique link id in a given digital map database

NOTE A link may contain additional intermediate coordinates (shape points) to better represent the shape of curved features. A link may be directed or undirected.

2.1.21**link identifier****link id**

identifier that is uniquely assigned to a link

NOTE A link identifier may be arbitrary or may be assigned by convention, to assure that no multiple occurrences of the same identifier will be used within one instance of a network or map database.

2.1.22**link location**

location identifiable by a part of the road network database having one identifier or having a uniquely identifiable combination of attributes throughout the continuous stretch

NOTE One link location can consist of multiple links.

2.1.23**location**

simple or compound geographic object to be referenced by a location reference

NOTE A location is matched to database objects by location definitions, which specify what is meant by a particular Location. Without any explicit remark it is meant to be a linear stretch in terms of topology in the database network without any loops or discontinuities in between (linear location). It might also be only a point in the network as a specialization of a linear stretch with length zero. In addition to that, a location can also be a set of road elements representing an area. This area is e.g. expressible by a polygon or a list of linear locations. For further description of different categories of locations, refer to 5.4.

2.1.24**location definition**

actual delineation of exactly what is meant (and, therefore, what is not meant) by a particular location within a specific database

NOTE It is the precise location definition of the database object, or set of database objects, which is referenced.

EXAMPLE The GDF road elements that make up a particular instance of an ALERT-C Location.

2.1.25**location reference****reference**

label which is assigned to a location

NOTE With a single LRM, one reference shall define unambiguously and exactly one location in the location referencing system. The reference is the string of data which is passed between different implementations of a location referencing system to identify the location.

2.1.26**location referencing method****LRM**

methodology of assigning location references to locations

2.1.27**location referencing system****LRS**

complete system by which location references are generated, according to a location referencing method, and communicated, including standards, definitions, software, hardware, and databases

2.1.28**matching**

translating a location reference to a specific object in a given map database to attempt recognition of the same identified object in both the sender's and the receiver's map database

NOTE Matching is seen as a subsequent part to the method of decoding a location reference adhering to the defined LRM.

2.1.29**node**

zero-dimensional element that is a topological junction of two or more edges, or an end point of an edge

NOTE A node is created for topologically significant points, such as simple intersections of roads or other linear features including boundaries but also for locations such as electric beacons, kilometre-posts or sensors detecting traffic flows, being significant points specified in a map.

2.1.30**node identifier**

identifier assigned to a node

NOTE A node identifier may be arbitrary, or may be assigned by convention, to ensure that multiple occurrences of the same identifier will not occur within one network or within the universe of similar networks or databases.

2.1.31**outlined area**

explicit area with an outline defined by segments being either polylines or linear locations

2.1.32**point**

zero-dimensional element that specifies geometric location

NOTE One coordinate pair or triplet specifies the location.

2.1.33**point location**

location that has a zero-dimensional character

EXAMPLE A simple crossing.

2.1.34**precision**

exactness of the measurement of a data value, or of the storage allocated to a measured data value

NOTE Alternatively, the closeness of measurements of the same phenomenon repeated under exactly the same conditions and using the same techniques.

2.1.35**pre-coded location reference**

location reference using a unique identifier that is agreed upon in both sender and receiver system to select a location from a set of pre-coded locations