

# SVENSK STANDARD

## SS-EN 15437-1:2009

Fastställt/Approved: 2009-04-06  
Publicerad/Published: 2009-05-20  
Utgåva/Edition: 1  
Språk/Language: engelska/English  
ICS: 45.060.01

---

### **Järnvägar – Kontroll av lagerboxar – Krav avseende gränssnitt och utförande – Del 1: Spårutrustning och lagerboxar för rullande materiel**

### **Railway applications – Axlebox condition monitoring – Interface and design requirements – Part 1: Track side equipment and rolling stock axlebox**

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-69386>

# Hitta rätt produkt och ett leveranssätt som passar dig

## Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

## Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på.

På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

## Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

## Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på [sis.se](http://sis.se) och ger dig en bra bild över hur olika produkter hör ihop.

## Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

# Find the right product and the type of delivery that suits you

## Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

## Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

## Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

## Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at [sis.se](http://sis.se), provide an overview of which publications belong together.

## Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Europastandarden EN 15437-1:2009 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 15437-1:2009.

The European Standard EN 15437-1:2009 has the status of a Swedish Standard. This document contains the official English version of EN 15437-1:2009.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00.

Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.

E-mail: [sis.sales@sis.se](mailto:sis.sales@sis.se) Internet: [www.sis.se](http://www.sis.se)



EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

EN 15437-1

March 2009

ICS 45.060.01

English Version

Railway applications - Axlebox condition monitoring - Interface  
and design requirements - Part 1: Track side equipment and  
rolling stock axlebox

Applications ferroviaires - Surveillance des boîtes d'essieux  
- Exigences liées aux interfaces - Partie 1: Equipments des  
voies et conception des boîtes d'essieux pour matériel  
roulant

Bahnanwendungen - Zustandsüberwachung von  
Radsatzlagern - Schnittstellen und  
Gestaltungsanforderungen - Teil 1:  
Heißläuferortungsanlagen und  
Radsatzlagergehäusegestaltung

This European Standard was approved by CEN on 21 February 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

## Contents

Page

Foreword.....	3
Introduction .....	4
1 Scope .....	5
2 Normative references .....	5
3 Terms and definitions .....	6
4 Symbols and abbreviations .....	9
5 Rolling Stock Requirements .....	10
5.1 Target zone.....	10
5.1.1 General.....	10
5.1.2 Dimensions of the target area .....	10
5.1.3 Position of the centre of the target area in the XY plane.....	11
5.1.4 Visibility requirements for the target area .....	11
5.2 Prohibitive zone .....	11
5.2.1 General.....	11
5.2.2 Dimensions of the prohibitive zone.....	11
5.2.3 Position of the centre of the prohibitive zone in the XY plane .....	12
5.3 Electromagnetic interference emissions .....	13
5.4 Design drawings .....	13
5.5 Protective finish .....	13
6 HABD requirements for its interface with rolling stock.....	13
6.1 General.....	13
6.2 HABD temperature measuring zone .....	13
6.3 HABD installation requirements.....	15
7 HABD system requirements .....	16
7.1 HABD functions .....	16
7.2 HABD temperature alarms .....	16
7.3 HABD general requirements .....	17
Annex A (informative) An example of an alternative HABD temperature measuring zone .....	18
Annex B (informative) Guidance for HABD installation .....	20
Annex C (informative) Accuracy of the HABD's calculated temperature of an axlebox.....	21
Annex D (informative) Examples of HABD system temperature alarm levels across Europe .....	22
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EC Directive 2008/57/EC of the European Parliament and of the Council of 17 June 2008 on the interoperability of the rail system within the Community .....	23
Bibliography .....	25

## Foreword

This document (EN 15437-1:2009) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2009, and conflicting national standards shall be withdrawn at the latest by September 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EC Directive 96/48 and EC Directive 2001/16, as modified by EC Directive 2004/50.

For relationship with EC Directive(s), see informative Annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## Introduction

Failed axle bearings on rolling stock create a hazard to the safe operation of the railway. If an axle bearing fails whilst rolling stock is in-service there is the potential for a catastrophic event. A catastrophic event may result in fatalities, severe damage to rolling stock and/or the infrastructure and a risk that rolling stock may derail and/or a fire may develop.

One indication that a bearing is about to fail is a rise in the heat generated by the bearing. Bearings that are about to fail may therefore be detected by monitoring their temperature to identify an unacceptable rise.

World-wide experience shows that one way of managing the risk is by installing trackside Hot AxleBox Detectors (HABDs) to monitor the in-service temperature of rolling stock axleboxes.

The sensors of a trackside HABD measure the thermal radiation emitted from the axleboxes of in-service rolling stock. The level of thermal radiation is influenced by the emissivity of the axlebox surface, which is influenced by the material, design, surface finish and operational conditions (dust, rain, etc). Even though operational conditions are continually changing the surface emissivity of the axlebox, long term experience indicates that such changing conditions can be tolerated.

This part of EN 15437 covers the monitoring of axlebox temperature by trackside HABD. It was developed by Working Group 35 "Hot Box Detection" of CEN Technical Committee 256 Railway Applications. It defines the minimum requirements for the interface between a trackside HABD and rolling stock, to ensure that the system works. It is important to note that Clause 1, Scope, sets out the minimum requirements for the interface.

The requirements set out in this document are based on long term existing rules, practices and procedures developed and currently in use by European member railway undertaking's (RUs) and infrastructure managers (IMs).

The following principles have been applied:

- a) The railway system requires technical rules in order to ensure an acceptable interface between rolling stock and trackside HABD.
- b) In view of the increasing significance of international traffic, the standardisation of this interface is required.
- c) It is of particular importance that the existing level of safety and reliability is not compromised.
- d) The Cartesian co-ordinate system is used to define dimensions and positions, that is X is longitudinal, Y is lateral and Z is vertical.

Some rolling stock, according to their performance or design, is fitted with on-board equipment to monitor axle bearings for potential overheating. However, in most cases, axle bearings continue to be monitored by trackside Hot Axle Bearing Detectors which is the subject of this standard.

Part 2 of EN 15437, which is currently being developed, covers on-board temperature monitoring of axle bearings.

Alternative technology is available, or being developed, to monitor the condition of axle bearings, using vibration sensors, thermocouples, etc. and may in the future be addressed by additional parts to this standard.



## 1 Scope

This part of EN15437 defines the minimum characteristics for the interface between a trackside Hot Axlebox Detector (HABD) and Rolling Stock (RST) that comply with the European Directives for Interoperability to ensure that the minimum functional requirement of the interface is achieved.

The minimum requirements of the interface apply to:

- a) Rolling stock conforming to standard European railway gauge, that is 1435mm;
- b) Rolling stock axles fitted with outboard bearings;

NOTE The design of rolling stock axles fitted with inboard bearings should respect the requirements set out in Note 2 of 5.2.

- c) Rolling stock with a maximum operational speed of up to and including 250 km/h;

NOTE 1 That is conventional rail and class 2 high speed rail rolling stock as defined in the rolling stock TSIs.

NOTE 2 Interoperable rolling stock designed for speeds above 250km/h (class 1 high speed rolling stock) are mandated to have on-board equipment for axlebox condition monitoring. The requirements for on-board equipment are described in part 2 of this standard which is currently under development.

NOTE 3 Interoperable rolling stock designed for speeds above 250km/h (class 1 high speed rolling stock) are outside the scope of this Part of the standard. However, if class 1 high speed trains are required to be monitored by HABDs their target area should comply with the requirements specified in this standard, except where stated otherwise.

- d) Trackside HABDs that are required to monitor conventional rail and class 2 high speed rail rolling stock.

The rolling stock requirements of the interface are described in Clause 5 and for the HABD requirements of the interface are described in Clause 6.

The scope of this part (part 1) of the standard does not include:

- Hot Wheel (Hot Disc) Detectors (HWDs). However, HWD are often installed in combination with trackside HABD to provide a dual monitoring system. This standard does not prevent the use of such a combination;
- how a HABD measures the temperature and identifies axle box position. This is part of an individual equipment design and not part of the functional requirements of this standard;
- operational requirements for acting on the information reported by the HABD system;
- maintenance requirements for HABD systems.

## 2 Normative references

The following referenced documents are required for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 15273-3, *Railway applications — Gauges — Part 3: Obstacles gauges*

EN 50121-3-1, *Railway applications — Electromagnetic compatibility — Part 3-1: Rolling stock — Train and complete vehicle*

EN 50121-4, *Railway applications — Electromagnetic compatibility — Part 4: Emission and immunity of the signalling and telecommunications apparatus*

EN 50125-3, *Railway applications — Environmental conditions for equipment — Part 3: Equipment for signalling and telecommunications*

EN 60950-1, *Information technology equipment — Safety — Part 1: General requirements (IEC 60950-1:2005, modified)*

ISO 14837-1, *Mechanical vibration — Ground-borne noise and vibration arising from rail systems — Part 1: General guidance*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

##### **axle bearing**

bearing or bearing assembly on a rail vehicle axle that transmits a proportion of the weight of the rail vehicle directly to the wheelset

NOTE For the purpose of this definition bearings associated with the mounting of traction motors or traction drives are excluded.

#### 3.1.1

##### **inboard axle bearing**

axle bearings that are positioned on the wheelset axle between the wheels of the wheelset

#### 3.1.2

##### **outboard axle bearing**

axle bearings that are positioned on the wheelset axle ends outside of the space between the wheels of the wheelset

#### 3.2

##### **axlebox**

structure, including for example cartridge bearing adaptor, which houses, or is in contact with, the axle journal bearing and provides an interface with the bogie and/or suspension arrangement

#### 3.3

##### **hot axlebox detector (HABD)**

trackside system that includes:

- sensors that measure the thermal radiation emitted from a defined area on each axlebox of a passing rail vehicle;
- data processing that calculates a temperature for each axlebox from these measured data;
- data processing that identifies signs that an axlebox is (or axleboxes are) overheated;
- communication link to transmit and receive data

#### 3.4

##### **target zone**

defined area on the underside of an axlebox that is designed to have its temperature monitored by a HABD

#### 3.5

##### **target area**

plan view dimensions, that is in the XY plane, of the target zone

#### 3.6

##### **axlebox temperature**

temperature of the target zone as calculated by a HABD

### **3.7**

#### **differential temperature**

temperature difference between the two axlebox temperatures of a wheelset, or of a pair of wheels at the same position, as calculated by the HABD

### **3.8**

#### **temperature alarm**

indication that a calculated axlebox temperature has exceeded a preset temperature level

#### **3.8.1**

##### **hot temperature alarm**

indication that a calculated axlebox temperature has exceeded a preset hot temperature level

#### **3.8.2**

##### **warm temperature alarm**

indication that a calculated axlebox temperature has exceeded a preset warm temperature level

#### **3.8.3**

##### **differential temperature alarm**

indication that a calculated differential temperature, between the left and right axleboxes of a wheelset, has exceeded a preset differential temperature level

#### **3.8.4**

##### **train-side differential temperature alarm**

indication that a calculated differential temperature, between the temperature of the axlebox compared to the average temperature of all the axleboxes along its side of the train, has exceeded a preset train-side differential temperature level

### **3.9**

#### **prohibitive zone**

zone in which heat sources such as exhausts, which might influence the behaviour of a HABD, are excluded or thermally shielded

### **3.10**

#### **track coordinates**

track coordinates, Figure 1, are based on the right hand rule Cartesian coordinate system, where the positive X-axis (longitudinal) is along the track in the direction of travel, the Z-axis is vertically upwards and the origin is at the centre of the track and level with the top of the rail

NOTE The Y-axis is the lateral axis.