

SVENSK STANDARD

SS-ISO 17512-1:2009

Fastställt/Approved: 2009-06-05

Publicerad/Published: 2009-09-15

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 13.080.30

Soil quality – Avoidance test for determining the quality of soils and effects of chemicals on behaviour –

Part 1: Test with earthworms (*Eisenia fetida* and *Eisenia andrei*) (ISO 17512-1:2008, IDT)



SWEDISH
STANDARDS
INSTITUTE

Hitta rätt produkt och ett leveranssätt som passar dig

Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på.

På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på sis.se och ger dig en bra bild över hur olika produkter hör ihop.

Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

Find the right product and the type of delivery that suits you

Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at sis.se, provide an overview of which publications belong together.

Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Den internationella standarden ISO 17512-1:2009 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 17512-1:2009.

The International Standard ISO 17512-1:2009 has the status of a Swedish Standard. This document contains the official English version of ISO 17512-1:2009.

! © Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

! © Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.
E-mail: sis.sales@sis.se Internet: www.sis.se

Contents	Page
Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Principle	2
5 Reagents and materials	3
6 Apparatus	4
7 Procedure	5
7.1 Appropriate concentration range	5
7.2 Testing of soils	5
7.3 Testing of chemical	6
7.4 Reference substance	6
7.5 Validity criteria	6
8 Calculation and expression of results	6
9 Test report	7
Annex A (informative) Test chambers	8
Annex B (informative) Example of a breeding technique for <i>Eisenia fetida</i> and <i>Eisenia andrei</i>	11
Annex C (informative) Further test organisms.....	12
Annex D (informative) Contaminants that earthworms can detect and avoid in the avoidance test	13
Annex E (normative) Testing of chemicals in the avoidance test	14
Annex F (normative) Determination of water-holding capacity	16
Annex G (informative) Comparison of the results obtained in the two section chamber and six section chamber system	17
Annex H (informative) Influence of soil properties on avoidance behaviour — Basis for the threshold value of 20 %	20
Annex I (informative) Data gained in “dual” tests with the same (untreated) control soil on both sides of the test vessels	22
Bibliography.....	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17512-1 was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 4, *Biological methods*.

ISO 17512 consists of the following parts, under the general title *Soil quality — Avoidance test for determining the quality of soils and effects of chemicals on behaviour*:

— *Part 1: Test with earthworms (Eisenia fetida and Eisenia andrei)*

The following part is under preparation:

— *Part 2: Test with collembolans (Folsomia candida)*

Introduction

Ecotoxicological test systems are applied to obtain information about the effects of contaminants in soil and are proposed to complement conventional chemical analysis (see ISO 15799). ISO 15799 includes a list and short characterisation of recommended and standardised test systems. Aquatic test systems with soil eluate are applied to obtain information about the fraction of contaminants potentially reaching the groundwater by the water path (retention function of soils), whereas terrestrial test systems are used to assess the habitat function of soils. As standardised test systems, a mortality test (ISO 11268-1) and a reproduction test (ISO 11268-2) exist to investigate the habitat function of a soil with respect to earthworms as representatives of the soil biocenosis.

The reproduction test with earthworms (ISO 11268-2) is applied to detect effects resulting from sublethal concentrations. Such endpoints are preferably applied to obtain information on environmental effects. However, the reproduction test is very labour-intensive and time-consuming, needing long incubation periods with results obtained only after 56 days. As the test period and the work expense dictate the costs of a given test, it is preferable to obtain the results within a short test period and at a high level of sensitivity. That is especially the case for the assessment of remediated soils. This feature is offered by the avoidance test with *Eisenia fetida* and *Eisenia andrei*. Experiences gained in a laboratory comparison test with eight contaminated soils in three laboratories point out that the avoidance test is as sensitive as the reproduction test (Reference [5]). However, it is not intended to use this test to replace the earthworm reproduction test.

NOTE The results were compared with those of the earthworm acute and reproduction tests carried out with the same soils. The results showed that with a criterion of > 80 % avoidance response, a 72 % agreement of the results was achieved.

Soil quality — Avoidance test for determining the quality of soils and effects of chemicals on behaviour —

Part 1:

Test with earthworms (*Eisenia fetida* and *Eisenia andrei*)

1 Scope

This part of ISO 17512 specifies a rapid screening method for evaluating the habitat function of soils and the influence of contaminants and chemicals on earthworm behaviour.

The sublethal test is a rapid method that reflects the bioavailability of contaminant mixtures in natural soils and substances spiked into soils to *Eisenia fetida* and *Eisenia andrei*. The avoidance behaviour of the worms is the measurement endpoint of the test. This test is not intended to replace the earthworm reproduction test.

Two different designs (a two section unit and a six section unit) have been developed and successfully applied. Both designs are applicable to either single-concentration (e.g. for assessing the quality of a field soil) or multi-concentration (e.g. for assessing the toxicity of a spiked chemical) tests. In both cases, the earthworms are allowed to make the initial choice on which compartment, control and a treatment [in the two section test vessel between right and left side; in the six section test vessel between the (3 + 3) alternating compartments], to enter.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10390, *Soil quality — Determination of pH*

ISO 11268-2:1998, *Soil quality — Effects of pollutants on earthworms (Eisenia fetida) — Part 2: Determination of effects on reproduction*

ISO 11269-2, *Soil quality — Determination of the effects of pollutants on soil flora — Part 2: Effects of chemicals on the emergence and growth of higher plants*

ISO 11465, *Soil quality — Determination of dry matter and water content on a mass basis — Gravimetric method*

ISO 15799, *Soil quality — Guidance on the ecotoxicological characterization of soil and soil materials*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

avoidance behaviour

tendency (of an organism) to avoid the test soil while preferring the control soil

3.2

habitat function

ability of soils/soil materials to serve as habitat for micro-organisms, plants and soil-living animals and their interactions

[ISO 15799:2003]

NOTE Ecotoxicological tests as indicators for the habitat function provide information concerning the respective test parameter, e.g. acute test for survival, or chronic tests for reproduction.

3.3

limited habitat function

habitat function (3.2) is limited if on average > 80 % of worms are found in the control soil (indication as an impact on behaviour)

3.4

effective concentration

EC_x

concentration at which a specific effect is detected [where *x* is a percentage (10, 25, 50) of this effect; e.g. avoidance]

EXAMPLE In this part of ISO 17512, an EC₅₀ means the concentration of a substance or mixture of substances in soil that is estimated to cause a behavioural response in 50 % of the test earthworms.

4 Principle

Ten adult earthworms (species *Eisenia fetida* or *Eisenia andrei*) are exposed at the same time to a control soil and a contaminated soil or a soil containing test substances. Test soil and control soil are placed into each test vessel and the earthworms are thus presented with a choice between the test soil and the control soil. Two test-vessel designs are available:

- a) a two section test vessel; and
- b) a six section test vessel.

After an incubation period of two days, the number of worms is determined in all sections of the vessels.

Individual studies (e.g. testing boric acid in one of the two designs in different laboratories) or comparative investigations (testing the same chemical or soil in the same laboratory, e.g. Reference [8]) have in some cases shown different results. Recently, both designs were validated in interlaboratory tests in Canada (Reference [2]) and France; however, no international ring test using both designs in parallel has been performed so far. Therefore, for the time being, the choice of the design is up to the experimenter. When doing so, practical considerations like costs of the units as well as the amount of waste produced should also be taken into consideration.

5 Reagents and materials

5.1 Boric acid reference toxicant, recommended. H_3BO_3 has been used historically as a soil chemosterilant and is an effective non-selective biocide (relative molecular mass: 61,81). Earthworms can detect and avoid sublethal concentrations that adversely affect reproduction. Boric acid satisfies the following criteria that attest to its suitability as a reference toxicant:

- a) it is effective at relatively low concentrations that are not strongly influenced by the nature of the substrate;
- b) it is relatively stable and persistent so that concentrations do not change rapidly over the duration of the test;
- c) it is reasonably water soluble or miscible in water, does not volatilise readily, and can be readily mixed with soils;
- d) there is a standard method for measuring boric acid concentrations in soil;
- e) it represents a minimal hazard to technicians and it is free of disposal problems.

5.2 Biological material, consisting of adult earthworms of the species *Eisenia fetida* or *Eisenia andrei* (individual mass: between 300 mg and 600 mg). Synchronisation of breeding of the organisms for this test is not necessary. An example of how to breed compost worms is given in Annex B.

Condition the selected worms for at least one day in the selected control soil (5.4).

NOTE *Eisenia fetida* and *Eisenia andrei* are compost worms. Ecologically, these species are not the most important in soils (Reference [7]). On the other hand, from a practical point of view, compost worms are much more suitable than any other lumbricid species due to the fact that they reproduce very quickly and easily in the laboratory (i.e. mass cultures can be obtained). In addition, the sensitivity of these species is more or less of the same order of magnitude in comparison to other earthworm species. In most cases, the differences between species are — depending on the chemical or contaminant mixture tested — not larger than a factor of 10 in acute or chronic tests (References [6], [7]). Despite the fact that other earthworm species have already successfully been used in avoidance tests (see Annex C), a factor describing their range of avoidance response is not yet known.

5.3 Test substrate. The soil to be tested should be sieved (size of openings, 2 mm) adjusted to about 60 % of the maximum water holding capacity. The optimum water content is achieved, if there is no standing water or free water appearing when the soil is compressed.

NOTE For highly silty and loamy soils, it can be difficult to get the necessary amount of soil sieved to ≤ 2 mm with an acceptable expenditure of work. The holes of the sieves may plug up within several minutes. Frequent cleaning is necessary. In this case, it is acceptable to sieve the amount of soil needed for the test to ≤ 4 mm.

Determine the water content and the pH in the presence of 1 mol/l KCl, in accordance with ISO 11465 and ISO 10390, respectively, immediately before the start of the test. In addition, the maximum water holding capacity shall be determined according to Annex F.

5.4 Control soil: three choices are possible (see also ISO 15799). Option a) is preferred, but since such a soil is often not available either a standard soil, b), or an artificial soil, c), is possible (potential influences of these soils are covered by the 80 % assessment criterion, see Clause 8).

- a) A control soil as similar as the test soil in all characteristics other than the presence of contaminants.
- b) A soil with the characteristics according to ISO 11269-2 [$C_{org} \leq 1,5$ %, sand (0,063 mm to 2 mm) content of 50 % to 75 %, < 20 % of particles less than 0,02 mm; pH of 5 to 7,5].
- c) Artificial soil in accordance with ISO 11268-2.

Natural soils should be sieved and the water content adjusted according to 5.3.

6 Apparatus

Usual laboratory equipment and in particular the following.

6.1 Containers (see Annex A).

6.1.1 Two section chamber: containers of capacity 1 l to 2 l with a cross-sectional area of about 0,02 m², such that a depth of 50 mm to 60 mm of the soil is achieved.

Test containers shall permit gaseous exchange between the medium and the atmosphere and access of light (e.g. by means of a perforated transparent cover), and shall have provisions to prevent worms from escaping (e.g. by using a tape to fix the cover). To avoid lateral effects of light, glass vessels shall be wrapped.

Two section chambers are commercially available¹⁾.

NOTE Due to the short test period and the proportionally large volume of soil in the vessels, a reduction of chemical concentration in the soil resulting from sorption to the vessel walls is negligible. Nevertheless, inert material (e.g. glass or stainless steel) is preferred.

6.1.2 Six section chamber (circular test units or vessels):

- 1) stainless steel for testing soil contaminated with organic compounds;
- 2) plastic (high density inert material) for testing soil contaminated with metals or metalloid compounds.

The circular test unit has a central chamber with six cut pie-shaped interconnecting compartments into which the test soil is placed; interconnecting holes are located along the bottom of the compartment walls (three per side) and along the bottom of the central chamber (two per side) so that the worms can move freely between compartments. The plastic test unit should be wrapped in an opaque material (tin foil) to eliminate light. Provisions to prevent worms from escaping are necessary.

The six section chamber is not commercially available. Therefore all details necessary to construct such chambers are presented in the figures and in the text.

6.2 Divider (e.g. plastic or thin sheets of metal):

- a) for the two section chamber, to divide the containers vertically into two identical sides;
- b) for the six section chamber, to slide along the walls of the compartments at the end of a test to isolate each section.

6.3 Equipment for measuring the water content of a substrate (according to ISO 11465).

6.4 Test environment.

6.4.1 Enclosure or environmental chamber, capable of being maintained at (20 ± 2) °C.

6.4.2 Light source, capable of delivering a constant light intensity of 400 lx to 800 lx on the containers at a controlled light/dark cycle of between 12 h/12 h and 16 h/8 h.

NOTE A day/night cycle was chosen so that the conditions are comparable to the acute and reproduction test.

1) Bellaplast No. 597 is an example of a suitable product available commercially. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this product.

7 Procedure

7.1 Appropriate concentration range

The avoidance test is designed to detect sublethal effects. Therefore, the test is invalid if more than one worm per vessel (i.e. one out of 10) is dead or missing at the end of the test (see 7.5). In order to avoid mortality, the performance of a range-finding test is recommended.

7.2 Testing of soils

7.2.1 Two section chamber

At the beginning of the test, the vessels (6.1.1) are divided into two equal sections by means of a vertically introduced divider. Vessels are filled with sieved soil up to a height of 50 mm to 60 mm. One half of the vessel is filled with test soil (section A), the other half is filled with control soil (section B). Then the separator is removed and 10 worms are placed on to the separating line of each test vessel (from there they have the possibility to dig quickly into the soil, using the slit left by the divider as a starting point). The containers are covered according to 6.1.1 and placed in the environmental chamber or in the test enclosure (6.4.1).

No feeding of the animals is required during the test.

The test is run with five replicates per treatment (test soils, controls or reference substance). To obtain a more precise quantification of the behavioural effect, a dilution series may be prepared. For dilution of the contaminated soil, the control soil should be used.

At the end of the test period (48 h) the control and test soils in each vessel are separated by inserting the dividers. The dividers shall be inserted before the test units are moved from the environmental chamber. The number of worms is determined for both sections of the vessels. Worms divided due to the introduction of the divider are counted as 0,5 independent of the length of the remaining body. Missing worms are considered to have either escaped from the test chamber or to have died and disintegrated during the test (see 7.1).

7.2.2 Six section chamber

The test soil and control soils are prepared (sieved, hydrated and mixed) and placed to a depth of 50 mm to 60 mm (350 ml soil) in each of three compartments in an alternating pattern (e.g. compartments 1, 3, and 5 have test soil and compartments 2, 4, and 6 have control soil) (see also Annex E). There is no soil in the central chamber. Ten earthworms are added to the central chamber, one at a time, and the compartment entered by each individual is recorded. The containers are covered (6.1.2) and placed in an environmental chamber (6.4.1).

No feeding of the animals is performed during the test.

The test is run with five replicates for a single concentration test and at least with duplicates for a multi-concentration test. For multi-concentration tests, the test soil consists of the site soil diluted with the appropriate control soil.

At the end of the test period (48 h) the dividers are positioned to prevent further movement of the earthworms between compartments. The dividers shall be inserted before the test units are moved from the environmental chamber. The number of worms in each compartment is recorded and the total number in each treatment within a test unit determined. Individual earthworms sliced inadvertently by the dividers are to be recorded as 0,5 independent of the length of the remaining body. Missing worms are considered to have either escaped from the test chamber or to have died and disintegrated during the test (see 7.1).

NOTE The hypothesis tested is that at the beginning of the test the worms are randomly distributed among sections and at the end of the test for a true avoidance response the earthworms are not distributed randomly among the sections in a vessel. If, at the beginning of the test, the worms are non-randomly distributed, then there might not be an avoidance response. Alternatively, there might be an avoidance response at the beginning of the test by worms refusing to enter sections with contaminated soil that they instantly avoid. This rarely happens when the levels in soil are sublethal.