

SVENSK STANDARD

SS-ISO 21299:2009

Fastställt/Approved: 2009-07-03

Publicerad/Published: 2009-09-15

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 65.060.70

Åkbara trädgårdsmaskiner – Överrullningsskydd (ROPS) – Provning och krav (ISO 21299:2009, IDT)

**Powered ride-on turf care equipment – Roll-over protective
structures (ROPS) – Test procedures and acceptance criteria
(ISO 21299:2009, IDT)**



SWEDISH
STANDARDS
INSTITUTE

Hitta rätt produkt och ett leveranssätt som passar dig

Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på.

På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på sis.se och ger dig en bra bild över hur olika produkter hör ihop.

Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

Find the right product and the type of delivery that suits you

Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at sis.se, provide an overview of which publications belong together.

Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Den internationella standarden ISO 21299:2009 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 21299:2009.

The International Standard ISO 21299:2009 has the status of a Swedish Standard. This document contains the official English version of ISO 21299:2009.

! © Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

! © Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00.

Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.

E-mail: sis.sales@sis.se Internet: www.sis.se

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	1
4 Test apparatus and equipment.....	3
4.1 Test equipment for horizontal loading	3
4.2 Test equipment for vertical crush loading	3
4.3 Other measuring apparatus	3
5 Preparation for strength testing	4
5.1 Purpose.....	4
5.2 Preparation rules for governing testing	4
6 Test procedures	4
6.1 Test sequence	4
6.2 Horizontal loading.....	5
6.3 Vertical crushing test	9
6.4 Observations during testing.....	10
7 Deflection-limiting volume (DLV)	10
8 Tolerances	12
9 Acceptance conditions.....	12
9.1 General requirements.....	12
9.2 Deflection-limiting volume/ground plane.....	12
9.3 Horizontal overload test for energy-absorbing ROPS	13
9.4 Vertical crush overload test.....	14
9.5 Cold weather embrittlement	14
10 Extension to other machines.....	16
11 Labelling	16
12 Test report	16
Annex A (normative) Requirements for providing resistance to brittle fracture of ROPS at reduced operating temperature.....	17
Annex B (informative) ROPS standards judged to provide operator protection comparable to this International Standard.....	19
Annex C (informative) Test report for roll-over protective structure	20
Bibliography	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 21299 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 13, *Powered lawn and garden equipment*.

Introduction

The testing of protective structures on machines is aimed at minimizing the frequency and severity of operator crushing injury resulting from accidental overturning during operation.

This International Standard enables a machine's roll-over protective structure (ROPS) to be tested by the application of static loads that simulate the actual loads which can be imposed on the cab or frame when the machine overturns without free-fall. Observations can be made on the strength of the structure, the brackets attaching it to the machine and those machine parts that could be affected by the load imposed on the structure.

Clause 6 contains testing alternatives for energy-absorbing and rigid ROPS. Field overturn experiences have demonstrated that when conservative, conventional ROPS design and test strategies are applied to small, low-mass vehicles, there is frequently little or no permanent deformation to the ROPS when the small vehicle overturns. Furthermore, standard structural steel shapes are not always incrementally sized to accommodate an efficient design for low-mass vehicles. Consequently, there is opportunity to more efficiently design and apply ROPS to small vehicles by the utilization of a rigid, non-energy-absorbing design.

Until now, there has been no ROPS International Standard covering the field of application of powered ride-on turf care machinery, and it was therefore necessary for the industry to employ standards from other fields of application to test this type of machinery. For information, Annex B lists those standards which have been employed in the past to determine the performance of ROPS for powered ride-on turf care machinery and which have been judged to provide operator protection comparable to that specified in this International Standard.

Powered ride-on turf care equipment — Roll-over protective structures (ROPS) — Test procedures and acceptance criteria

1 Scope

This International Standard defines test procedures and acceptance criteria for the roll-over protective structures (ROPS) of powered ride-on turf care machinery with a mass of 3 000 kg or less.

It is not applicable to stand-on or sulky type machines, nor to self-propelled machinery and tractors used in agriculture, forestry or construction applications.

NOTE Product-specific standards such as ISO 5395 specify whether or not a certain type of machine is to be fitted with a ROPS and these can include additional information on aspects related to ROPS, e.g. seat-belt anchorages and seat belts.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5353, *Earth-moving machinery, and tractors and machinery for agriculture and forestry — Seat index point*

ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs with specified property classes — Coarse thread and fine pitch thread*¹⁾

ISO 898-2, *Mechanical properties of fasteners — Part 2: Nuts with specified proof load values — Coarse thread*

ASTM A370, *Standard test methods and definitions for mechanical testing of steel products*

3 Terms, definitions and symbols

For the purposes of this document, the following terms, definitions and symbols (see Table 1) apply.

3.1

attachment

device designed for mounting only on a specific machine to perform a specific task

3.2

horizontal loading test

application of a horizontal load to the rear, front and sides of a ROPS

1) To be published. (Revision of ISO 898-1:1999)

3.3

machine mass

mass of the machine in working order, not including the operator, with all fluid levels full and with ROPS

NOTE The machine mass includes the heaviest configuration of attachments.

3.4

reference mass

m_t

mass, not less than the machine mass, used by the manufacturer to calculate the loading energies and forces to be applied in the tests

NOTE Adapted from ISO 5700:2006, definition 3.3.

3.5

reference plane

vertical plane generally longitudinal to the machine and passing through the seat index point (SIP) as defined in ISO 5353

3.6

roll-over protective structure

ROPS

framework protecting operators of turf care machinery that minimizes the likelihood of crushing injury resulting from accidental overturning during operation

NOTE 1 The ROPS is characterized by the provision of space for a deflection-limiting volume, either inside the envelope of the structure or within a space bounded by a series of planes from the outer edges of the structure to any part of the machine that might come into contact with flat ground; the structure is capable of supporting the mass of the machine in the overturned position.

NOTE 2 A ROPS may be designed and tested as a rigid ROPS or an energy-absorbing ROPS. A rigid ROPS, like an energy-absorbing ROPS, must be geometrically designed to protect the prescribed deflection-limiting volume. The primary difference is the static force resistance requirements in lieu of energy absorbing horizontal loads.

NOTE 3 The ROPS may be front- or rear-mounted, fixed or foldable (e.g. hinged or telescoping).

NOTE 4 Adapted from ISO 5700:2006, definition 3.1.

3.7

turf care machinery

machines used in the care and maintenance of predominantly grassy areas, including golf courses, sports fields and lawns

3.8

vertical crushing test

application of a vertical load through a beam placed laterally across the uppermost members of the ROPS

Table 1 — Symbols

Symbol	Description	Unit
D	Deflection of the ROPS at the point of, and in line with, the load application	mm
E_{il}	Energy input to be absorbed during longitudinal loading	J
E_{is}	Energy input to be absorbed during side loading	J
F	Static load force	N
F_{max}	Maximum static load force occurring during loading with the exception of the overload	N
F_v	Vertical crush load force	N
L	Length of forward projection of ROPS	mm
m_t	Reference mass	kg
W	External width of ROPS	mm

4 Test apparatus and equipment

4.1 Test equipment for horizontal loading

4.1.1 General

The test equipment shall enable horizontal loading to be applied to the ROPS. Provision shall be made for the load to be uniformly distributed in the direction of loading and along a beam having a maximum length of 700 mm. This stiff beam shall have a maximum vertical face dimension of 150 mm. The edges of the beam in contact with the ROPS shall be rounded, with a maximum radius of 50 mm.

The beam shall be capable of being adjusted to any angle in relation to the load direction, in order for it to be able to follow the angular variations of the ROPS load-bearing surface as it deflects.

Universal joints, or equivalent, shall be incorporated to ensure that the loading device does not constrain the structure in rotation or translation in any direction other than the loading direction.

The deviation in direction of the force shall not exceed

- $\pm 2^\circ$ at the start of the test under zero load, and
- 10° above or 20° below horizontal during testing under load.

The deflection rate shall be slow (< 5 mm/s) so that the load can at all times be considered "static".

4.1.2 Apparatus for measuring energy absorbed by the ROPS

The force vs. deflection curve shall be plotted continuously in order to determine the energy absorbed by the ROPS. Measurement of the force and deflection at the point where the load is applied to the ROPS is not required; however, force and deflection shall be measured simultaneously and co-linearly.

The point of origin of deflection measurements shall be selected so that only the energy absorbed by the ROPS or the deflection of certain parts of the machine, or both, is measured. The energy absorbed by deflection or slipping of the anchoring, or both, shall not be included.

4.2 Test equipment for vertical crush loading

The test equipment shall be capable of exerting a downward force on the ROPS through a rigid beam up to a maximum of 250 mm wide, connected to the load-applying mechanism by means of universal pin joints. Suitable axle stands shall be provided so that the machine's tyres do not bear the vertical crush load force. See Figure 6.

4.3 Other measuring apparatus

A device for checking that the ROPS has not entered the deflection-limiting volume (DLV), (see Clause 7), and that this volume has remained within the ROPS protection during testing, shall be used.

5 Preparation for strength testing

5.1 Purpose

Strength testing is intended to simulate such loads as are imposed on a ROPS when the machine overturns. These tests enable observations to be made on the strength of the ROPS and any brackets attaching it to the machine, as well as on any parts of the machine transmitting the test load.

5.2 Preparation rules for governing testing

The preparation for testing the ROPS is governed by the following general rules.

- a) The ROPS shall be to production specifications and shall be fitted to the appropriate machine model chassis in accordance with the manufacturer's declared attachment method. A complete machine is not required for the evaluation; however, the machine frame and ROPS mounting shall represent an operating installation.
- b) The assembly shall be secured to the bedplate so that the members connecting the assembly and the bedplate do not deflect significantly in relation to the ROPS under loading. The assembly shall not receive any support from the bedplate under loading other than that due to the initial attachment.
- c) Components that could create a hazard in the DLV shall also be fitted so that they can be examined to ascertain whether the requirements of the acceptance conditions have been fulfilled.
- d) All detachable windows, panels, canopies, and removable non-structural fittings shall be removed so that they do not contribute to the strength of the ROPS. In cases where it is possible to fix doors and windows open or remove them during work, they shall be either removed or fixed open for the test, so that they do not add to the strength of the ROPS. It shall be noted whether, in this position, they would create a hazard for the driver in the event of overturning.
- e) A track width setting for the rear wheels, if present, shall be chosen such that no interference exists with the ROPS during the tests. The assembly shall be supported and secured or modified so that all the test energy is absorbed by the ROPS and its attachment to the machine's rigid components.
- f) If, during the test procedure, any part of the machine restraining equipment breaks or moves, the test procedure shall be restarted.
- g) No repairs or adjustments of the machine or the ROPS are allowed during the test procedure.
- h) The ROPS shall be instrumented with the necessary equipment to obtain the required force-deflection data.

6 Test procedures

6.1 Test sequence

If an energy-absorbing or rigid ROPS is fabricated from materials meeting the cold weather embrittlement resistance requirements specified in Annex A, all the ROPS loadings may be conducted at ambient temperature. If an energy-absorbing or rigid folding ROPS is fabricated from materials not meeting the cold weather embrittlement resistance requirements specified in Annex A, all the ROPS loadings shall be conducted at $-18\text{ }^{\circ}\text{C}$.

NOTE This test procedure was developed for two- and four-post structures. For other designs, adaptation of the procedure could be necessary.

ROPS assembly 1 loadings

- a) longitudinal loading from the front, applied at either side;
- b) side loading from the side opposite to the applied longitudinal load;

c) vertical crush loading.

ROPS assembly 2 loadings

d) longitudinal loading from the rear, applied at either side;

e) side loading from the side opposite to the applied longitudinal load;

f) vertical crush loading.

See also Figure 1.

6.2 Horizontal loading

6.2.1 Longitudinal loading

Apply the longitudinal load in a plane parallel to the reference plane (see Figure 2). The load application point shall be that part of the ROPS likely to hit the ground first in a longitudinal overturning incident (normally the upper edge). The vertical plane in which the load is applied is located at a distance of one-sixth the external width of the ROPS, inwards from the outside, as shown in Figure 3, or as close as possible depending on ROPS configuration. If the ROPS is curved or protruding at this point, add wedges enabling the load to be applied to it, but do so in a way that will not reinforce the ROPS.

The central pivot of an articulated machine shall be supported and securely mounted as appropriate for all test procedures. For the side-loading test procedure, the pivot shall also be propped from the side opposite the loading. Only the frame portion to which the ROPS is mounted need be used.

The energy absorbed, E_{ij} , in joules, by the ROPS during the test shall be at least

$$E_{ij} = 1,6 \cdot m_t$$

Alternatively, the static load force, F , in newtons, of the rigid ROPS during the test shall be at least

$$F = 20 \cdot m_t$$

Maintain this force at least 5 s after the cessation of any visually detectable movement of the ROPS.