

SPECIFIKATION

SIS-ISO/PAS 13396:2009

Publicerad/Published: 2010-01-15

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 43.040.80

Barnsäkerhet i bil – Provningsmetod för utvärdering av skyddseffekt hos bilbarnstolar vid sidokollision – Väsentliga parametrar (ISO/PAS 13396:2009, IDT)

Road vehicles – Sled test method to enable the evaluation of side impact protection of child restraint systems – Essential parameters (ISO/PAS 13396:2009, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-71982>

Hitta rätt produkt och ett leveranssätt som passar dig

Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på.

På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på sis.se och ger dig en bra bild över hur olika produkter hör ihop.

Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

Find the right product and the type of delivery that suits you

Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at sis.se, provide an overview of which publications belong together.

Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Denna specifikation är inte en svensk standard. Detta dokument innehåller den engelska språkversionen av ISO/PAS 13396:2009

This Specification is not a Swedish Standard. This document contains the English version of ISO/PAS 13396:2009.

! © Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

! © Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.
E-mail: sis.sales@sis.se Internet: www.sis.se

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/PAS 13396 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 12, *Passive safety crash protection systems*.

Introduction

The UNECE/GRSP Working Group on Child Restraint Systems in April 2008 sent a request to ISO/TC 22/SC 12 to support their work on defining a side impact test procedure for CRS (child restraint systems) homologation based on state-of-the-art research and experience.

UNECE/GRSP specifically requested ISO/TC 22/SC 12 to define the essential parameters of a simplified test method, to ensure that a child restraint system has a sufficient capacity to contain the child and to absorb energy in case of side impact exposure.

The aim of this Publicly Available Specification is to answer the UNECE request.

Road vehicles — Sled test method to enable the evaluation of side impact protection of child restraint systems — Essential parameters

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This Publicly Available Specification mainly summarises the content of ISO/TR 14646^[1] to assist the Informal Group on CRS of UNECE/GRSP in their development of a simplified side impact method based on commonly agreed input data. In addition to the content of ISO/TR 14646, new data and further recommendations have been included. Where not otherwise stated, ISO/TR 14646 is reference source.

The essential input parameters given in Clause 3 are applicable to accessory child restraint systems aiming to offer side impact protection.

2 Accident statistics

The accident data presented in ISO/TR 14646 shows that side impact is especially severe for those children (age up to 12 years) sitting on the struck side. Head, neck and chest are the body regions most frequently showing severe injuries, and the head in particular needs to be protected. Comparison of accident data from different years (1985 to 1990; 1991 to 1996 and 1997 to 2001), without any filter on product age shows, however, decreasing risk for head injuries and increasing risk for neck injuries in the recent data compared to the older data.

Based on results of the EC funded CHILD project and the EEVC/WG18 Report^[5], non-head containment combined with intrusion loading are found to be one of the major reasons for head injuries in side impacts involving rearward facing and forward facing harness type CRS, as well as high back booster and backless booster (Johannsen et al.^[4]; EEVC^[5]).

Analysis of accident data involving children in side impacts from different sources and different regions of the world (Germany, Sweden and USA) indicates that the purely lateral impact (due to the accident data coding with $\pm 15^\circ$ deviation) is possibly more severe than angled ones, while the share of perpendicular and angled impacts with forward component is nearly equal (Johannsen and Menon^[3]). Although all three sources show the same tendency, final conclusions are not possible, as the number of children involved is too small to allow statistically significant results. These data regard all types of impact objects and restraint use.

Henary et al.^[7], when comparing the risk of injury between children (aged 0-23 months) in side impacts, using US crash data (NASS-CDS), found a significantly higher benefit for children in rearward facing compared to forward facing harness type CRS. The authors conclude that this is likely because a forward component in the vehicle travel direction in many of the cases will move the head forward during the crash and will therefore improve the containment situation. The forward movement of the head is directed towards the backrest of the CRS used.

The struck car is in many cases subjected to an angled acceleration due to its initial speed. The main expected influence of a possible forward component would be an increase in head forward motion. Head forward trajectory can also be influenced by pre-braking conditions. Maltese et al.^[6] mapped probable head

contact points for 4 year to 15 year old injured children (not using child seats) involved in a side impact, seated on the struck side in the rear seat. The contacts were mainly found adjacent to the likely initial position of the head of the in-position rear seat child occupant, and adjusted forward. The authors state this forward adjustment is likely due to the forward component.

3 Input parameters for side impact test procedure

3.1 General

Relevant input parameters for defining a side impact test procedure for CRS, based on experience from accident data analysis, full-scale tests and sled tests, as described in ISO/TR 14646, are presented below. These input parameters are divided into sections covering body regions to be protected, occupant kinematics, test severity, validation and field of application.

3.2 Body regions to be protected

Based on accident data, the body region to be protected with highest priority is the head, followed by neck and chest. Especially for the protection of the head, body kinematics as well as energy management capabilities of the CRS are important.

3.3 Occupant kinematics

As head containment and head loadings are crucial issues with respect to the assessment of the performance of a CRS in side impact, it is necessary to utilize a test procedure capable of simulating real world occupant kinematics and realistic loading conditions.

Containing the head within the CRS is more of a challenge for the larger dummies, representing the upper limit of the respective CRS group in a given CRS, than for the smaller ones, based on experience with different side impact test procedures within the development of ISO/TR 14646 and ISO/TS 29062^[2].

The application of side impact test procedures needs to be defined carefully, taking into account the protection capabilities of today's cars.

3.4 Test characteristics

3.4.1 General

When designing a sled test method, the aim should be to replicate the characteristics of a full-scale side impact test situation, but in a simplified way and as generic as possible. The characteristics are derived from vehicle acceleration, vehicle velocity, intrusion depth and intrusion velocity, but also by geometrical measurements such as the distance of the CRS in relation to the structure and the coverage/profile of the intruding vehicle structure.

The analysis of full-scale side impact tests presented in ISO/TR 14646 shows that the performance of today's cars has been significantly improved, especially with respect to intrusion velocity during the last few years. However, the test severity of the full-scale test is subject to several discussions, as it is felt to be too moderate. One example of higher severity tests is the IIHS test procedure (see Reference [11]), where the mass of the barrier as well as the stiffness and shape of the barrier face cause a more aggressive contact with the car in comparison to ECE Regulation No. 95 and FMVSS 214 test conditions.

Summing up the results presented in ISO/TR 14646 and the statements above, the following properties defining the test characteristics are suggested as a generic and representative (for the majority of cars in use) side impact sled test method. The intrusion and intrusion velocity graphs shown in this document are measured at the front door close to the b-pillar. Data of the rear seat position for a P1.5 dummy in a rearward facing CRS can be found in ISO/TR 14646.