

# Teknisk specifikation

## SIS-ISO/TS 19130:2010

Publicerad/Published: 2011-01-12

Utgåva/Edition: 1

Språk/Language: engelska/English

ICS: 35.240.01; 35.240.30; 35.240.50; 35.240.60; 35.240.70

---

### **Geografisk information – Sensormodeller för positionering (ISO/TS 19130:2010, IDT)**

### **Geographic information – Imagery sensor models for geopositioning (ISO/TS 19130:2010, IDT)**

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-76069>

# Standarder får världen att fungera

*SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.*

## Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.


## Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

## Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

**Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på [www.sis.se](http://www.sis.se) eller ta kontakt med oss på tel 08-555 523 00.**



# Standards make the world go round

*SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.*

## Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

## Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

## Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

**If you want to know more about SIS, or how standards can streamline your organisation, please visit [www.sis.se](http://www.sis.se) or contact us on phone +46 (0)8-555 523 00**



Denna tekniska specifikation är inte en svensk standard. Detta dokument innehåller den engelska språkversionen av ISO/TS 19130:2010.

This Technical Specification is not a Swedish Standard. This document contains the English version of ISO/TS 19130:2010.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

*Uppllysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna uppllysningar om svensk och utländsk standard.*

*Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.*

Dokumentet är framtaget av kommittén för Ramverk för geodata, SIS/TK 323.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på [www.sis.se](http://www.sis.se) - där hittar du mer information.



# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Conformance</b> .....	<b>1</b>
<b>3 Normative references</b> .....	<b>2</b>
<b>4 Terms and definitions</b> .....	<b>2</b>
<b>5 Symbols and abbreviated terms</b> .....	<b>11</b>
<b>5.1 Abbreviated terms</b> .....	<b>11</b>
<b>5.2 Notation</b> .....	<b>13</b>
<b>6 Image ge positioning: overview and common elements</b> .....	<b>13</b>
<b>6.1 Introduction</b> .....	<b>13</b>
<b>6.2 Type of ge positioning information</b> .....	<b>14</b>
<b>6.3 Calibration data</b> .....	<b>15</b>
<b>6.4 Ground control points</b> .....	<b>16</b>
<b>7 Physical Sensor Models</b> .....	<b>19</b>
<b>7.1 Sensor types</b> .....	<b>19</b>
<b>7.2 Physical Sensor Model approach</b> .....	<b>23</b>
<b>7.3 Quality associated with Physical Sensor Models</b> .....	<b>29</b>
<b>7.4 Physical Sensor Model metadata</b> .....	<b>31</b>
<b>7.5 Location and orientation</b> .....	<b>32</b>
<b>7.6 Sensor parameters</b> .....	<b>37</b>
<b>8 True Replacement Models and Correspondence Models</b> .....	<b>43</b>
<b>8.1 Functional fitting</b> .....	<b>43</b>
<b>8.2 True Replacement Model approach</b> .....	<b>44</b>
<b>8.3 Quality associated with a True Replacement Model</b> .....	<b>50</b>
<b>8.4 Schema for True Replacement Model</b> .....	<b>52</b>
<b>8.5 Correspondence Model approach</b> .....	<b>53</b>
<b>8.6 Schema for Correspondence Models</b> .....	<b>56</b>
<b>Annex A (normative) Conformance and testing</b> .....	<b>57</b>
<b>Annex B (normative) Geolocation information data dictionary</b> .....	<b>60</b>
<b>Annex C (normative) Coordinate systems</b> .....	<b>77</b>
<b>Annex D (informative) Frame sensor model metadata profile supporting precise ge positioning</b> .....	<b>106</b>
<b>Annex E (informative) Pushbroom / Whiskbroom sensor model metadata profile</b> .....	<b>114</b>
<b>Annex F (informative) Synthetic Aperture Radar sensor model metadata profile supporting precise ge positioning</b> .....	<b>128</b>
<b>Bibliography</b> .....	<b>140</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, a technical committee may decide to publish other types of normative document:

- an ISO Publicly Available Specification (ISO/PAS) represents an agreement between technical experts in an ISO working group and is accepted for publication if it is approved by more than 50 % of the members of the parent committee casting a vote;
- an ISO Technical Specification (ISO/TS) represents an agreement between the members of a technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/PAS or ISO/TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/PAS or ISO/TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TS 19130 was prepared by Technical Committee ISO/TC 211, *Geographic information/Geomatics*.

## Introduction

The purpose of this Technical Specification is to specify the geolocation information that an imagery data provider shall supply in order for the user to be able to find the earth location of the data using a Physical Sensor Model, a True Replacement Model or a Correspondence Model. Detailed Physical Sensor Models are defined for passive electro-optical visible/infrared (IR) sensors (frame, pushbroom and whiskbroom) and for an active microwave sensing system (Synthetic Aperture Radar). A set of components from which models for other sensors can be constructed is also provided. Metadata required for geopositioning using a True Replacement Model, a Correspondence Model, or ground control points are also specified. The intent is to standardize sensor descriptions and specify the minimum geolocation metadata requirements for data providers and geopositioning imagery systems.

Vast amounts of data from imaging systems are collected, processed and distributed by government mapping and remote sensing agencies and commercial data vendors. In order for this data to be useful in extraction of geographic information, it requires further processing. Geopositioning, which determines the ground coordinates of an object from image coordinates, is a fundamental processing step. Because of the diversity of sensor types and the lack of a common sensor model standard, data from different producers can contain different parametric information, lack parameters required to describe the sensor that produces the data, or lack ancillary information necessary for geopositioning and analysing the data. Consequently, a separate software package often has to be developed to deal with data from each individual sensor or data producer. Standard sensor models and geolocation metadata allow agencies or vendors to develop generalized software products that are applicable to data from multiple data producers or from multiple sensors. With such a standard, different producers can describe the geolocation information of their data in the same way, thus promoting interoperability of data between application systems and facilitating data exchange.

This Technical Specification defines the set of metadata elements specified for providing sensor model and other geopositioning data to users. For the case where a Physical Sensor Model is provided, it includes a location model and metadata relevant to all sensors; it also includes metadata specific to whiskbroom, pushbroom, frame, and SAR sensors. It also includes metadata for functional fit geopositioning, where the function is part of a Correspondence Model or a True Replacement Model. This Technical Specification also provides a schema for all of these metadata elements.



# Geographic information — Imagery sensor models for geopositioning

## 1 Scope

This Technical Specification identifies the information required to determine the relationship between the position of a remotely sensed pixel in image coordinates and its geoposition. It supports exploitation of remotely sensed images. It defines the metadata to be distributed with the image to enable user determination of geographic position from the observations.

This Technical Specification specifies several ways in which information in support of geopositioning may be provided.

- a) It may be provided as a sensor description with the associated physical and geometric information necessary to rigorously construct a Physical Sensor Model. For the case where precise geoposition information is needed, this Technical Specification identifies the mathematical formulae for rigorously constructing Physical Sensor Models that relate two-dimensional image space to three-dimensional ground space and the calculation of the associated propagated errors. This Technical Specification provides detailed information for three types of passive electro-optical/infrared (IR) sensors (frame, pushbroom and whiskbroom) and for an active microwave sensing system [Synthetic Aperture Radar (SAR)]. It provides a framework by which these sensor models can be extended to other sensor types.
- b) It may be provided as a True Replacement Model, using functions whose coefficients are based on a Physical Sensor Model so that they provide information for precise geopositioning, including the calculation of errors, as precisely as the Physical Sensor Model they replace.
- c) It may be provided as a Correspondence Model that provides a functional fitting based on observed relationships between the geositions of a set of ground control points and their image coordinates.
- d) It may be provided as a set of ground control points that can be used to develop a Correspondence Model or to refine a Physical Sensor Model or True Replacement Model.

This Technical Specification does not specify either how users derive geoposition data or the format or content of the data the users generate.

## 2 Conformance

This Technical Specification specifies four conformance classes. There is one conformance class for each of the methods specified for providing geopositioning information. Any set of geopositioning information claiming conformance to this Technical Specification shall satisfy the requirements for at least one conformance class as specified in Table 1. The requirements for each class are shown by the presence of an X in the boxes for all clauses in the application test suite (ATS) required for that class. If the requirement is conditional, the box contains a C.

**Table 1 — Conformance classes**

		Subclause										
		A.1	A.2.1	A.2.2	A.3.1	A.3.2	A.3.3	A.3.4	A.3.5	A.4	A.5	A.6
Conformance Class	Correspondence Model	X	X	X						X		X
	Physical Sensor Model	SAR	X			X	X	X		X		
		electro-optical	X			X	X	X	X			
	True Replacement Model	X								X	X	
	GCP Collection	X	X	X	C	C	C	C	C	C	C	C

### 3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 19103:2005, *Geographic information — Conceptual schema language*

ISO 19107, *Geographic information — Spatial schema*

ISO 19108, *Geographic information — Temporal schema*

ISO 19111:2007, *Geographic information — Spatial referencing by coordinates*

ISO 19115:2003, *Geographic information — Metadata*

ISO 19115-2:2009, *Geographic information — Metadata — Part 2: Extensions for imagery and gridded data*

ISO 19123, *Geographic information — Schema for coverage geometry and functions*

ISO/TS 19138:2006 *Geographic information — Data quality measures*

### 4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

- 4.1 active sensing system**  
sensing system that emits energy that the **sensor** uses to perform sensing
- 4.2 adjustable model parameters**  
model parameters that can be refined using available additional information, such as **ground control points**, to improve or enhance modelling corrections
- 4.3 along-track**  
direction in which the **sensor** platform moves

#### 4.4

##### **ARP**

##### **aperture reference point**

3D location of the centre of the synthetic aperture

NOTE It is usually expressed in ECEF **coordinates** in metres.

#### 4.5

##### **attitude**

orientation of a body, described by the angles between the axes of that body's **coordinate system** and the axes of an external coordinate system

[ISO 19116:2004, definition 4.2]

#### 4.6

##### **attribute**

named property of an entity

[ISO/IEC 2382-17:1999, definition 17.02.12]

NOTE In this Technical Specification, the property relates to a geometrical, topological, thematic, or other characteristic of an entity.

#### 4.7

##### **azimuth resolution**

⟨SAR⟩ resolution in the cross-range direction

NOTE This is usually measured in terms of the **impulse response** of the **SAR sensor** and processing system. It is a function of the size of the synthetic aperture, or alternatively the dwell time (i.e. a larger aperture results in a longer dwell time results in better resolution).

#### 4.8

##### **beam width**

⟨SAR⟩ useful angular width of the beam of electromagnetic energy

NOTE Beam width is usually measured in radians and as the angular width between two points that have 50 % of the power (3 dB below) of the centre of the beam. It is a property of the antenna. Power emitted outside of this angle is too little to provide a usable return.

#### 4.9

##### **broadside**

⟨SAR⟩ direction orthogonal to the velocity vector and parallel to the plane tangent to the Earth's **ellipsoid** at the nadir point of the **ARP**

#### 4.10

##### **calibrated focal length**

distance between the **perspective centre** and the **image plane** that is the result of balancing positive and negative radial lens distortions during **sensor** calibration

#### 4.11

##### **coordinate**

one of a sequence of  $n$  numbers designating the position of a point in  $n$ -dimensional space

[ISO 19111:2007, definition 4.5]

NOTE In a **coordinate reference system**, the coordinate numbers are qualified by units.

#### 4.12

##### **coordinate reference system**

**coordinate system** that is related to an object by a **datum**

[ISO 19111:2007, definition 4.8]

NOTE For geodetic and vertical datums, the object will be the Earth.

**4.13  
coordinate system**

set of mathematical rules for specifying how **coordinates** are to be assigned to points

[ISO 19111:2007, definition 4.10]

**4.14  
Correspondence Model**

functional relationship between ground and **image coordinates** based on the correlation between a set of **ground control points** and their corresponding image coordinates

**4.15  
cross-track**

perpendicular to the direction in which the collection platform moves

**4.16  
data**

reinterpretable representation of information in a formalised manner suitable for communication, interpretation, or processing

[ISO/IEC 2382-1:1993, definition 01.01.02]

**4.17  
datum**

parameter or set of parameters that define the position of the origin, the scale, and the orientation of a **coordinate system**

[ISO 19111:2007, definition 4.14]

**4.18  
detector**

device that generates an output signal in response to an energy input

**4.19  
Doppler angle**

⟨SAR⟩ angle between the velocity vector and the **range vector**

**4.20  
Doppler shift**

wavelength change resulting from relative motion of source and **detector**

NOTE In the **SAR** context, it is the frequency shift imposed on a radar signal due to relative motion between the transmitter and the object being illuminated.

**4.21  
ellipsoid**

surface formed by the rotation of an ellipse about a main axis

[ISO 19111:2007, definition 4.17]

NOTE The Earth ellipsoid is a mathematical ellipsoid figure of the Earth which is used as a reference frame for computations in geodesy, astronomy and the geosciences.

#### 4.22

##### **ellipsoidal coordinate system**

geodetic coordinate system

**coordinate system** in which position is specified by **geodetic latitude**, **geodetic longitude** and (in the three-dimensional case) **ellipsoidal height**

[ISO 19111:2007, definition 4.18]

#### 4.23

##### **ellipsoidal height**

geodetic height

*h*

distance of a point from the **ellipsoid** measured along the perpendicular from the ellipsoid to this point, positive if upwards or outside of the ellipsoid

[ISO 19111:2007, definition 4.19]

NOTE Only used as part of a three-dimensional **ellipsoidal coordinate system** and never on its own.

#### 4.24

##### **error propagation**

process of determining the uncertainties of derived quantities from the known uncertainties of the quantities on which the derived quantity is dependent

NOTE Error propagation is governed by the mathematical function relating the derived quantity to the quantities from which it was derived.

#### 4.25

##### **external coordinate reference system**

**coordinate reference system** whose **datum** is independent of the object that is located by it

#### 4.26

##### **fiducial centre**

point determined on the basis of the camera **fiducial marks**

NOTE When there are four fiducial marks, fiducial centre is the intersection of the two lines connecting the pairs of opposite fiducial marks.

#### 4.27

##### **fiducial mark**

index marks, typically four or eight rigidly connected with the camera body, which form **images** on the film negative and define the **image coordinate reference system**

NOTE When a camera is calibrated the distances between fiducial marks are precisely measured and assigned **coordinates** that assist in correcting for film distortion.

#### 4.28

##### **frame sensor**

**sensor** that detects and collects all of the **data** for an **image** (frame / rectangle) at an instant of time

#### 4.29

##### **geodetic datum**

**datum** describing the relationship of a two- or three-dimensional **coordinate system** to the Earth

[ISO 19111:2007, definition 4.24]

NOTE In most cases, the geodetic datum includes an **ellipsoid** description.

#### 4.30

##### **geodetic latitude**

ellipsoidal latitude

$\varphi$

angle from the equatorial plane to the perpendicular to the ellipsoid through a given point, northwards treated as positive

[ISO 19111:2007, definition 4.25]

#### 4.31

##### **geodetic longitude**

ellipsoidal longitude

$\lambda$

angle from the prime meridian plane to the meridian plane of a given point, eastward treated as positive

[ISO 19111:2007, definition 4.26]

#### 4.32

##### **geoid**

equipotential surface of the Earth's gravity field which is everywhere perpendicular to the direction of gravity and which best fits mean sea level either locally or globally

[ISO 19111:2007, definition 4.27]

#### 4.33

##### **geographic information**

information concerning phenomena implicitly or explicitly associated with a location relative to the Earth

[ISO 19101:2002, definition 4.16]

#### 4.34

##### **geolocating**

**geopositioning** an object using a **Physical Sensor Model** or a **True Replacement Model**

#### 4.35

##### **geolocation information**

information used to determine geographic location corresponding to **image** location

[ISO 19115-2:2009, definition 4.11]

#### 4.36

##### **geopositioning**

determining the geographic position of an object

NOTE While there are many methods for geopositioning, this Technical Specification is focused on geopositioning from **image coordinates**.

#### 4.37

##### **georeferencing**

**geopositioning** an object using a **Correspondence Model** derived from a set of points for which both ground and **image coordinates** are known

#### 4.38

##### **gimbal**

mechanical device consisting of two or more rings connected in such a way that each rotates freely around an axis that is a diameter of the next ring toward the outermost ring of the set

NOTE An object mounted on a three-ring gimbal will remain horizontally suspended on a plane between the rings regardless as to the stability of the base.

#### 4.39

##### **grazing angle**

⟨SAR⟩ vertical angle from the local surface tangent plane to the **slant range** direction

#### 4.40

##### **grid**

network composed of two or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way

[ISO 19123:2005, definition 4.1.23]

NOTE The curves partition a space into grid cells.

#### 4.41

##### **grid coordinates**

sequence of two or more numbers specifying a position with respect to its location on a **grid**

[ISO 19115-2:2009, definition 4.16]

#### 4.42

##### **ground control point**

point on the earth that has an accurately known geographic position

[ISO 19115-2:2009, definition 4.18]

#### 4.43

##### **ground range**

⟨SAR⟩ magnitude of the **range vector** projected onto the ground

NOTE Ground range of an **image** is represented by the distance from the nadir point of the antenna to a point in the scene. Usually measured in the horizontal plane, but can also be measured as true distance along the ground, DEM, **geoid** or **ellipsoid** surface.

#### 4.44

##### **GRP**

##### **ground reference point**

3D position of a reference point on the ground for a given synthetic aperture

NOTE It is usually the centre point of an **image** (Spotlight) or an image line (Stripmap). It is usually expressed in ECEF **coordinates** in metres.

#### 4.45

##### **ground sampling distance**

linear distance between **pixel** centres on the ground

NOTE This definition also applies for water surfaces.

#### 4.46

##### **gyroscope**

device consisting of a spinning rotor mounted in a **gimbal** so that its axis of rotation maintains a fixed orientation

NOTE The rotor spins on a fixed axis while the structure around it rotates or tilts. In airplanes, the pitch and orientation of the airplane is measured against the steady spin of the gyroscope. In space, where the four compass points are meaningless, the gyroscope's axis of rotation is used as a reference point for navigation. An inertial navigation system includes three gimbal-mounted gyroscopes, used to measure roll, pitch, and yaw.

#### 4.47

##### **image**

gridded coverage whose **attribute** values are a numerical representation of a physical parameter

[ISO 19115-2:2009, definition 4.19]

NOTE The physical parameters are the result of measurement by a **sensor** or a prediction from a model.

**4.48****image coordinate reference system**

**coordinate reference system** based on an **image datum**

[ISO 19111:2007, definition 4.30]

**4.49****image datum**

engineering **datum** which defines the relationship of a **coordinate system** to an **image**

[ISO 19111:2007, definition 4.31]

**4.50****image distortion**

deviation between the actual location of an **image point** and the location that theoretically would result from the geometry of the imaging process without any errors

**4.51****image formation**

⟨SAR⟩ process by which an **image** is generated from collected Phase History Data in a **SAR** system

**4.52****image-identifiable ground control point**

**ground control point** associated with a marker or other object on the ground that can be recognized in an **image**

NOTE The ground control point may be marked in the image, or the user may be provided with an unambiguous description of the ground control point so that it can be found in the image.

**4.53****image plane**

plane behind an imaging lens where **images** of objects within the depth of field of the lens are in focus

**4.54****image point**

point on the **image** that uniquely represents an **object point**

**4.55****imagery**

representation of phenomena as **images** produced by electronic and/or optical techniques

[ISO/TS 19101-2:2008, definition 4.14]

NOTE In this Technical Specification, it is assumed that the phenomena have been sensed or detected by one or more devices such as radars, cameras, photometers and infrared and multispectral scanners.

**4.56****impulse response**

width of the return generated by a small point reflector, which equates to the smallest distance between two point reflectors that can be distinguished as two objects

**4.57****incident angle**

vertical angle between the line from the detected element to the **sensor** and the local surface normal (tangent plane normal)

**4.58****internal coordinate reference system**

**coordinate reference system** having a **datum** specified with reference to the object itself

#### 4.59

##### **metadata**

**data** about data

[ISO 19115:2003, definition 4.5]

#### 4.60

##### **object point**

point in the object space that is imaged by a **sensor**

NOTE In **remote sensing** and aerial photogrammetry an object point is a point defined in an Earth-fixed **coordinate reference system**.

#### 4.61

##### **passive sensor**

**sensor** that detects and collects energy from an independent source

EXAMPLE Many optical sensors collect reflected solar energy.

#### 4.62

##### **perspective centre**

projection centre

point located in three dimensions through which all rays between **object points** and **image points** appear to pass geometrically

#### 4.63

##### **Physical Sensor Model**

**sensor model** based on the physical configuration of a sensing system

#### 4.64

##### **pixel**

smallest element of a digital **image** to which **attributes** are assigned

[ISO/TS 19101-2:2008, definition 4.28]

NOTE 1 This term originated as a contraction of “picture element”.

NOTE 2 Related to the concept of a **grid** cell.

#### 4.65

##### **platform coordinate reference system**

engineering **coordinate reference system** fixed to the collection platform within which positions on the collection platform are defined

#### 4.66

##### **principal point of autocollimation**

point of intersection between the **image plane** and the normal from the **perspective centre**

#### 4.67

##### **principal point of best symmetry**

centre of the circles of equal distortion of the lens positioned in the **image plane**

#### 4.68

##### **pushbroom sensor**

**sensor** that collects a single **cross-track image** line at one time and constructs a larger image from a set of adjacent lines resulting from the **along-track** motion of the sensor

#### 4.69

##### **range bin**

⟨SAR⟩ group of radar returns that all have the same range

**4.70****range direction****slant range direction**

<SAR> direction of the **range vector**

**4.71****range resolution**

spatial **resolution** in the **range direction**

NOTE For a **SAR sensor**, it is usually measured in terms of the **impulse response** of the sensor and processing system. It is a function of the bandwidth of the pulse.

**4.72****range vector**

vector from the antenna to a point in the scene

**4.73****rectified grid**

**grid** for which there is an affine transformation between the **grid coordinates** and the **coordinates** of an **external coordinate reference system**

[ISO 19123:2005, definition 4.1.32]

NOTE If the **coordinate reference system** is related to the Earth by a **datum**, the grid is a georectified grid.

**4.74****remote sensing**

collection and interpretation of information about an object without being in physical contact with the object

[ISO/TS 19101-2:2008, definition 4.33]

**4.75****resolution (of a sensor)**

smallest difference between indications of a **sensor** that can be meaningfully distinguished

[ISO/TS 19101-2:2008, definition 4.34]

NOTE For **imagery**, resolution refers to radiometric, spectral, spatial and temporal resolutions.

**4.76****SAR****Synthetic Aperture Radar**

imaging radar system that simulates the use of a long physical antenna by collecting multiple returns from each target as the actual antenna moves along the track

NOTE The electromagnetic radiation is at microwave frequencies and is sent in pulses.

**4.77****scan mode**

**SAR** mode in which the antenna beam is steered to illuminate a swath of ground at various angles relative to flight path throughout the collection

NOTE Steering the antenna also allows dwell time to be increased and provides the ability to collect strips at angles non-parallel to the flight direction and with better resolution than **Stripmap mode**.

**4.78****ScanSAR mode**

special case of **stripmap mode** that uses an electronically steerable antenna to quickly change the swath being imaged during collection to collect multiple parallel swaths in one pass

#### 4.79

##### **sensor**

element of a measuring system that is directly affected by a phenomenon, body, or substance carrying a quantity to be measured

[ISO/IEC Guide 99:2007, definition 3.8]

#### 4.80

##### **sensor model**

⟨geopositioning⟩ mathematical description of the relationship between the three-dimensional object space and the two-dimensional plane of the associated **image** produced by a **sensor**

#### 4.81

##### **slant plane**

⟨SAR⟩ plane that passes through the **sensor** velocity vector and the GRP

#### 4.82

##### **slant range**

⟨SAR⟩ magnitude of the **range vector**

#### 4.83

##### **spotlight mode**

⟨SAR⟩ **SAR** mode in which the antenna beam is steered to illuminate one area during collection

NOTE Spotlight mode provides the ability to collect higher resolution SAR **data** over relatively smaller patches of ground surface.

#### 4.84

##### **squint angle**

⟨SAR⟩ angle measured from the **broadside** direction vector to the **range direction** vector in the **slant plane**

#### 4.85

##### **stripmap mode**

⟨SAR⟩ **SAR** mode in which the antenna beam is fixed throughout the collection of an **image**

NOTE **Doppler angle** in processed products is fixed for all **pixels**. It provides the ability to collect SAR **data** over strips of land over a fixed swath of **ground range** parallel to the direction of flight.

#### 4.86

##### **True Replacement Model**

model using functions whose coefficients are based on a **Physical Sensor Model**

#### 4.87

##### **whiskbroom sensor**

**sensor** that sweeps a **detector** forming **cross-track image** line(s) and constructs a larger image from a set of adjacent lines using the **along-track** motion of the sensor's collection platform

## 5 Symbols and abbreviated terms

### 5.1 Abbreviated terms

ARP Aperture Reference Point

CCD Charge-Coupled Device

CCS Common Coordinate System