

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

This document was prepared by ISO/TC 22, *Road vehicles*, Subcommittee SC 36, *Safety and impact testing*.

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80003406>

Road vehicles — Measurement techniques in impact tests — Instrumentation

AMENDMENT 1

4.5.3, Table 3

Replace Table 3 by the following:

Table 3 — Calibration procedures and uncertainties

Calibration procedures	Uncertainties	Calibration range
	Relative expanded measurement uncertainty (k=2) for transducer types used in crash testing specific to the maximum value of the calibration range	
Accelerometer Shock calibration (pendulum or shock table)	<1,8 %	Application range
Accelerometer Sinusoidal calibration (Shaker)	<2 % below 400 Hz	minimum amplitude : 0,1% of range or 25 m/s ² whichever is greater min frequency < FH/5
	<2,5 % from 400 Hz to 2 kHz	minimum amplitude : 0,1% of range or 25 m/s ² whichever is greater min frequency < FH/5
	<3,5 % from 2 kHz to 5 kHz	minimum amplitude : 0,1% of range or 25 m/s ² whichever is greater min frequency < FH/5
Acceleration static calibration (centrifuge)	<1,5 %	min 500 m/s ² or full scale of accelerometer if range is <500 m/s ²
Force sensor - static calibration	<1 %	Application range
Displacement (including optical displacement sensors)	<1 %	Application range
Angle	<1,5 %	Application range
Angular velocity	<3 %	min 25% of full scale or 2 400°/s whichever is lower
Angular acceleration	<3 %	Application range
Pressure	1%	Application range
Temperature	<1 % or 0,2 K	Application range
Torque	<3 %	Application range
Seat belt sensor	<3%	Application range
NOTE Calculation of uncertainties according to JCGM 100:2008.		