

SVENSK STANDARD

SS-ISO 20816-1:2018



Fastställt/Approved: 2018-11-06
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 17.160; 21.120.40

Vibration och stöt – Mätning och värdering av maskinvibrationer – Del 1: Allmänna riktlinjer (ISO 20816-1:2016, IDT)

Mechanical vibration – Measurement and evaluation of machine vibration – Part 1: General guidelines (ISO 20816-1:2016, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80007708>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.


Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 20816-1:2016 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 20816-1:2016.

Denna standard ersätter SS-ISO 10816-1, utgåva 1 och SS-ISO 7919-1, utgåva 2 och SS-ISO 10816-1/Amd 1:2009, utgåva 1

The International Standard ISO 20816-1:2016 has the status of a Swedish Standard. This document contains the official English version of ISO 20816-1:2016.

This standard supersedes the SS-ISO 10816-1, edition 1 and SS-ISO 7919-1, edition 2 and SS-ISO 10816-1/Amd 1:2009, edition 1

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Maskiners påverkan av vibrationer, SIS/TK 111/AG 02.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Measurements	2
4.1 General	2
4.1.1 Overview.....	2
4.1.2 Vibration measurements	2
4.1.3 Frequency range.....	2
4.2 Types of measurements.....	2
4.2.1 Vibration measurements on non-rotating parts.....	2
4.2.2 Relative shaft vibration measurements.....	2
4.2.3 Absolute shaft vibration measurements.....	3
4.3 Measurement parameters.....	3
4.3.1 Measurement quantities	3
4.3.2 Vibration magnitude.....	4
4.3.3 Vibration severity	4
4.4 Measuring positions	4
4.4.1 Positions for measurements on non-rotating parts.....	4
4.4.2 Positions for measurements on rotating shafts.....	7
4.5 Machine support structure for acceptance testing	9
4.5.1 General.....	9
4.5.2 In-situ tests	9
4.5.3 In a test facility.....	10
4.6 Machine operating conditions.....	10
4.7 Evaluation of vibration from other sources	10
5 Instrumentation	10
6 Evaluation criteria	11
6.1 General	11
6.1.1 Overview.....	11
6.1.2 Types of measurement on rotating shafts.....	11
6.2 Factors affecting evaluation criteria.....	12
6.3 Types of evaluation criteria.....	12
6.3.1 General.....	12
6.3.2 Criterion I: Vibration magnitude at rated speed under steady operation conditions	12
6.3.3 Criterion II: Change in vibration magnitude	16
6.4 Operational limits.....	16
6.4.1 General.....	16
6.4.2 Setting of ALARMS.....	17
6.4.3 Setting of TRIPS	17
6.5 Additional factors	17
6.5.1 Vibration frequencies and vectors.....	17
6.5.2 Vibration sensitivity of the machine.....	17
6.5.3 Techniques for rolling element bearings	18
Annex A (informative) Explanation of measurement quantities	19
Annex B (informative) Techniques for detection of problems in rolling element bearings	26
Annex C (informative) Guidelines for specification of evaluation criteria for vibration measured on non-rotating parts and rotating shafts	28

Annex D (informative) Vector analysis of change in vibration	31
Bibliography	33

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 2, *Measurement and evaluation of mechanical vibration and shock as applied to machines, vehicles and structures*.

This first edition of ISO 20816-1 cancels and replaces ISO 7919-1:1996, ISO 10816-1:1995 and ISO 10816-1:1995/Amd 1:2009 which have been merged and editorially revised.

A list of all parts in the ISO 20816 series can be found on the ISO website.

Introduction

Machines are now being operated at increasingly high rotational speeds and loads, as well as more flexible operation at part and full load, and under increasingly severe operating conditions. This has become possible, to a large extent, by the more efficient use of materials, although this has sometimes resulted in there being less margin for design and application errors.

At present, it is not uncommon for continuous operation to be expected and required for 2 years or 3 years between maintenance operations. Consequently, more restrictive requirements are being specified for operating vibration values of rotating machinery, in order to ensure continued safe and reliable operation.

This document is a basic document which establishes general guidelines for the measurement and evaluation of mechanical vibration of machinery, as measured on rotating and on non-rotating (and, where applicable, non-reciprocating) parts of complete machines, such as shafts or bearing housings. Recommendations for measurements and evaluation criteria pertaining to specific machine types are provided in additional parts of ISO 20816 as they become available as a replacement of the relevant parts of ISO 7919 and ISO 10816. ISO/TR 19201 gives an overview over these and further machinery vibration standards.

For some machines, measurements made on non-rotating parts are sufficient to characterize adequately their running conditions with respect to trouble-free operation. There are also types of machine, such as steam turbines, gas turbines and turbo compressors, all of which can have several modes of vibration in the service speed range, for which measurements on structural members, such as the bearing housings, might not adequately characterize the running condition of the machine, although such measurements are useful. Such machines generally contain flexible rotor shaft systems, and changes in the vibration condition can be detected more decisively and more sensitively by measurements on the rotating elements. Machines having relatively stiff and/or heavy casings in comparison to rotor mass are typical of those classes of machines for which shaft vibration measurements are frequently preferred.

Vibration measurements are used for a number of purposes, ranging from routine operational monitoring and acceptance tests to advanced experimental testing, as well as diagnostic and analytical investigations. These various measurement objectives lead to many differences in methods of interpretation and evaluation. To limit the number of these differences, this document is designed to provide guidelines primarily for operational monitoring and acceptance tests.

Three primary vibration quantities (displacement, velocity and acceleration) are defined and their limitations given. Adherence to the guidelines presented should, in most cases, ensure satisfactory service performance.

Mechanical vibration — Measurement and evaluation of machine vibration —

Part 1: General guidelines

1 Scope

This document establishes general conditions and procedures for the measurement and evaluation of vibration using measurements made on rotating, non-rotating and non-reciprocating parts of complete machines. It is applicable to measurements of both absolute and relative radial shaft vibration with regard to the monitoring of radial clearances, but excludes axial shaft vibration. The general evaluation criteria, which are presented in terms of both vibration magnitude and change of vibration, relate to both operational monitoring and acceptance testing. They have been provided primarily with regard to securing reliable, safe, long-term operation of the machine while minimizing adverse effects on associated equipment. Guidelines are also presented for setting operational limits.

NOTE 1 The evaluation criteria for different classes of machinery will be included in other parts of ISO 20816 when they become available. In the meantime, guidelines are given in [Clause 6](#).

NOTE 2 The term “shaft vibration” is used throughout ISO 20816 because, in most cases, measurements are made on machine shafts. However, the ISO 20816 series is also applicable to measurements made on other rotating elements if such elements are found to be more suitable, provided that the guidelines are respected.

For the purposes of ISO 20816, operational monitoring is considered to be those vibration measurements made during the normal operation of a machine. The ISO 20816 series permits the use of different measurement quantities and methods, provided that they are well-defined and their limitations are set out, so that the interpretation of the measurements is well-understood.

The evaluation criteria relate only to the vibration produced by the machine itself and not the vibration transmitted to it from outside.

This document does not include consideration of torsional vibration.

NOTE 3 For torsional vibration, see, for example, ISO 3046-5, ISO 22266-1 or VDI 2039.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2954, *Mechanical vibration of rotating and reciprocating machinery — Requirements for instruments for measuring vibration severity*

ISO 5348, *Mechanical vibration and shock — Mechanical mounting of accelerometers*

ISO 10817-1, *Rotating shaft vibration measuring systems — Part 1: Relative and absolute sensing of radial vibration*

3 Terms and definitions

No terms and definitions are listed in this document.

SS-ISO 20816-1:2018 (E)

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Measurements

4.1 General

4.1.1 Overview

This clause describes the measurements, procedures and operating conditions recommended for assessing machine vibration. The guidelines given permit the evaluation of vibration in accordance with the general criteria and principles given in [Clause 6](#).

4.1.2 Vibration measurements

It is common practice to measure vibration on non-rotating parts or to measure relative shaft vibration, or both. The measurement type for the protection system is normally based on the experience from the machine manufacturer.

4.1.3 Frequency range

The measurement of vibration shall be broad band, so that the frequency spectrum of the machine is adequately covered.

The frequency range depends on the type of machine being considered (e.g. the frequency range necessary to assess the integrity of rolling element bearings should include frequencies higher than those on machines with fluid-film bearings only).

Guidelines for instrumentation frequency ranges for specific machine classes are given in the appropriate parts of ISO 20816.

NOTE 1 In the past, broad-band measurements in the range 10 Hz to 1 000 Hz were the intended metric for full-load acceptance testing. This might not meet the requirements of a condition monitoring scheme and might need to be modified for the purposes of vibration monitoring and diagnostics.

NOTE 2 Vibration condition monitoring and diagnostics of machines are described in ISO 13373.

On certain equipment, e.g. gearboxes and rolling element bearings, it can be appropriate to use a different frequency range for acceptance purposes.

4.2 Types of measurements

4.2.1 Vibration measurements on non-rotating parts

Vibration measurements on non-rotating parts are generally carried out with a seismic transducer which senses the absolute velocity or acceleration of structure parts on which it is mounted (e.g. the bearing housing).

4.2.2 Relative shaft vibration measurements

Relative shaft vibration measurements are generally carried out with a non-contacting transducer which senses the vibratory displacement between the shaft and a structural member on which it is mounted (e.g. the bearing housing).

4.2.3 Absolute shaft vibration measurements

Absolute shaft vibration measurements are carried out by one of the following methods:

- a) by a shaft-riding probe on which a seismic transducer (velocity type or accelerometer) is mounted so that it measures absolute shaft vibration directly;
- b) by a non-contacting transducer which measures relative shaft vibration in combination with a seismic transducer (velocity type or accelerometer) which measures the support vibration. Both transducers shall be mounted close together so that they undergo the same absolute motion in the direction of measurement. Their conditioned outputs are summed to provide a measurement of the absolute shaft motion.

NOTE In order to avoid incorrect results, it is important to ensure that the same datum time reference be used for the outputs from both the seismic and non-contacting transducers.

4.3 Measurement parameters

4.3.1 Measurement quantities

For the purposes of this document, the following measurement quantities can be used:

- a) vibration displacement, measured in micrometres;
- b) vibration velocity, measured in millimetres per second;
- c) vibration acceleration, measured in metres per square second.

The use, application and limitations of these quantities are discussed in [Clause 6](#).

Generally, there is no simple relationship between broad-band acceleration, velocity and displacement; nor is there between peak (0-p), peak-to-peak (p-p), root-mean-square (r.m.s.) and average values of vibration. The reasons for this are briefly discussed in [A.1](#), which also defines some precise relationships between the above quantities when the harmonic content of the vibration waveform is known.

In order to avoid confusion and to ensure correct interpretation, it is important at all times to identify clearly the measurement quantity and its unit, e.g. peak-to-peak displacement in μm ($1 \mu\text{m} = 10^{-6} \text{m}$), r.m.s. velocity in mm/s.

NOTE Vibration is a vector quantity and therefore, when comparing two different values, it can be necessary to consider the phase angle between them (see [Annex D](#)).

Generally, it can be stated that the preferred measurement quantity for the measurement of vibration of non-rotating parts is r.m.s. velocity while the preferred measurement quantity for the measurement of shaft vibration is peak-to-peak displacement.

Since this document applies to both relative and absolute shaft vibration measurements, displacement is further defined as follows:

- relative displacement which is the vibratory displacement of the shaft with reference to support structure, such as a bearing housing or machine casing;
- absolute displacement which is the vibratory displacement of the shaft with reference to an inertial reference system.

It should be clearly indicated whether displacement values are relative or absolute.

Relative and absolute displacements are further defined by several different displacement quantities, each of which is now in widespread use. These include the following: