

SVENSK STANDARD

SS-ISO 19642-7:2019

Fastställt/Approved: 2019-02-14
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 43.040.10

Vägfordon – Elledningar –

Del 7: Mått och krav för enkel- och flerledare av koppar, runda, skärmade och oskärmade med skyddshölje, avsedda för 30 V växelström eller 60 V likström (ISO 19642-7:2019, IDT)

Road vehicles – Automotive cables –

Part 7: Dimensions and requirements for 30 V a.c. or 60 V d.c. round, sheathed, screened or unscreened multi or single core copper conductor cables (ISO 19642-7:2019, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80009890>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 19642-7:2019 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 19642-7:2019.

The International Standard ISO 19642-7:2019 has the status of a Swedish Standard. This document contains the official English version of ISO 19642-7:2019.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Uppllysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Elledningar för vägfordon, SIS/TK 240/AG 04.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

Foreword	v
Introduction	vi
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Specifications	7
4.1 General test conditions	7
4.2 Safety concerns.....	8
4.3 Voltage rating.....	8
4.4 Temperature classes.....	8
4.5 Conductor material.....	8
4.6 Conductors	8
4.7 Sheath thickness	8
4.8 Core cable outside diameter	8
4.9 Representative conductor sizes for testing	8
4.10 Reference and requirements for the tests according to ISO 19642-2.....	8
5 Requirements for single-core cables	10
6 Requirements for round, sheathed, screened or unscreened multi or single core cables	11
6.1 General	11
6.2 Dimensional tests	11
6.2.1 Cable outside and inner layer diameters	11
6.2.2 Ovality of sheath.....	11
6.2.3 Thickness of sheath.....	11
6.2.4 In-process cable outside diameter	11
6.3 Electrical tests.....	11
6.3.1 Electrical continuity.....	11
6.3.2 Withstand voltage at final inspection.....	12
6.3.3 Screening effectiveness.....	12
6.3.4 Sheath fault on screened cables.....	12
6.4 Mechanical tests.....	12
6.4.1 Strip force of sheath.....	12
6.4.2 Cyclic bending.....	12
6.4.3 Flexibility	12
6.5 Environmental tests	13
6.5.1 Test specimen preparation and winding tests.....	13
6.5.2 Long term heat ageing, 3 000 h at temperature class rating.....	13
6.5.3 Short term heat ageing, 240 h at temperature class rating +25 °C.....	13
6.5.4 Thermal overload, 6 h at temperature class rating +50 °C	13
6.5.5 Pressure test at high temperature	13
6.5.6 Shrinkage by heat of sheath.....	13
6.5.7 Low temperature winding.....	13
6.5.8 Cold impact.....	13
6.5.9 Temperature and humidity cycling	14
6.5.10 Resistance to liquid chemicals.....	14
6.5.11 Durability of sheath marking	14
6.5.12 Resistance to ozone.....	14
6.5.13 Artificial weathering.....	14
6.5.14 Resistance to flame propagation	14
Annex A (informative) Dimensions of preferred constructions	15
Bibliography	21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 32, *Electrical and electronic components and general system aspects*.

A list of all parts in the ISO 19642 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document was prepared following a joint resolution to improve the general structure of the ISO Automotive Electric Cable standards. This new structure adds more clarity and, by defining a new standard family, opens up the standard for future amendments.

Many other standards currently refer to ISO 6722-1, ISO 6722-2 and ISO 14572. So these standards will stay valid at least until the next scheduled systematic review and will be replaced later on by the ISO 19642 series.

For new Automotive Cable Projects customers and suppliers are advised on using the ISO 19642 series.

Road vehicles — Automotive cables —

Part 7:

Dimensions and requirements for 30 V a.c. or 60 V d.c. round, sheathed, screened or unscreened multi or single core copper conductor cables

WARNING — The use of this document can involve hazardous materials, operations and equipment. This document does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this document to establish appropriate safety practices and determine the applicability of regulatory limitations prior to use.

1 Scope

This document specifies the dimensions and requirements for multi or single core cables intended for use in road vehicle applications where the nominal system voltage is 30 V a.c. or 60 V d.c.. It also applies to individual cores in multi core and single core cables.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19642-1, *Road vehicles — Automotive cables — Vocabulary and design guidelines*

ISO 19642-2, *Road vehicles — Automotive cables — Test methods*

ISO 19642-3, *Road vehicles — Automotive cables — Dimensions and requirements — 30 V a.c. or 60 V d.c. single core copper cables*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19642-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Specifications

4.1 General test conditions

The test conditions of ISO 19642-2 shall apply.

The cables shall be submitted to the tests as specified in [Table 1](#).

If suppliers and customers agree upon modifications or changes to the methods and requirements, all the changes and modifications shall be clearly documented.

4.2 Safety concerns

The precautions as described in the WARNING at the beginning of this document shall be followed.

4.3 Voltage rating

The voltage rating is established by the rating of the cores 30 V a.c. or 60 V d.c..

4.4 Temperature classes

The temperature class rating is established by the rating(s) of the cores and sheath.

The rating of the cable shall be equal to the lowest rating of the individual cores and sheath.

For details on temperature classes, see ISO 19642-1.

4.5 Conductor material

The conductor material shall be according to ISO 19642-3.

4.6 Conductors

The conductors of the core or cores shall be according to ISO 19642-3.

4.7 Sheath thickness

Two different sheath thicknesses are allowed in this document:

1. thin wall sheath;
2. thick wall sheath.

The insulation wall thickness of the core or cores shall be according to ISO 19642-3.

4.8 Core cable outside diameter

The maximum and minimum outside cable diameter for the core or cores shall be according to ISO 19642-3.

4.9 Representative conductor sizes for testing

When a test is required, all combinations of conductor size, insulation thickness and insulation formulation shall meet the specified requirements.

However, if testing of representative conductor sizes is permitted by agreement between the customer and the supplier, compliance for a cable family may be demonstrated by testing examples of large and small conductor sizes only.

4.10 Reference and requirements for the tests according to ISO 19642-2

Additional production processes in a multi core cable (such as twisting, braiding, jacket extrusion) influence the properties of the cores in the finished cable. Thus for the dimensions and maximum conductor resistance of the used cores the requirements of ISO 19642-3 apply with the following additions:

The minimum wall thickness may follow the design guidelines in ISO 19642-1:—¹⁾, A.4.

1) Under preparation.

The maximum resistance of cores may follow the design guidelines in ISO 19642-1 :—, A.5.

The values for maximum conductor resistance and minimum wall thickness of the insulation should be documented in the data sheet of the supplier and are the basis for assessment.

Dimensions of preferred constructions for round, sheathed, screened or unscreened multi or single core copper conductor cables are presented in Annex A, Tables A.1 through A.6.

A complete definition of all possible multi core cables is not feasible. In addition to the preferred constructions other constructions are permissible using the calculation rules in ISO 19642-1:—, Annex A.

The diameter under sheath may be calculated according to ISO 19642-1:—, A.3.

The wall thickness of sheath and the bedding layer may be calculated according to ISO 19642-1:—, A.6.

The maximum and minimum outside cable diameter may be calculated according to ISO 19642-1:—, A.9.

The dimensions of all cables should be documented in the datasheet of the supplier and are the basis for assessment.

Table 1 provides a list of all relevant tests in ISO 19642-2:2019 for round, sheathed, screened or unscreened multi or single core cables.

Table 1 — Tests

Test description	Mandatory			If required ^c	
	In process ^a	Initial certification	Periodic ^b	Initial certification	Periodic ^b
6.1 Dimensional tests					
6.1.1 Cable outside and inner layer diameters	—	X	X	—	—
6.1.2 Ovality of sheath	—	—	—	X	X
6.1.3 Thickness of sheath	—	X	X	—	—
6.1.4 In-process cable outside diameter	X	—	—	—	—
6.2 Electrical tests					
6.2.1 Electrical continuity	—	X	X	—	—
6.2.2 Withstand voltage at final inspection	X	X	X	—	—
6.2.3 Screening effectiveness					
6.2.3.1 Purpose					
6.2.3.2 d.c. resistance of the screen	—	—	—	X	X
6.2.3.3 Surface transfer impedance — Tri-axial method	—	—	—	X	X

Key

X: Test shall be performed according to ISO 19642-2

—: Test is not required

^a A test made on entire cable length during or after manufacture.

^b The frequency of periodic testing shall be established by agreement between the customer and the supplier.

^c The usage of "If required" tests shall be established by agreement between the customer and the supplier.

^d These tests are only used in preparation and after environmental endurance tests.

^e Only one of the two abrasion tests has to be performed as to agreement between the customer and the supplier.

^f Compliance for a cable family may be demonstrated by testing examples of large and small conductor sizes only.

^g Some fluids are for "Initial certification" and others are "if required".

Table 1 (continued)

Test description	Mandatory			If required ^c	
	In process ^a	Initial certification	Periodic ^b	Initial certification	Periodic ^b
6.2.3.4 Screening attenuation — Absorbing clamp method	—	—	—	X	X
6.2.3.5 Screening attenuation — Tri-axial method	—	—	—	X	X
6.2.4 Sheath fault on screened cables	X	—	—	—	—
6.3 Mechanical tests					
6.3.1 Strip force of sheath	—	—	—	X	X
6.3.2 Cyclic bending	—	—	—	X	—
6.3.3 Flexibility	—	—	—	X	—
6.4 Environmental tests					
6.4.1 Test specimen preparation and winding tests ^d	—	—	—	—	—
6.4.2 Long term heat ageing, 3 000 h at temperature class rating	—	X	—	—	—
6.4.3 Short term heat ageing, 240 h at temperature class rating +25 °C	—	X	X	—	—
6.4.4 Thermal overload, 6 h at temperature class rating +50 °C	—	—	—	X	X
6.4.5 Pressure test at high temperature	—	X	X	—	—
6.4.6 Shrinkage by heat of sheath	—	X	X	—	—
6.4.7 Low temperature winding	—	X	X	—	—
6.4.8 Cold impact	—	—	—	X	X
6.4.9 Temperature and humidity cycling ^f	—	—	—	X	—
6.4.10 Resistance to liquid chemicals ^{f, g}	—	X	—	X	—
6.4.11 Durability of sheath marking ^f	—	—	—	X	X
6.4.12 Resistance to ozone ^f	—	—	—	X	—
6.4.13 Artificial weathering ^f	—	—	—	X	—
6.4.14 Resistance to flame propagation	—	X	X	—	—
Key					
X: Test shall be performed according to ISO 19642-2					
—: Test is not required					
^a A test made on entire cable length during or after manufacture.					
^b The frequency of periodic testing shall be established by agreement between the customer and the supplier.					
^c The usage of "If required" tests shall be established by agreement between the customer and the supplier.					
^d These tests are only used in preparation and after environmental endurance tests.					
^e Only one of the two abrasion tests has to be performed as to agreement between the customer and the supplier.					
^f Compliance for a cable family may be demonstrated by testing examples of large and small conductor sizes only.					
^g Some fluids are for "Initial certification" and others are "if required".					

5 Requirements for single-core cables

Cores shall fulfill the requirements of ISO 19642-3 with thin or thick wall dimensions.

Any construction with inner conductors that do not match ISO 19642-3 due to additional protection by the sheath are considered special purpose cable and captured as an agreement between the customer and the supplier.

6 Requirements for round, sheathed, screened or unscreened multi or single core cables

6.1 General

The cables shall be tested per ISO 19642-2 according to their temperature class rating.

The cables shall be tested as specified in [Table 1](#).

6.2 Dimensional tests

6.2.1 Cable outside and inner layer diameters

Measure the following parameters, if applicable:

- outside diameter of twisted cores;
- outside diameter of bedding layer;
- outside diameter of braid;
- outside diameter of foils;
- outside diameter of jacket.

Dimensions shall be within the limits established by agreement between the customer and the supplier.

6.2.2 Ovality of sheath

Ovality shall be less than 10 %, measured immediately after extrusion.

NOTE Ovality can be different after handling due to mechanical deformation.

6.2.3 Thickness of sheath

The thickness of sheath shall be within the limits established by agreement between the customer and the supplier.

The measuring should be without the inner covering (bedding layer).

6.2.4 In-process cable outside diameter

In-process cable outside diameter monitoring is mandatory.

The cable outside diameter measurement shall be within the specified limits.

6.3 Electrical tests

6.3.1 Electrical continuity

The indicator shall show continuity.