

SVENSK STANDARD

SS-ISO 23274-1:2019

Fastställt/Approved: 2019-09-02
Utgåva/Edition: 2
Språk/Language: engelska/English
ICS: 43.120

Hybrid-eldrivna vägfordon – Mätning av avgasutsläpp och bränsleförbrukning –

Del 1: Fordon utan extern laddning (ISO 23274-1:2019, IDT)

Hybrid-electric road vehicles – Exhaust emissions and fuel consumption measurements –

Part 1: Non-externally chargeable vehicles (ISO 23274-1:2019, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80015367>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 23274-1:2019 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 23274-1:2019.

Denna standard ersätter SS-ISO 23274-1:2013, utgåva 1

The International Standard ISO 23274-1:2019 has the status of a Swedish Standard. This document contains the official English version of ISO 23274-1:2019.

This standard supersedes the SS-ISO 23274-1:2013, edition 1

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för EI- och hybridfordon, SIS/TK 517.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

| | |
|-------------------------------------------------------------------------------------------|-----------|
| Foreword | v |
| 1 Scope..... | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Test conditions and instrumentation..... | 3 |
| 4.1 Test conditions..... | 3 |
| 4.1.1 General..... | 3 |
| 4.1.2 Ambient temperature..... | 3 |
| 4.1.3 Vehicle conditions..... | 3 |
| 4.1.4 Chassis dynamometer conditions..... | 4 |
| 4.2 Test instrumentation..... | 5 |
| 5 Measurement of exhaust emissions and fuel consumption..... | 5 |
| 5.1 General | 5 |
| 5.2 Test procedure | 5 |
| 5.2.1 Vehicle preconditioning | 5 |
| 5.2.2 Vehicle soak..... | 5 |
| 5.2.3 Vehicle movement to the test room..... | 5 |
| 5.2.4 Measurement over ADT..... | 5 |
| 5.3 Correction of the test results | 6 |
| 5.3.1 General..... | 6 |
| 5.3.2 Allowable range of RESS energy balance..... | 6 |
| 5.3.3 Correction procedure by correction coefficient..... | 6 |
| 6 Calculations and expressions..... | 6 |
| Annex A (informative) Linear correction method using a correction coefficient..... | 7 |
| Annex B (informative) Calculation of allowable range of RESS energy change | 10 |
| Annex C (informative) Theory for the linear regression method | 12 |
| Annex D (informative) Guidelines for charge balance measurement | 14 |
| Bibliography..... | 23 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 37, *Electrically propelled vehicles*.

This second edition cancels and replaces the first edition (ISO 23274-1:2013), which has been technically revised.

The main changes compared to the previous edition are as follows:

- the content of ISO/TR 11955:2008, *Hybrid-electric road vehicles — Guidelines for charge balance measurement* was merged with this document as [Annex D](#).

A list of all parts in the ISO 23274 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Hybrid-electric road vehicles — Exhaust emissions and fuel consumption measurements —

Part 1: Non-externally chargeable vehicles

1 Scope

This document specifies a chassis dynamometer test procedure to measure the exhaust emissions and the electric energy and fuel consumption for the vehicles.

This document applies to vehicles with the following characteristics:

- vehicles classified as passenger cars or light duty trucks, as defined in the relevant regional applicable driving test (ADT) standard;
- the nominal energy of the rechargeable energy storage system (RESS) is at least 2 % of the total energy consumption over an ADT;
- internal combustion engine (ICE) only using liquid fuels (for example, gasoline and diesel fuel).

NOTE In the case of the vehicles with ICE using other fuel [for example, compressed natural gas (CNG), liquefied petroleum gas (LPG), hydrogen], this document can apply except the measurement of consumed fuel; otherwise the measurement method for those using the corresponding fuel can apply.

This document proposes procedures for correcting the measured emissions and fuel consumption of hybrid-electric vehicles (HEVs), in order to obtain the values when the state of charge (SOC) of the RESS does not remain the same between the beginning and the end of an ADT.

It can also be applied to measurement procedures for exhaust emissions and fuel consumption of externally chargeable HEVs when a vehicle is not externally charged and operated only in the charge sustaining (CS) state, as described in ISO 23274-2.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10521 (all parts), *Road vehicles — Road load*

ISO/TR 8713, *Electrically propelled road vehicles — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/TR 8713 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

SS-ISO 23274-1:2019 (E)

3.1 applicable driving test ADT

single driving test schedule which is specified for a relevant region

Note 1 to entry: Chassis dynamometer test schedules for a relevant region are the Worldwide Light-duty Test Cycle (WLTC) or the Urban Dynamometer Driving Schedule (UDDS), for example.

3.2 charge balance of RESS

change of charge in the *RESS* (3.10) during fuel consumption measurement

Note 1 to entry: Normally expressed in ampere hours (Ah).

3.3 coulomb efficiency Ah efficiency

efficiency of the battery, based on electricity in coulomb for a specified charge/discharge procedure, expressed by output electricity divided by input electricity

3.4 energy balance of RESS

ΔE_{RESS}
change of *RESS* (3.10) energy state during an *applicable driving test* (3.1)

Note 1 to entry: Normally expressed in watt hours (Wh).

Note 2 to entry: For practical use, the energy balance of RESS is approximated by multiplying the *charge balance of RESS* (3.2) in ampere hours (Ah) by the nominal voltage in volts (V).

3.5 energy efficiency Wh efficiency

efficiency of the battery, based on energy for a specified charge/discharge procedure, expressed by output energy divided by input energy

3.6 externally chargeable HEV

HEV (3.7) with a *RESS* (3.10) that is intended to be charged from an external electric energy source

Note 1 to entry: External charge for the purpose of conditioning of the RESS is not included.

Note 2 to entry: Externally chargeable HEVs are widely known as plug-in HEVs (PHEVs).

3.7 hybrid-electric vehicle HEV

vehicle with both a *RESS* (3.10) and a fuelled power source for propulsion

EXAMPLE Internal combustion engine or fuel cell systems are typical types of fuelled power sources.

3.8 non-externally chargeable HEV

HEV (3.7) with a *RESS* (3.10) that is not intended to be charged from an external electric energy source

3.9 rated capacity

supplier's specification of the total number of ampere hours that can be withdrawn from a fully charged battery pack or system for a specified set of test conditions such as discharge rate, temperature and discharge cut-off voltage

3.10
rechargeable energy storage system
RESS

rechargeable system that stores energy for delivery of electric energy for the electric drive

EXAMPLE Batteries or capacitors.

3.11
regenerative braking

braking with conversion of kinetic energy into electric energy for charging the *RESS* ([3.10](#))

3.12
state of charge
SOC

available capacity of a *RESS* ([3.10](#)) or *RESS* subsystem expressed as a percentage of *rated capacity* ([3.9](#))

4 Test conditions and instrumentation

4.1 Test conditions

4.1.1 General

For test conditions, [4.1.2](#) to [4.1.4](#) apply. Otherwise, the test conditions of the relevant regional ADT standards apply.

4.1.2 Ambient temperature

Tests shall be conducted at ambient temperature of (25 ± 5) °C.

4.1.3 Vehicle conditions

4.1.3.1 Vehicle conditioning

Prior to testing, the test vehicle with *RESS* shall be stabilized as specified by the manufacturers, or the mileage shall be accumulated to above 3 000 km and less than 15 000 km.

4.1.3.2 Vehicle appendages

Vehicles shall be tested with normal appendages (mirrors, bumpers, etc.). When the vehicle is on the dynamometer, certain items (e.g. hub caps) should be removed for safety reasons, where necessary.

4.1.3.3 Vehicle test mass

The vehicle test mass shall be selected in accordance with the relevant regional ADT standards.

4.1.3.4 Tyres

4.1.3.4.1 General

The correctly rated tyres as recommended by the vehicle manufacturer shall be used.

4.1.3.4.2 Tyre pressure

The vehicle tyres shall be inflated to the pressure specified by the vehicle manufacturer in accordance with the test chosen (track or chassis dynamometer).

SS-ISO 23274-1:2019 (E)

4.1.3.4.3 Tyre conditioning

The tyres shall be conditioned as recommended by the vehicle manufacturer.

4.1.3.5 Lubricants

The vehicle lubricants normally specified by the manufacturer shall be used.

4.1.3.6 Gear shifting

If the vehicle is fitted with a manually shifted gear box, gear shifting positions shall correspond to the relevant regional ADT standard. However, the shift positions should be selected and determined in accordance with the vehicle manufacturer's specification.

4.1.3.7 Regenerative braking

If the vehicle has regenerative braking, the regenerative braking system shall be enabled for all dynamometer testing except where specified in [4.1.4.4](#) determining the dynamometer load coefficient.

If the vehicle is tested on a single axle dynamometer and is equipped with systems such as an antilock braking system (ABS) or a traction control system (TCS), those systems may inadvertently interpret the non-movement of the set of wheels that are off the dynamometer as a malfunctioning system. If so, these systems shall be temporarily disabled for adjustment to achieve normal operation of the remaining vehicle systems, including the regenerative braking system.

4.1.3.8 RESS conditioning

The RESS shall be conditioned with the vehicle as specified in [4.1.3.1](#), or by equivalent conditioning.

4.1.4 Chassis dynamometer conditions

4.1.4.1 General

The vehicle should generally be tested on a single axle chassis dynamometer. A vehicle with four-wheel drive shall be tested by modifying the drive train of the vehicle. When the vehicle is modified, the details shall be explained in the test report.

Double axle chassis dynamometer testing should be performed if a modification for single axle chassis dynamometer testing is not possible for a specific four-wheel drive vehicle.

4.1.4.2 Dynamometer calibration

The dynamometer shall be calibrated in accordance with the specifications indicated in the service manual provided by the dynamometer manufacturers.

4.1.4.3 Dynamometer warm-up

The dynamometer shall be warmed up sufficiently prior to testing.

4.1.4.4 Determining the dynamometer load coefficient

The determination of vehicle road load and the reproduction on a chassis dynamometer shall conform to the ISO 10521 series Vehicles equipped with regenerative braking systems that are activated at least in part when the brake pedal is not depressed shall have regenerative braking disabled during the deceleration portion of coast-down testing on both the test track and dynamometer.

4.2 Test instrumentation

Test instrumentation shall have accuracy levels as shown in [Table 1](#), unless specified differently by the relevant regional ADT standards.

Table 1 — Accuracy of measured values

| Item | Unit | Accuracy |
|---------------------------------------------------------------------------------------------------------------|------|---------------------|
| Time | s | ±0,1 s |
| Distance | m | ±0,1 % |
| Temperature | °C | ±1 °C |
| Speed | km/h | ±1 % |
| Mass | kg | ±0,5 % |
| Current | A | ±0,5 % ^a |
| Capacitor voltage | V | ±0,5 % |
| ^a Accuracy for measure value: ±0,5% full scale deflection or ±1% of reading, whichever is greater. | | |

5 Measurement of exhaust emissions and fuel consumption

5.1 General

The ADT procedure shall be selected according to the relevant regional ADT standards. Common requirements, if not described in the relevant regional ADT standards, are described below.

5.2 Test procedure

5.2.1 Vehicle preconditioning

Vehicle preconditioning shall be carried out in accordance with the relevant regional ADT standard, if necessary.

If necessary, the RESS SOC may be preadjusted by charging or discharging, to obtain a suitable energy balance of RESS between the beginning and the end of the test.

5.2.2 Vehicle soak

The vehicle shall be soaked in accordance with the relevant regional ADT standards.

5.2.3 Vehicle movement to the test room

When the vehicle is brought into the test room, and moved during the test if necessary, it shall be pushed or towed (neither driven nor regenerative recharged). The test vehicle shall be set on the chassis dynamometer after the chassis dynamometer has warmed up just before the test. The vehicle shall not be activated during soak until right before starting the test.

5.2.4 Measurement over ADT

Energy balance of RESS, consumed fuel and exhaust emissions shall be measured in each ADT. The conditions of the vehicle during the ADT shall follow the relevant regional ADT standards.