


SVENSK STANDARD

SS-ISO 16992:2021

Personbilsdäck – Ersättningsutrustning för reservhjul
(ISO 16992:2018, IDT)

Passenger car tyres – Spare unit substitutive equipment (SUSE)
(ISO 16992:2018, IDT)



sis Svenska
Institutet för
Standarder

Language: engelska/English

Edition: 3

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80030325>

Den här standarden kan hjälpa dig att effektivisera och kvalitetssäkra ditt arbete. SIS har fler tjänster att erbjuda dig för att underlätta tillämpningen av standarder i din verksamhet.

SIS Abonnemang

Snabb och enkel åtkomst till gällande standard med SIS Abonnemang, en prenumerationstjänst genom vilken din organisation får tillgång till all världens standarder, senaste uppdateringarna och där hela din organisation kan ta del av innehållet i prenumerationen.

Utbildning, event och publikationer

Vi erbjuder även utbildningar, rådgivning och event kring våra mest sålda standarder och frågor kopplade till utveckling av standarder. Vi ger också ut handböcker som underlättar ditt arbete med att använda en specifik standard.

Vill du delta i ett standardiseringsprojekt?

Genom att delta som expert i någon av SIS 300 tekniska kommittéer inom CEN (europeisk standardisering) och/eller ISO (internationell standardisering) har du möjlighet att påverka standardiseringsarbetet i frågor som är viktiga för din organisation. Välkommen att kontakta SIS för att få veta mer!

Kontakt

Skriv till kundservice@sis.se, besök [sis.se](https://www.sis.se) eller ring 08 - 555 523 10

© Copyright/Upphovsrätten till denna produkt tillhör Svenska institutet för standarder, Stockholm, Sverige. Upphovsrätten och användningen av denna produkt regleras i slutanvändarlicensen som återfinns på [sis.se/slutanvandarlicens](https://www.sis.se/slutanvandarlicens) och som du automatiskt blir bunden av när du använder produkten. För ordlista och förkortningar se [sis.se/ordlista](https://www.sis.se/ordlista).

© Copyright Svenska institutet för standarder, Stockholm, Sweden. All rights reserved. The copyright and use of this product is governed by the end-user licence agreement which you automatically will be bound to when using the product. You will find the licence at [sis.se/enduserlicenseagreement](https://www.sis.se/enduserlicenseagreement).

Upplysningar om sakinnehållet i standarden lämnas av Svenska institutet för standarder, telefon 08 - 555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Standarden är framtagen av kommittén för Däck och hjul, SIS/TK 218.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Den internationella standarden ISO 16992:2018 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 16992:2018.

Denna standard ersätter SS-ISO 16992:2010, utgåva 2

The International Standard ISO 16992:2018 has the status of a Swedish Standard. This document contains the official English version of ISO 16992:2018.

This standard supersedes the SS-ISO 16992:2010, edition 2

LÄSANVISNINGAR FÖR STANDARDER

I dessa anvisningar behandlas huvudprinciperna för hur regler och yttre begränsningar anges i standardiseringsprodukter.

Krav

Ett krav är ett uttryck i ett dokumentets innehåll som anger objektivet verifierbara kriterier som ska uppfyllas och från vilka ingen avvikelse tillåts om efterlevnad av dokumentet ska kunna åberopas. Krav uttrycks med hjälpverbet ska (eller ska inte för förbud).

Rekommendation

En rekommendation är ett uttryck i ett dokumentets innehåll som anger en valmöjlighet eller ett tillvägagångssätt som bedöms vara särskilt lämpligt utan att nödvändigtvis nämna eller utesluta andra. Rekommendationer uttrycks med hjälpverbet bör (eller bör inte för avrådanden).

Instruktion

Instruktioner anges i imperativ form och används för att ange hur något görs eller utförs. De kan underordnas en annan regel, såsom ett krav eller en rekommendation. De kan även användas självständigt, och är då att betrakta som krav.

Förklaring

En förklaring är ett uttryck i ett dokumentets innehåll som förmedlar information. En förklaring kan uttrycka tillåtelse, möjlighet eller förmåga. Tillåtelse uttrycks med hjälpverbet får (eller motsatsen behöver inte). Möjlighet och förmåga uttrycks med hjälpverbet kan (eller motsatsen kan inte).

READING INSTRUCTIONS FOR STANDARDS

These instructions cover the main principles for the use of provisions and external constraints in standardization deliverables.

Requirement

A requirement is an expression, in the content of a document, that conveys objectively verifiable criteria to be fulfilled, and from which no deviation is permitted if conformance with the document is to be claimed. Requirements are expressed by the auxiliary shall (or shall not for prohibition).

Recommendation

A recommendation is an expression, in the content of a document, that conveys a suggested possible choice or course of action deemed to be particularly suitable, without necessarily mentioning or excluding others. Recommendations are expressed by the auxiliary should (or should not for dissuasion).

Instruction

Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	3
5 Conformance	4
6 SUSE systems	4
6.1 General	4
6.2 Function and performance	4
7 Endurance test	8
7.1 Endurance test for a run-flat tyre, or a self-supporting tyre, or a tyre equipped with the internal supporting ring.....	8
7.2 Endurance test for an extended mobility tyre.....	10
8 Markings	10
Annex A (informative) Properties of a SUSE providing restored mobility	11
Annex B (informative) Properties of a SUSE providing preserved mobility	12
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 31, *Tyres, rims and valves*, Subcommittee SC 3, *Passenger car tyres and rims*.

This third edition cancels and replaces the second edition (ISO 16992:2010), which has been technically revised through the following significant changes:

- new “extended mobility tyres” definition and pictogram added;
- “extended mobility system” definition renamed “SUSE system”;
- TPMS definition added;
- endurance testing conditions for run-flat tyres better defined with the aim to avoid interpretations while improving the test repeatability;
- new endurance test for extended mobility tyres added;
- Figure 3: symbol for internal support ring amended as per ISO TC 145/SC 3 recommendation to comply with ISO/IEC Directives (SPR letters removed).

This corrected version of ISO 16992:2018 incorporates the following correction: the dimensions of [Figure 2](#) have been corrected.

Introduction

In order to ensure unrestricted mobility, road vehicles should be equipped with fully efficient tyres in all positions.

Road vehicles are therefore traditionally provided with a spare unit intended to reinstate vehicle mobility in the event of loss of efficiency of one tyre. The spare unit can be either of the following:

- of the same type of the units normally equipping the vehicle, or
- of “temporary use” type, thus intended for use only under restricted conditions.

Some vehicles, however, can be constructed and provided with devices that can reinstate their mobility even in the absence of a spare unit on board. Various types of such devices (emergency solutions, products and systems) are available to users in order to ensure that they are able to continue their journey in the event of loss of efficiency of one or more tyres.

The term “spare unit substitutive equipment (SUSE)” (see [3.6](#)) is used as a general name for all equipment intended to replace a spare unit on board the vehicle.

The term “SUSE system” (see [3.7](#)) refers to the assembly of several independent but interacting components specified and approved by a system manager.

This document mainly concerns the SUSE systems for vehicles equipped with passenger car tyres, thus allowing driving to continue in restricted conditions after a loss of efficiency of at least one of the tyres of the vehicle.

This document specifies minimum performance levels for SUSE. It provides guidance when establishing objective requirements for a SUSE and allows the standard level of a given existing SUSE system to be determined.

It is recommended that for any on-road application of run-flat or extended mobility tyres, they be mounted on rims with humps on both inboard and outboard sides.

Passenger car tyres — Spare unit substitutive equipment (SUSE)

1 Scope

This document describes spare unit substitutive equipment (SUSE) for passenger car tyres, which is designed to enable users to continue their journey (with or without a stop) in a reasonably safe manner.

NOTE 1 Certain equipment becomes effective automatically, thus avoiding the need to stop the vehicle immediately for inspection and corrective action.

This document is intended only to qualify the performance of SUSE systems. Its specifications only apply to SUSE systems that can permit the extended mobility of the vehicle.

NOTE 2 Other types of SUSE are described in [Annexes A](#) and [B](#).

The specifications in this document apply from the moment the SUSE system becomes effective, with the driver continuing to control the vehicle (in terms of speed and direction) in an attempt to reach an appropriate place for servicing.

The following are within the scope of this document:

- the description of the various types of SUSE;
- the description and performance levels of complete SUSE systems.

NOTE 3 The performance level that the user reasonably has the right to expect, as well as the restrictive conditions placed upon that level, can vary to a large degree depending on the equipment installed and on the real operating conditions of the tyre in flat-tyre running mode.

The following are outside the scope of this document:

- the vehicle to be equipped;
- the tyre while operating in inflated mode;
- the characteristics of the pressure survey device and of the warning function relative to the inflated mode or to the partially deflated mode due to slow pressure losses;
- the transitory phase, if any, before the equipment becomes effective;
- the inspection, assessment, and the servicing of the SUSE system, after it has been activated in flat tyre running mode.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4000 (all parts), *Passenger car tyres and rims*

ISO 10191, *Passenger car tyres — Verifying tyre capabilities — Laboratory test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

SS-ISO 16992:2021 (E)

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1
tyre
pneumatic tyre which is a flexible component of the wheel assembly made of rubber and reinforcing materials

Note 1 to entry: Inflating the tyre with compressed gas, as described in [5.1](#), enables the tyre to carry the wheel load as a part of an axle load and to transmit longitudinal and transversal forces. In the unladen condition, the inflated tyre is essentially toroidal.

3.2
run-flat tyre
self supporting tyre
SST
tyre structure provided with any technical solutions (for example, reinforced sidewalls, etc.) designed to operate in an inflated mode and allowing the tyre, mounted on the appropriate wheel and in the absence of any supplementary component, to supply the vehicle with the basic tyre functions at a specified speed and distance when operating in flat tyre running mode, able to successfully complete the endurance test as described in [7.1](#)

3.3
extended mobility tyre
EMT
tyre featuring on purpose technology designed to operate in an inflated mode and allowing the tyre, mounted on the appropriate wheel and in the absence of any supplementary component, to supply the vehicle with the basic tyre functions at a specified speed and distance when operating in flat tyre running mode, able to successfully complete the endurance test as described in [7.2](#)

3.4
internal support
device, resting on the rim, that helps supply the vehicle with basic tyre functions when operating in flat tyre running mode which allows the tyre to successfully complete the endurance test as described in [7.1](#)

3.5
spare unit
assembly of a tyre and a wheel intended to replace a tyre/wheel assembly already fitted on a vehicle that has lost some functional efficiency

Note 1 to entry: The tyre/wheel assembly can include a tube and a valve, etc.

3.6
spare unit substitutive equipment
SUSE
equipment intended to maintain or restore, but not replace, the basic functions of a tyre in the event of a tyre/wheel assembly failure

3.7
SUSE system
assembly of specified functionally dependent components including, but not limited to, a tyre and a run-flat warning system, which together provide the specified performance granting extended mobility to a vehicle thus, equipped as described in [6.2](#)

Note 1 to entry: This definition was previously titled “extended mobility system” in 16992:2010.

Note 2 to entry: Examples which do not meet this document are shown in [Annexes A](#) and [B](#).

3.8

inflated mode

normal working state of a tyre, inflated at the cold inflation pressure recommended by the vehicle manufacturer or the tyre manufacturer for the intended service

3.9

loss of tyre functional efficiency

pressure loss of the tyre/wheel assembly which results in operation in flat tyre running mode and which could be rapid, slow or uncontrolled, leading to a reduction of basic tyre function

3.10

flat tyre running mode

state of a tyre while operating at an inflation pressure between 0 kPa and 70 kPa

3.11

run-flat warning system

RFWS

system which delivers information to the driver that a tyre is operating in the flat tyre running mode

Note 1 to entry: In addition, an RFWS can also warn the driver when the expected run-flat potential of the SUSE system has been used.

3.12

tyre pressure monitoring system

TPMS

system fitted on a vehicle, able to perform a function to evaluate the inflation pressure of the tyres or the variation of this inflation pressure over time and to transmit corresponding information to the user while the vehicle is running

3.13

significant reduction of the tyre inflation pressure

event leading a tyre to operate at an inflation pressure insufficient for the intended service on a given vehicle

Note 1 to entry: The intended service comprises the load, speed and camber.

3.14

restored mobility

operating condition of a vehicle that, following the loss of tyre functional efficiency, is recovered by manual deployment of a SUSE after an immediate stop

3.15

preserved mobility

operating condition of a vehicle that, following the loss of tyre functional efficiency, is recovered automatically by means of a SUSE

3.16

extended mobility

operating condition of a vehicle that, following the loss of tyre functional efficiency, is provided by means of a SUSE system

3.17

basic tyre functions

normal capability of an inflated tyre to support a given load up to a given speed and to transmit the driving, the steering and the braking forces to the ground on which it runs

4 Symbols

The ISO 16992 symbols are used to identify those tyres that comply with requirements of this document (see also [Clause 8](#)).