

SVENSK STANDARD

SS-EN 15863:2015



Fastställt/Approved: 2015-04-05
Publicerad/Published: 2015-04-08
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 13.030.10

Karaktärisering av avfall – test av grundläggande lakegenskaper – Dynamisk laktest för monoliter med periodiskt utbyte av lakvätska vid bestämda testförhållanden

Characterization of waste – Leaching behaviour test for basic characterization – Dynamic monolithic leaching test with periodic leachant renewal, under fixed conditions

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8013628>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Europastandarden EN 15863:2015 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 15863:2015.

The European Standard EN 15863:2015 has the status of a Swedish Standard. This document contains the official English version of EN 15863:2015.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Uppllysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna uppllysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Karaktärisering av avfall, mark och slam, SIS/TK 535.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

EUROPEAN STANDARD

EN 15863

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2015

ICS 13.030.10

Supersedes CEN/TS 15863:2012

English Version

**Characterization of waste - Leaching behaviour test for basic
characterization - Dynamic monolithic leaching test with periodic
leachant renewal, under fixed conditions**

Caractérisation des déchets - Essais de comportement à la
lixiviation pour la caractérisation de base - Essai de
lixiviation dynamique des monolithes avec renouvellement
périodique du lixiviant, dans des conditions d'essai fixes

Charakterisierung von Abfällen - Untersuchung des
Elutionsverhaltens für die grundlegende Charakterisierung -
Dynamisches Elutionsverfahren für monolithische Abfälle
mit periodischer Erneuerung des Elutionsmittels unter
festgelegten Prüfbedingungen

This European Standard was approved by CEN on 7 February 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		Page
Foreword.....		4
Introduction		5
1 Scope		7
2 Normative references		7
3 Terms and definitions		8
4 Principle		10
5 Reagents		10
6 Equipment		11
7 Sample preparation		12
7.1 General.....		12
7.2 Preparation of the test portion		12
7.3 Determination of the geometric surface area		12
8 Procedure		13
8.1 Testing conditions		13
8.2 Step 1 of the leaching procedure		13
8.3 Steps 2 – 8 of the leaching procedure		13
8.4 Weight loss of the monolithic waste during the test		14
8.5 Further preparation of the eluates for analysis		14
8.6 Blank test.....		15
9 Calculations.....		15
9.1 Expression of results		15
9.1.1 General.....		15
9.1.2 Expression of results in terms of area related release		16
9.1.3 Expression of results in concentrations		17
9.1.4 Calculation of release mechanism		17
10 Performance characteristics		17
11 Documentation and test report		18
11.1 General.....		18
11.2 General data		18
11.3 Leaching test conditions		18
11.4 Analytical report.....		18
11.5 Results of the leaching test		19
Annex A (informative) Identification of release mechanisms and use of test results		20
A.1 Introduction		20
A.2 Examples of factors influencing the leaching of monolithic waste		20
A.3 Long term release prediction		22
Annex B (informative) Assessment of release mechanisms (if required)		23
B.1 Overview of release mechanisms		23
B.2 Procedure of identification of release mechanisms		24
B.3 Concentrations close to the limit of quantification		25
B.3.1 Overall low concentrations		25
B.3.2 Surface wash-off followed by low concentrations		26
B.4 Diffusion controlled release of a substance		26

B.4.1	Identification of diffusion controlled release	26
B.4.2	Surface wash-off preceding diffusion-controlled release.....	28
B.4.3	Diffusion-controlled release followed by depletion.....	28
B.4.4	Surface wash-off preceding diffusion-controlled release followed by depletion.....	28
B.5	Dissolution controlled release of a substance.....	28
B.6	Other release mechanism.....	29
B.6.1	Unidentified release mechanism	29
B.6.2	Surface wash-off of a substance	29
B.6.3	Depletion of a substance	30
B.6.4	Surface wash-off and depletion	31
B.7	Calculation of release	31
B.7.1	Area release	31
B.7.2	Surface wash-off.....	31
B.7.3	Release in the case of dissolution.....	31
B.7.4	Extrapolation of the cumulative area release for larger time values	31
B.8	Examples	32
Annex C (informative) Examples of data about the <i>L/A</i> ratio.....		51
Annex D (informative) Process map for EN 15863.....		52
Annex E (informative) Repeatability and reproducibility data.....		54
E.1	Material used in the interlaboratory comparison study	54
E.2	Interlaboratory comparison results.....	54
Bibliography.....		61

Foreword

This document (EN 15863:2015) has been prepared by Technical Committee CEN/TC 292 "Characterization of waste", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2015, and conflicting national standards shall be withdrawn at the latest by October 2015.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 15863:2012.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

This document was elaborated on the basis of NEN 7345:1995.

The following significant technical changes have been implemented in this new edition of the text:

- the status of the document has been changed from a CEN/TS into a European Standard;
- performance data has been added (see Annex E).

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This document has been developed primarily to support the requirements for leaching behaviour testing within EU and EFTA countries.

This document specifies a dynamic leaching test for monolithic waste materials, to determine key parameters to address the leaching behaviour of monolithic waste materials.

For the complete characterization of the leaching behaviour of waste under specified conditions the application of other test methods is required (see EN 12920).

Anyone dealing with waste and sludge analysis should be aware of the typical risks of that kind of material irrespective of the parameter to be determined. Waste and sludge samples can contain hazardous (e.g. toxic, reactive, flammable, infectious) substances, which can be liable to biological and/or chemical reaction.

Consequently these samples should be handled with special care. Gases which can be produced by microbiological or chemical activity are potentially flammable and will pressurize sealed bottles. Bursting bottles are likely to result in hazardous shrapnel, dust and/or aerosol. National regulations should be followed with respect to all hazards associated with this method.

In the different European countries, tests have been developed to characterize and assess the constituents which can be leached from waste materials. The release of soluble constituents upon contact with water is regarded as one of the main mechanism of release which results in a potential risk to the environment during life-cycle of waste materials (disposal or re-use scenario). The intent of these tests is to identify the leaching properties of waste materials. The complexity of the leaching process makes simplifications necessary. Not all of the relevant aspects of leaching behaviour can be addressed in one single standard.

Procedures to characterize the behaviour of waste materials can generally be divided into three steps, using different tests in relation to the objective. The following test hierarchy is taken from the Landfill Directive ¹⁾ and the Decision on Annex II of this Directive ²⁾ for disposal of waste.

- a) Basic characterization constitutes a full characterization of the waste by gathering all the necessary information for a safe management of the waste in the short and long term. Basic characterization may provide information on the waste (type and origin, composition, consistency, leachability, etc.), information for understanding the behaviour of waste in the considered management scenario, comparison of waste properties against limit values, and detection of key variables (critical parameters as liquid/solid (L/S) ratios, leachant composition, factors controlling leachability such as pH, redox potential, complexing capacity and physical parameters) for compliance testing and options for simplification of compliance testing. Characterization may deliver ratios between test results from basic characterization and results from simplified test procedures as well as information on a suitable frequency for compliance testing. In addition to the leaching behaviour, the composition of the waste should be known or determined by testing. The tests used for basic characterization should always include those to be used for compliance testing.
- b) Compliance testing is used to demonstrate that the sample of today fits the population of samples tested before by basic characterization and through that, is used to carry out compliance with regulatory limit values. The compliance test should therefore always be part of the basic characterization program. The compliance test focuses on key variables and leaching behaviour identified by basic characterization tests. Parts of basic characterization tests can also be used for compliance purposes.

1) Council Directive 1999/31/EC of 26 April 1999 on the landfill of waste.

2) Council Decision 2003/33/EC of 19 December 2002.

- c) On-site verification tests are used as a rapid check to confirm that the waste is the same as that which has been subjected to characterization or compliance tests. On-site verification tests are not necessarily leaching tests.

The test procedure described in this document is a basic characterization test and falls in category a).

According to EN 12920 the evaluation of the release of constituents from waste materials in a certain scenario involves the performance of various tests. This document describes one of the parametric test that can be used for such purposes, especially for monolithic waste.

The test procedure allows the determination of the release under dynamic conditions of constituents from a monolithic waste material, as a function of time. This release is calculated from the concentrations of the constituents measured in the solution (eluate) that is collected in a fixed number of separate fractions. Besides, the following test conditions are fixed: the type of leachant, the temperature, the liquid to surface area ratio (L/S), and the duration of the test.

Results of this test, combined with those from other tests (e.g. EN 14429) and the use of more or less sophisticated models, allow the identification of the main leaching mechanisms that can be distinguished, such as diffusion, dissolution of constituents, initial surface wash-off, dissolution of the matrix (see Annex A). These intrinsic properties can be used to predict the release of constituents at a given time frame, in order to assess the leaching behaviour of monolithic waste materials in practical situations or scenarios as defined in EN 12920. For assessment of the leaching under equilibrium conditions (low L/A condition, pore water and/or long contact times) there are other tools available, such as the pH dependence test EN 14429, the percolation test for granular material CEN/TS 14405 (with L/S 0,1 l/kg to 0,5 l/kg) and the batch test for granular waste EN 12457-1 to EN 12457-4.

NOTE At low L/A conditions, pore water conditions in monolithic specimens can be approached.

1 Scope

This European Standard is applicable for determining the leaching behaviour of monolithic wastes under dynamic conditions. The test is performed under fixed experimental conditions in this document. This test is aimed at determining the release as a function of time of inorganic constituents from a monolithic waste, when it is put into contact with an aqueous solution (leachant).

This dynamic monolithic leaching test (DMLT) is a parameter specific test as specified in EN 12920 and is therefore not aimed at simulating real situations. The application of this test method alone is not sufficient for the determination of the detailed leaching behaviour of a monolithic waste under specified conditions.

In the framework of EN 12920 and in combination with additional chemical information, the test results are used to identify the leaching mechanisms and their relative importance. The intrinsic properties can be used to predict the release of constituents at a given time frame, in order to assess the leaching behaviour of monolithic waste materials, placed in different situations or scenarios (including disposal and recycling scenarios).

The test method applies to regularly shaped test portions of monolithic wastes with minimum dimensions of 40 mm in all directions that are assumed to maintain their integrity over a time frame relevant for the considered scenario. The test method applies to test portions for which the geometric surface area can be determined with the help of simple geometric equations. The test method applies to low permeable monolithic materials.

Within the reproducibility ranges, the leaching results obtained with EN 15863 are expected to be equivalent to those obtained with CEN/TS 16637-2 (DMLT for construction products), because the main testing conditions are equalized in both standards. As shown in the results obtained with EN 15863 (see Annex E), they are also demonstrated to be comparable with US EPA method 1315 (SW846). These observations imply that a monolithic waste tested with this European Standard, does not need to be tested a second time, when the material proves suitable for beneficial use in construction and provided it has not undergone a treatment or other changes modifying its leaching behaviour.

NOTE 1 If, in order to comply with the requirements of regular shape, the test portion is prepared by cutting or coring, then new surfaces are exposed which can lead to change(s) in leaching properties. On the other hand if the test portion is prepared by moulding, the surface will be dependent to the type of mould and the conditions of storage. If the intention is to evaluate the behaviour of the material core, the specimen needs to be stored without any contact with air to avoid carbonation.

NOTE 2 For monolithic waste materials with a saturated hydraulic conductivity higher than 10^{-8} m/s water is likely to percolate through the monolith rather than flow around. In such cases relating the release to the geometric surface can lead to misinterpretation. A percolation test is more appropriate then (e.g. CEN/TS 14405).

This procedure may not be applicable to materials reacting with the leachant, leading for example to excessive gas emission or an excessive heat release.

This document has been developed to determine the release of mainly inorganic constituents from wastes. It does not take into account the particular characteristics of organic constituents, nor the consequences of microbiological processes in organic degradable wastes.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.