

# SVENSK STANDARD

## SS-ISO 12646:2015



Fastställt/Approved: 2015-10-26  
Publicerad/Published: 2015-11-06  
Utgåva/Edition: 2  
Språk/Language: engelska/English  
ICS: 37.100.01

---

### **Grafisk teknik – Bildskärmar för skärmprovtryck – Karaktäristik (ISO 12646:2015, IDT)**

### **Graphic technology – Displays for colour proofing – Characteristics (ISO 12646:2015, IDT)**

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-8016949>

# Standarder får världen att fungera

*SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.*

## Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.


## Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

## Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

**Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på [www.sis.se](http://www.sis.se) eller ta kontakt med oss på tel 08-555 523 00.**



# Standards make the world go round

*SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.*

## Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

## Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

## Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

**If you want to know more about SIS, or how standards can streamline your organisation, please visit [www.sis.se](http://www.sis.se) or contact us on phone +46 (0)8-555 523 00**



Den internationella standarden ISO 12646:2015 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 12646:2015.

Denna standard ersätter SS-ISO 12646:2009, utgåva 1 och SS-ISO 12646:2009/Amd 1:2010, utgåva 1.

The International Standard ISO 12646:2015 has the status of a Swedish Standard. This document contains the official English version of ISO 12646:2015.

This standard supersedes the Swedish Standard SS-ISO 12646:2009, edition 1 and SS-ISO 12646:2009/Amd 1:2010, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

*Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.*

*Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.*

Denna standard är framtagen av kommittén för Grafisk teknik, SIS/TK 434.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på [www.sis.se](http://www.sis.se) - där hittar du mer information.



# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Requirements</b> .....	<b>2</b>
4.1 General.....	2
4.2 Uniformity of luminance and chromaticity.....	3
4.2.1 General.....	3
4.2.2 Evaluation of tone uniformity.....	3
4.2.3 Tonality evaluation (uniformity).....	3
4.3 Viewing cone characteristics.....	3
4.4 Reflective characteristics.....	4
<b>5 Test methods</b> .....	<b>5</b>
5.1 General.....	5
5.2 Preparation and display set-up.....	5
5.3 Viewing angle dependent tonality evaluation (“ $\Delta$ Gamma”).....	5
5.4 Measurement conditions.....	6
5.4.1 Photometric and colorimetric measurements.....	6
5.4.2 Measurements as a function of viewing direction.....	8
<b>Bibliography</b> .....	<b>11</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 130, *Graphic technology*.

This third edition cancels and replaces the second edition (ISO 12646:2008), which has been technically revised to improve the compatibility with the requirements of soft proofing defined in ISO 14861.

## Introduction

The ability to match colour images displayed on colour displays to the images produced when the same digital file is rendered by proofing and printing systems (commonly referred to as “soft” proofing) is increasingly expected in graphic arts. Obtaining such a match is not simple and to be fully accurate requires careful control of many aspects of the process. The primary purpose of this International Standard is to make recommendations with respect to the soft proof displays requirements. If these are met, it is then possible for a soft proofing system such as defined in ISO 14861 to accurately colour match to the hard copy proof. Hence, this International Standard is intended for display manufacturers in order to qualify their display for use in graphic arts proofing systems.

The appearance of a colour image on a colour display is influenced by many physical factors other than controlled ambient viewing conditions. Among the most important of these are uniformity, size and resolution (in order to permit rendition of the proof at close to its normal size and with the finest detail visible on the hard copy at normal viewing distances), variation of electro-optical properties with viewing direction, freedom from flicker and glare (specular reflections with distinct images), the opto-electronic calibration of the display, and the settings of its display driver software. In this regard, to be acceptable in a proofing system that provides a reasonable level of image quality, the display needs to also exhibit these properties at an acceptable quality.

Note that even for displays of the highest quality, the appearance of the displayed image will be limited by the accuracy of the colour transformation used for converting the digital file from its encoded colour space to that required for display purposes.

This International Standard specifies requirements for displays to be used in soft proofing systems defined by ISO 14861. ISO 14861 primarily focuses on applications where the displayed image will be compared to a hard copy in an adjacent viewing cabinet or where the viewing cabinet intentionally contains the display. Furthermore, in order to address the different needs for the soft proofing use cases, two different conformance levels (class A and class B) will be defined in this International Standard.

However, in some practical situations, the image on the screen is evaluated in the absence of a hard copy. This International Standard might be used as reference, but this is not required. Users of this International Standard will also benefit from CIE Publication 122 which provides an overview of the relationship between digital and colorimetric data. Those unfamiliar with the evaluation of displays will also find it helpful to read IEC 61223-2-5 which contains much useful detailed information about evaluation and testing of image display devices.



# Graphic technology — Displays for colour proofing — Characteristics

## 1 Scope

This International Standard specifies requirements for two conformance levels for the characteristics of displays to be used for soft proofing of colour images. Included are requirements for uniformity and variations of electro-optical properties with viewing direction for different driving signals.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **calibration**

set of operations that establish, under specified conditions, the relationship between values of quantities indicated by a measuring instrument or measuring system or values represented by a material measure of a reference material and the corresponding values realized by standards

[SOURCE: ISO International Vocabulary of Basic and General Terms in Metrology]

Note 1 to entry: However, in typical graphic arts, use cases calibration is understood as an active process where a display or a printer is adjusted such that it produces the defined aim values.

### 3.2

#### **colorimeter**

instrument for measuring colour values such as the tristimulus values of a colour stimulus

[SOURCE: ISO 12637-2:2008, 2.18]

### 3.3

#### **design viewing direction**

#### **DVD**

direction for which specific electro-optical characteristics of the display have been optimized

Note 1 to entry: Examples of important electro-optical characteristics are maximum luminance and maximum contrast in definite direction.

### 3.4

#### **gamma**

#### **$\gamma$**

best-fit parameter which relates the display normalized output luminance to a normalized input digital value presented to the display system including its hardware and software components as given in Formula (1):

$$L = (S)^{\gamma} + O$$

where

- $L$  is the normalized output luminance;
- $S$  is the normalized input digital value;
- $O$  is the offset.

### 3.5

#### **ON-state**

condition in which the display is switched on

Note 1 to entry: This definition is important for light-valve-like displays which might emit a significant light intensity even when displaying the darkest image ( $R = G = B = 0$ ) in the ON-state.

### 3.6

#### **spectrophotometer**

instrument for measuring the reflectance or transmittance of light (or other radiation) by an object at one or more wavelengths in the spectrum

[SOURCE: ISO 105-A08:2001, 2.24]

### 3.7

#### **viewing cone**

##### **VC**

conical space originating at the display surface that includes all viewing directions with a specified angle of inclination,  $\theta$  (3.8)

### 3.8

#### **viewing angle**

##### $\theta$

angle between the normal to the display and the *design viewing direction* (3.3)

## 4 Requirements

### 4.1 General

All display tests should be performed for a display calibrated to a luminance of 160 cd/m<sup>2</sup> and a chromaticity corresponding to a D50 ( $x = 0,3457$  and  $y = 0,3585$ ) illuminant with a 2° observer at a gamma of 2,2. The display shall display a "white" image consisting of the maximum value in each channel, red, green, and blue (255 for 8-bit). It shall be reported if other calibration aims were used.

NOTE 1 This calibration condition is typical of the conditions used in the graphic arts industry and ensures that the results of different tested displays can be compared because uniformity can be dependent to some extent on the chosen gamma, luminance, and white point settings.

If a display to be tested will be used solely in a specific soft proofing system where no display calibration is used, but only the state of the display is characterized, the calibration can be omitted. The luminance, the white point chromaticity (as expressed in CIE<sub>xy</sub> units), and tone reproduction curve (as expressed by a single gamma value or as a set of tabulated values) shall be reported.

The display shall be tested in a stable condition. In order to establish the individual stabilization time, each display to be tested shall be operated in the calibration mode for 12 h in a room with controlled temperature conditions. The room temperature shall not change more than  $\pm 0,5$  °C and shall be in the range of 18 °C to 28 °C.

The stabilization time (warm up time) is achieved when the luminance change is less than 2 % (compared to the average of the measurements of the last 9 h of the 12 h period) and the white point is within  $\pm 0,005$  for CIE  $\Delta x, \Delta y$  of the calibrated conditions. If the display will not achieve stable conditions, it shall not be used.

The warm up behaviour of a display shall be reported with a graph of luminance and CIE  $\Delta x$ ,  $\Delta y$  in measured values and in percentage compared to the average of the last 9 h of the 12 h period.

NOTE 2 When using viewing condition P2, according to ISO 3664, a luminance of 160 cd/m<sup>2</sup> correlates with an illuminance of 500 lux illuminating a perfect reflecting diffusor.

## 4.2 Uniformity of luminance and chromaticity

### 4.2.1 General

The uniformity of a soft proofing system is vital and shall be checked for solid colours and for tonality (gradation) changes of the screen. If the informative requirements of 4.2.2. or 4.2.3 are not met, this shall be reported. Therefore, the following method is normatively required in ISO 14861. However, since there are soft proofing solutions that are able to perform a spatial resolved uniformity correction, this International Standard makes the uniformity assessment informative.

It shall be reported and if hardware based, look up table display corrections are turned on (if present).

### 4.2.2 Evaluation of tone uniformity

The CIELAB values of a uniform 5 × 5 grid are calculated using the measurement of the centre patch at maximum driving as the reference white illuminant. Note that this method may result in some CIEL\* values being greater than 100. 24 readings are compared with the centre colour for three different driving levels, namely white, at the maximum driving level (R = G = B = 255 for 8-bit displays), grey at about half maximum driving level (R = G = B = 127 for 8-bit displays), and dark grey at about one fourth of maximum driving level (R = G = B = 63 for 8-bit displays) by means of the DE00 colour difference formulae. For the white and the grey driving levels, the DE00 colour differences should be equal or less than four.

### 4.2.3 Tonality evaluation (uniformity)

Utilizing luminance (cd/m<sup>2</sup>) measurements of grey at half maximum driving level (R = G = B = 127 for 8-bit displays) and white at max driving level (R = G = B = 255 for 8-bit displays) the grey/white ratio should be calculated for the 25 regions. For the non-central regions, new ratios,  $T_i$ , with  $i = \{1, \dots, 24\}$  should be computed by dividing the individual grey/white ratios,  $R_i$ , with  $i = \{1, \dots, 24\}$  by the grey/white ratio of the centre,  $R_c$ , subtracting one and calculate the absolute value of the number. This measure of the deviation from uniform tonality should be less than 10 %, i.e.  $\max(T_i), i = \{1, \dots, 24\}$  should be less than 0,10.

$$T_i = \text{abs}(R_i / R_c - 1), (i = 1, \dots, 24) \quad (1)$$

The uniformity of tonality, determined as  $\max(T_i)$ , with  $i = \{1, \dots, 24\}$ , should be less than 0,1.

## 4.3 Viewing cone characteristics

The instrumentation setup and measurement geometry for viewing cone measurements shall be as defined in 5.4.2.

Based on the viewing cone which is visible for an observer viewing a display centred with one eye at a given viewing distance (default: 500 mm), the maximal viewing angles  $\theta_{\max}$  ( $\theta_{\max}$ ) shall be calculated for the horizontal, diagonal and vertical directions. In addition,  $\theta_{\max}$  for the four 45° angles (starting at 45° being 90° apart from each other) shall be calculated. The maximum inclination ( $\theta_{\max}$ ) depends on screen size, screen aspect ratio (ratio of display width and height), and viewing distance and will be calculated as follows:

$$\theta_{\max, \text{horizontal}} = \arctan(W2 / VD) * 180^\circ / \pi \quad (2)$$

$$\theta_{\max, \text{vertical}} = \arctan(H2 / VD) * 180^\circ / \pi \quad (3)$$