

SVENSK STANDARD

SS-ISO 18619:2015



Fastställt/Approved: 2015-10-27
Publicerad/Published: 2015-11-06
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 35.240.30; 37.100.99

Grafisk teknik – Bildteknik för färgstyrning – Svartpunktskompensation (ISO 18619:2015, IDT)

Image technology colour management – Black point compensation (ISO 18619:2015, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8016953>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 18619:2015 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 18619:2015.

The International Standard ISO 18619:2015 has the status of a Swedish Standard. This document contains the official English version of ISO 18619:2015.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Grafisk teknik, SIS/TK 434.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

| | |
|--|-----------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Requirements | 2 |
| 4.1 Constraints..... | 2 |
| 4.2 Computation..... | 3 |
| 4.2.1 Outline..... | 3 |
| 4.2.2 Functions used..... | 3 |
| 4.2.3 Computing the SourceBlackPoint..... | 4 |
| 4.2.4 Computing the DestinationBlackPoint for ICC profiles that are not LUT-based..... | 4 |
| 4.2.5 Computing the DestinationBlackPoint for ICC profiles that are LUT-based..... | 5 |
| 4.2.6 Computing the mapping from SourceBlackPoint to DestinationBlackPoint..... | 10 |
| 4.2.7 Applying the black point compensation in a colour conversion..... | 11 |
| Annex A (informative) Why black point compensation is necessary | 12 |
| Bibliography | 14 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 130, *Graphic technology*, in cooperation with the International Color Consortium.

Introduction

Black point compensation (BPC) is a technique used to address colour conversion problems caused by differences between the darkest level of black achievable on one device and the darkest level of black achievable on another. This procedure was first implemented in Adobe Photoshop in the late 1990s. The International Color Consortium (ICC) and ISO Technical Committee 130 (Graphic technology) have created this document to allow black point compensation to be used in a consistent manner across applications.

The purpose of BPC is to adjust a colour transform between the colour spaces of source and destination ICC profiles, so that it retains shadow details and utilizes available black levels. The procedure depends only on the rendering intent(s) and the source and destination ICC profiles, not on any points in a particular image. Therefore, the colour transform using specific source and destination ICC profiles and rendering intent can be computed once, and then efficiently applied to many images which use the same ICC profile colour transform pair and rendering intent.

Image technology colour management — Black point compensation

1 Scope

This International Standard specifies a procedure, including computation, by which a transform between ICC profiles can be adjusted (compensated) to take into account differences between the dark end of the source colour space and the dark end of the destination colour space. This is referred to as black point compensation (BPC). The relative colorimetric encoding of ICC profile transforms already provides a mechanism for such adjustment of the light (white) end of the tone scale.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15076-1, *Image technology colour management — Architecture, profile format and data structure — Part 1: Based on ICC.1:2010*

ICC.1:2001-04, *File Format for Color Profiles*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15076-1 and the following apply.

3.1

DestinationBlackPoint

coordinate representing a dark neutral reproducible colour in the destination colour gamut

3.2

DestinationProfile

ICC profile, containing the transform from profile connection space to the destination device colour space

3.3

SourceBlackPoint

coordinate representing a dark neutral colour in the source colour gamut

3.4

SourceProfile

ICC profile, containing the transform from the source device colour space to the profile connection space

3.5

RenderingIntent

rendering intent of the conversion from a source ICC profile's colour space to a destination ICC profile's colour space

3.6

LabIdentityProfile

real or virtual ICC profile that contains a bi-directional (identity) transform between CIELAB and PCSLAB

3.7
black point compensation
BPC

computational procedure by which a transform between the colour spaces of ICC profiles can be adjusted (compensated) to take into account differences between the dark end of the source colour space and the dark end of the destination colour space

3.8
L, a, b
L*, a*, or b* component of the CIELAB colour space

3.9
output-capable CMYK profile
CMYK profile containing a transform from the ICC PCS encoding to the colour space encoding

3.10
transform
mathematical operations that define the change in representation of a colour between two colour spaces

3.11
gamut
range of colours that a given system is capable of reproducing

4 Requirements

4.1 Constraints

The black point compensation procedure defined in this International Specification shall take as its inputs a destination ICC profile, a source ICC profile, and a rendering intent (in this International Standard called *DestinationProfile*, *SourceProfile* and *RenderingIntent* respectively).

Applications that apply black point compensation shall support ICC profiles that conform to ISO 15076-1 and ICC profiles that conform to ICC.1:2001-04.

NOTE 1 This requirement ensures that processing applications will properly process all Version 2 and Version 4 ICC profiles.

NOTE 2 ISO 15076-1 provides a description of source and destination ICC profiles.

The rendering intent shall be one of: RelativeColorimetric; Perceptual; or Saturation. The rendering intent used with *DestinationProfile* shall be the same as the rendering intent used with *SourceProfile*. Black point compensation is not appropriate for the AbsoluteColorimetric rendering intent.

The versions of *SourceProfile* and *DestinationProfile* do not need to match.

SourceProfile and *DestinationProfile* types shall be Input, Display, Output, or ColorSpace. The types of *SourceProfile* and *DestinationProfile* do not need to match.

DestinationProfile shall contain a transform from the ICC PCS encoding to the colour space encoding.

The data colour spaces of the *SourceProfile* and *DestinationProfile* shall be Gray, RGB, CMYK or CIELAB. The data colour spaces of *SourceProfile* and *DestinationProfile* do not need to match.

NOTE 3 Some implementations of BPC extend to additional colour spaces or mixed rendering intents. The way in which BPC operates in these cases is outside the scope of this International Standard.

4.2 Computation

4.2.1 Outline

Black point compensation shall be performed according to the following procedure:

- a) the *SourceBlackPoint* of *SourceProfile* shall be calculated as specified in [4.2.3](#);
- b) the *DestinationBlackPoint* of *DestinationProfile* shall be calculated as specified in [4.2.4](#) and [4.2.5](#);
- c) a mapping from *SourceBlackPoint* to *DestinationBlackPoint* shall be calculated as specified in [4.2.6](#);
- d) the mapping shall be applied in a colour conversion as specified in [4.2.7](#).

4.2.2 Functions used

4.2.2.1 Colour transform with profiles

T shall denote a function to transform a point in the data colour space of *Profile1* to a point in the device colour space of *Profile2*, using a rendering intent, such that

$$y = \mathbf{T}(x, Profile1, Profile2, Intent) \quad (1)$$

where

x is a point in the data colour space of *Profile1*;

y is a point in the data colour space of *Profile2*;

Intent is the rendering intent.

4.2.2.2 Darkest colour of a profile

D shall denote a function to provide the darkest colour coordinate in the data colour space of *Profile* for a rendering intent, such that

$$dc = \mathbf{D}(Profile, Intent) \quad (2)$$

where

dc is the darkest colour

Profile is the profile being evaluated,

Intent is the rendering intent.

dc shall be determined as follows:

A subset of the vertices within the data colour space of *Profile*, *V*, shall be defined as follows.

If the data colour space of *Profile* is Gray

V shall be the set of {(0) (1)}.

If the data colour space of *Profile* is RGB

V shall be the set of {(0, 0, 0) (1, 1, 1)}.

If the data colour space of *Profile* is CMYK

V shall be the set of {(0, 0, 0, 0) (1, 1, 1, 1) (0, 0, 0, 1) (1, 1, 1, 0)}.