

SVENSK STANDARD

SS-EN 15528:2015



Fastställt/Approved: 2015-11-02
Publicerad/Published: 2015-11-10
Utgåva/Edition: 2
Språk/Language: engelska/English
ICS: 03.220.30; 45.060.20

Järnvägar – Linjekategorier för hantering av samverkan mellan lastgränser för fordon och infrastruktur

Railway applications – Line categories for managing the interface between load limits of vehicles and infrastructure

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8017069>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Europastandarden EN 15528:2015 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 15528:2015.

Denna standard ersätter SS-EN 15528:2008+A1:2012, utgåva 1.

The European Standard EN 15528:2015 has the status of a Swedish Standard. This document contains the official English version of EN 15528:2015.

This standard supersedes the Swedish Standard SS-EN 15528:2008+A1:2012, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Uppllysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna uppllysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Järnvägar, SIS/TK 254.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

EUROPEAN STANDARD

EN 15528

NORME EUROPÉENNE

EUROPÄISCHE NORM

October 2015

ICS 03.220.30; 45.060.20

Supersedes EN 15528:2008+A1:2012

English Version

Railway applications - Line categories for managing the interface between load limits of vehicles and infrastructure

Applications ferroviaires - Catégories de ligne pour la gestion des interfaces entre limites de charges des véhicules et de l'infrastructure

Bahnwendungen - Streckenklassen zur Behandlung der Schnittstelle zwischen Lastgrenzen der Fahrzeuge und Infrastruktur

This European Standard was approved by CEN on 22 August 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword.....	6
Introduction	7
1 Scope.....	8
2 Normative references.....	9
3 Terms, definitions, symbols and abbreviated terms.....	9
3.1 Terms and definitions	9
3.2 Symbols and abbreviated terms	12
4 Classification system.....	14
4.1 Definition of line categories	14
4.2 Correlation to types of vehicles.....	14
4.3 Correlation between line category and speed.....	15
4.3.1 Introduction	15
4.3.2 Freight traffic.....	15
4.3.3 Mixed traffic and passenger traffic.....	15
5 Classification of infrastructure	16
5.1 Civil engineering structures.....	16
5.1.1 Classification.....	16
5.1.2 Dynamic checks	16
5.2 Track construction, track substructure and earthworks.....	17
5.3 Infrastructures classification results.....	18
6 Categorization of railway vehicles.....	18
6.1 General rules.....	18
6.2 Freight wagons.....	21
6.2.1 Specific rules for freight wagons	21
6.2.2 Resulting load limits for freight wagons.....	21
6.3 Locomotives	21
6.3.1 General.....	21
6.3.2 4-axle locomotives	21
6.3.3 6-axle locomotives	22
6.4 Passenger carriages	22
6.5 Multiple units.....	23
6.6 Special vehicles	23
6.7 Vehicle categorization results.....	24
7 Compatibility of the interface between vehicle and infrastructure	24
Annex A (normative) Reference wagons and load models representing the line categories.....	26
Annex B (informative) Flow chart: Classification of infrastructure and categorization of vehicles	31
Annex C (informative) MU-Groups and MU-Classes.....	32
C.1 Definition	32
C.2 MU-Group CB.....	34
C.2.1 General.....	34

C.2.2	Train parameters of MU-Class CB_1	34
C.2.3	Train parameters of MU-Class CB_2	34
C.3	MU-Group AB	34
C.3.1	General	34
C.3.2	Train parameters of MU-Class AB_1	35
C.3.3	Train parameters of MU-Class AB_2	35
C.3.4	Train parameters of MU-Class AB_3	35
C.3.5	Train parameters of MU-Class AB_4	36
C.4	MU-Group SA	36
C.4.1	General	36
C.4.2	Train parameters of MU-Class SA_1	36
C.4.3	Train parameters of MU-Class SA_2	36
C.5	Example: Correspondence check of a real MU-train to MU-classes	37
C.5.1	General	37
C.5.2	General description of the real MU-train to be checked	37
C.5.3	MU-group identification	37
C.5.4	MU-class identification	37
C.5.5	Results	38
C.5.6	Example of infrastructure compatibility check	38
Annex D (normative) Mass definitions for line category and dynamic compatibility check for passenger carriages and multiple units		39
Annex E (informative) Load models corresponding to MU-classes		40
E.1	General	40
E.2	Geometric axle configuration	40
E.2.1	General	40
E.2.2	Axle spacing pattern of MU-Class CB_1	41
E.2.3	Axle spacing pattern of MU-Class CB_2	42
E.2.4	Axle spacing pattern of MU-Class AB_1	43
E.2.5	Axle spacing pattern of MU-Class AB_2	44
E.2.6	Axle spacing pattern of MU-Class AB_3	45
E.2.7	Axle spacing pattern of MU-Class AB_4	46
E.2.8	Axle spacing pattern of MU-Class SA_1	47
E.2.9	Axle spacing pattern of MU-Class SA_2	48
E.3	Axle load $P_{MUclass}$	48
E.4	Results and basic information	49
Annex F (informative) Speeds which do not require dynamic compatibility checks		50

Annex G (informative) Methods used to determine the load carrying capacity of existing structures	52
Annex H (informative) Line classification result	53
H.1 General	53
H.2 Example 1	53
H.3 Example 2	53
H.4 Example 3	54
Annex I (informative) Example of calculation methodology	55
I.1 General	55
I.2 Tables of calculation results for example in Annex I	57
I.3 Diagram of calculation results for example in Annex I	59
Annex J (informative) Maximum permissible axle load P – Wagons with two 2-axles bogies	61
Annex K (informative) Maximum permissible axle load P – Wagons with two 3-axles bogies	64
Annex L (informative) Line categories of 6-axle locomotives	67
Annex M (informative) L4 locomotive classes (4-axle locomotives)	68
Annex N (informative) L6 locomotive classes (6-axle locomotives)	69
Annex O (informative) Example of correspondence between a national track classification system and line categories	71
Annex P (informative) Parametric studies for dynamic analysis	74
P.1 Nature and objective	74
P.2 Parameters to consider	74
P.3 Methods and assumptions	74
P.4 Results	75
P.5 Example	75
Annex Q (informative) Comparison of RA-classification with line categories	83
Annex R (informative) Weight note for locomotives	84
R.1 General	84
R.2 Example of a weight note for a series A locomotive	85
R.3 Example of a weight note for a series B locomotive	86
Annex S (informative) Examples of axle spacings for locomotives and for a standard passenger carriage	87
S.1 Introduction	87
S.2 Typical axle spacing patterns of locomotives with 22,5 t axle load	87
S.3 Axle spacing pattern and axle load of a 26,4 m carriage	88
Annex T (informative) Categorization of MU's by parameter check	91
T.1 General	91
T.2 MU-Group CB	91

T.3	MU-Group AB.....	92
T.4	MU-group SA.....	92
T.5	Identification of line category by axle load	93
Annex U (informative)	Guidence for categorizing light rail MU's into line category a10, a12 or a14	94
U.1	General	94
U.2	4 axle light rail MU with 2 bogies.....	94
U.3	4 axle light rail MU with 4 single axles.....	95
U.4	6 axle light rail MU with 3 bogies.....	96
U.5	6 axles light rail MUs with 6 single axles.....	98
U.6	6 axles light rail MUs with 2 bogies and 2 single axles.....	99
U.7	8 axles light rail MUs or more axles	101
Annex ZA (informative)	Relationship between this European standard and the Essential Requirements of EU Directive 2008/57/EC of the European Parliament and of the Council of 17 June 2008 on the interoperability of the rail system within the Community (Recast)	102
Bibliography	106

European foreword

This document (EN 15528:2015) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2016, and conflicting national standards shall be withdrawn at the latest by April 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 15528:2008+A1:2012.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2008/57/EC.

For relationship with EU Directive 2008/57/EC, see informative Annex ZA, which is an integral part of this document.

Significant technical changes between this European Standard and the previous edition are:

- Extension of the range of Line Categories
 - new Line Categories a10, a12 and a14 to cover light passenger vehicles (Urban Rail);
 - new Line Categories D5 and E6 to optimize the payload for freight wagons.
- Providing information and guidance for additional dynamic checks, for higher speeds and certain vehicle types.
- Implementation of MU-classes alternative to individual train checks.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

The existing European railway infrastructure consists of elements designed for varying historical requirements. Most civil engineering railway infrastructure was built before the introduction of the Technical Specifications for Interoperability (TSIs) and the Eurocodes for the design of structures.

This European Standard defines a line classification system for infrastructure managers and railway undertakings to manage the interface between the load limits for railway vehicles and the payload limits for freight wagons and the vertical load carrying capacity of a line.

The line classification system takes into account parameters such as:

- axle load (P);
- geometrical aspects relating to the spacing of axles;
- mass per unit length (p);
- speed;

and provides a transparent method for determining whether the vertical loading characteristics of vehicles are compatible with the load carrying capacity of lines on the network.

The line classification system utilizes a suite of line categories with each line category defined in this standard by a load model.

1 Scope

This European Standard describes methods of classification of existing and new railway lines and the categorization of vehicles. The standard specifies the technical requirements for ensuring the compatibility of the interface between a vehicle and infrastructure with respect to the vertical load carrying capacity of a line. The standard is suitable for use on freight, passenger and mixed traffic lines with standard track gauge and wider than standard track gauge. It contains requirements relevant to:

- classification of the vertical load carrying capacity of railway infrastructure;
- design of railway vehicles;
- determination of payload limits of freight wagons.

A summary of the classification of infrastructure and the categorization of vehicles is given in Annex B.

The assessment of the vertical load carrying capacity of civil engineering structures, track, sub-grade and earthworks by the use of the load models defined in Annex A permits the classification of infrastructure into line categories.

This European Standard identifies on which lines vehicles are compatible to the infrastructure for regular traffic regarding vertical load effects.

Line categories are provided for:

- all traffic types;
- heavy freight traffic;
- locomotives;
- multiple units;
- lightweight passenger traffic.

Portable trolleys as defined by EN 13977 are outside the scope of this European Standard as well as the working mode of maintenance vehicles (e.g. rail mounted plant, cranes).

This European Standard does not cover the system used in Great Britain, where all lines and vehicles are classified in accordance with the RA (Route Availability) System. A guide to the equivalent categories in accordance with this European Standard is given in Annex Q.

This European Standard does not cover requirements relating to the maximum total mass or maximum length of a train.

The requirements of this European Standard do not replace any regulations related to running behaviour of vehicles described by the assessment quantities for running safety, track loading and ride characteristics (see EN 14363).

This Standard does not impose any requirements to vehicles or infrastructure, but gives guidance to a simplified management of the interface between vehicles and infrastructure.

Publication of line categories is outside the scope of this European Standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1991-2:2003, *Eurocode 1: Actions on structures — Part 2: Traffic loads on bridges*

EN 15663:2009¹⁾, *Railway applications — Definition of vehicle reference masses*

EN 15877-1, *Railway applications — Marking on railway vehicles — Part 1: Freight wagons*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

associated maximum speed

local maximum speed for which the line category is valid

3.1.2

axle load

P

sum of the static vertical wheel forces exerted on the track through a wheelset or a pair of independent wheels divided by g

Note 1 to entry: In this standard “load” and “force” are described with units of “mass” (kg or t).

3.1.3

axle load

P_i

axle load P of the axle i

3.1.4

axle spacing

design values of the distances between the centres of adjacent axles

3.1.5

bending moment

designation of an internal force of a beam as used in structural design

3.1.6

categorization of vehicles

statement of the vertical loading characteristics of a railway vehicle, according to the combination of axle loads and axle spacing, by allocation of a line category

1) This document is currently impacted by the corrigendum EN 15663:2009/AC:2010.

3.1.7

classification of infrastructure

statement of the load carrying capacity of infrastructure on a line by allocation of a line category and related speed information

3.1.8

compatibility

demonstration of the satisfactory interface between the load effects of the vehicles and the load capacity of the infrastructure

3.1.9

design mass under normal payload

mass of vehicle equipped with all the consumables and occupied by all staff, which it requires in order to fulfil its function plus the normal payload defined in EN 15663 as implemented by Annex D

3.1.10

design mass under exceptional payload

mass of vehicle equipped with all the consumables and occupied by all staff, which it requires in order to fulfil its function plus the exceptional payload defined in EN 15663 as implemented by Annex D

3.1.11

length over buffers

L

length over buffers or between coupling planes in case of no buffers

3.1.12

line category

designation of the specific load model based on reference wagons

3.1.13

line speed

general maximum speed of traffic on a route

3.1.14

load limit

maximum allowable payload for a wagon related to each line category

3.1.15

load model

defined by a specific formation of reference wagons

3.1.16

locomotive

traction vehicle that is not intended to carry a payload

Note 1 to entry: In this standard, power heads are considered as locomotives.

3.1.17

locomotive class

reference vehicle with representative locomotive parameters

3.1.18

mass per unit length

p

mass of a vehicle or unit divided by length over buffers

3.1.19

maximum passenger traffic speed/maximum freight traffic speed

additional information provided by the infrastructure manager giving the general limit to the maximum traffic speed on a line according to the type of traffic

3.1.20

reference wagon

virtual vehicle used as a module of loading for a load model defined by axle load, axle spacing and mass per unit length

3.1.21

multiple unit

MU

fixed formation or railcar that can operate as a train not intended to be reconfigured, except within a workshop environment

3.1.22

MU-group

group of MU-trains determined according to the predominant running gear within the unit (conventional bogie, articulated bogie, single axle)

3.1.23

MU-class

defined by the train parameters, axle spacing pattern and axle load within a MU-group

3.1.24

passenger carriages

vehicles without traction: coaches, restaurant cars, sleeping cars, couchettes cars, vans, driving trailers, car carriers and similar vehicles, intended to be integrated in a variable formation as passenger train

3.1.25

series of locomotives

locomotives designed to be equal (the same axle spacing and the same nominal values for mass m_{nom} and, axle loads $P_{i,\text{nom}}$)

3.1.26

shear force

designation of an internal force of a beam as used in structural design

3.1.27

special vehicles

vehicles which are designed for maintenance, inspection or renewal of infrastructure elements or for special transport purposes where the fleet is operated with a low mileage compared to normal railway vehicles including:

a) maintenance vehicles including:

1) cranes and matching wagons;

- 2) on-Track Machines (see EN 14033 (all parts));
 - 3) road rail machines (see EN 15746 (all parts));
 - 4) demountable machines (see EN 15955 (all parts));
 - 5) trailers (see EN 15954 (all parts));
- b) monitoring and inspection vehicles, including:
- 1) track inspection vehicles;
 - 2) catenary inspection vehicles;
- c) special transport vehicles, including:
- 1) transformer transporter;
 - 2) crucible transporters;
 - 3) loaded wagons with more than 8 axles (UIC 502-1)

3.1.28
wheel load

Q
 static vertical wheel/rail contact forces divided by g

Note 1 to entry: The terminology in this standard for “load” and “force” is used with the meaning and units of “mass” (kg or t).

3.1.29
wheel load

Q_i
 wheel load Q of the axle i

3.2 Symbols and abbreviated terms

$1 + \varphi'$	Dynamic factor	—
$1 + \varphi'_{\text{UIC}}$	Limit value of the dynamic factor as defined in UIC 776-1	—
$2a^*$	Bogie spacing between pivot centres within a vehicle	m
$2a^*_{\text{adopted}}$	Adopted value of $2a^*$ used in Annex U	m
$2a^*_{\text{table}}$	$2a^*$ value in tables of Annex U	m
$2a^*_{\text{unit}}$	$2a^*$ value of a MU unit used in Annex U	m
$2a^+$	Axle spacing in a bogie	m
$2a^+_{\text{table}}$	$2a^+$ value in tables of Annex U	m
$2a^+_{\text{unit}}$	$2a^+$ value of a MU unit used in Annex U	m
AB	Articulated bogie	Unit
a	Distance between axles	m

b	Distance from end axle to the end of the nearest coupling plane	m
c	Distance between two inside axles	m
CB	Conventional bogie	—
ETCS	Electronic Train Control System	—
HSLM	High Speed Load Model	—
d_n	Distance between axle n and axle $(n-1)$	m
g	acceleration due to gravity	9,81 m/s ²
L	Length over buffers	mm
L_Coa	Coach length	m
m	Mass	t
m_{nom}	Nominal values for mass	t
$m_{\text{nom,excess}}$	Modified nominal value for mass due to excess of tolerances	t
MU	Multiple unit	—
No_Coa	Number of coaches within a unit	—
No_Units	Number of units within a train	—
n	Axle number	—
n_0	Natural frequency	Hz
p	Mass per unit length	t/m
P	Axle load	t
P_i	Axle load of axle i	t
$P_{i,\text{nom}}$	Nominal value for axle load of axle i	t
$P_{\text{LineCategory}}$	Maximum axle load for a Line Category	t
P_{MUclass}	Maximum axle load for a MU-class	t
$P_{\text{nom,excess}}$	Modified nominal value for axle load due to excess of tolerances	t
P_{red}	Reduced value of axle load	t
P_{unit}	Maximum axle load within the unit	t
Q	Wheel load	t
Q_i	Wheel load of axle i	t
$Q_{i\text{r}}/Q_{i\text{l}}$	Wheel load of axle i right or left	t
RA	Route Availability	—
SA	Single axle	—
s_n	Distance between axle n and axle 1	m
$u1+u2$	Bogie spacing between pivot centres of adjacent vehicles	m
$u3$	Overhang of end coaches	m
u_{unit}	Overhang value of a MU unit used in Annex U	m
u_{table}	Overhang value in tables of Annex U	m

UIC	International Union of Railways	—
V	Speed	km/h

4 Classification system

4.1 Definition of line categories

The use of a classification system using line categories permits easy understanding of the load-related compatibility of vehicles and infrastructure.

The line category resulting from the classification process for infrastructure represents the ability of the infrastructure (track, track substructures, earthworks, civil engineering structures) to withstand the vertical loads imposed by vehicles on the line or section of line for regular service.

Each line category (a10, a12, a14, A, B1, B2, C2, C3, C4, D2, D3, D4, D5, D4xL and also E4 and E5, E6) is defined by a load model based on reference wagons defined by the characteristics given in Annex A:

- axle load;
- geometrical characteristics of the spacing of axles;
- length of the vehicle.

The value “mass per unit length” of the reference wagon is determined from the above parameters.

4.2 Correlation to types of vehicles

The load effects of different vehicle types are compared to the load models defining the different line categories.

All types of vehicles and freight wagons with their corresponding payload are covered by the line categories A, B1, B2, C2, C3, C4, D2, D3, D4.

Line categories D5, E4, E5 and E6 are defined exclusively for heavy freight wagons.

Locomotives can be covered by:

- line categories B1, B2, C2, C3, C4, D2, D3, D4 and D4xL (plus optional detailed specification for axle spacing ranges);
- locomotive classes L4 and L6.

Passenger carriages and Multiple Units can be covered by:

- line categories a10, a12, a14, B1, C2, D2 (plus optional detailed specification for axle spacing and vehicle lengths). Line categories a10, a12 and a14 have been specially developed for light rail vehicles with up to 14 t axle loads.
- MU-groups and MU-classes, which are provided to assist additional compatibility checks between infrastructure and vehicles where there is a risk of excessive dynamic effects in bridges.

For rail vehicles or wagons with payload limits categorized above D4 or D4xL it is recommended that the infrastructure manager and railway undertaking consider the use of static and dynamic wheel load measuring devices attached to the track and/or fitted to vehicles to assist with ensuring compliance with the requirements of this European Standard.

4.3 Correlation between line category and speed

4.3.1 Introduction

The classification of infrastructure applies to all types of railway vehicles, which can have different maximum speeds (e.g. freight and passenger traffic). Additional information defining the maximum speed corresponding to the line category shall be stated.

As a result of the classification of infrastructure, additional information specifying the line classification can be given to cover two or more combinations (e.g. different maximum speeds and associated line categories for passenger and freight trains).

NOTE Examples illustrating information about line classification and relationship with speed are given in Annex H.

The combinations used for publication should be in accordance with legal, technical and operational requirements (e.g. ETCS ²⁾ speed levels).

The local line speed shall be taken into account for the classification of engineering structures (see 5.1) and other relevant infrastructure elements (see 5.2).

The line category and associated maximum speed shall be considered as a single combined quantity.

4.3.2 Freight traffic

When classifying infrastructure lines into line categories, the line category at maximum freight traffic speed (maximum 120 km/h) shall be determined.

120 km/h corresponds to the maximum speed for conventional freight traffic and is the limit of validity for freight traffic using line categories. In excess of 120 km/h individual checks shall be carried out.

Optionally, an additional higher line category at an associated lower speed (less than the maximum freight traffic speed) may be determined.

NOTE In some situations it may be desirable to determine the line category at a lower speed to maximize the line category.

In addition, for D5, E4, E5 or E6 lines, an associated maximum speed for such traffic shall be stated together with the associated maximum speed for conventional line traffic of line category D4.

4.3.3 Mixed traffic and passenger traffic

On mixed traffic lines with passenger traffic, the line category at maximum freight traffic speed in 4.3.2 is generally sufficient and appropriate for the optimization of freight traffic.

For vehicles and locomotives, categorized into the same or lesser line category as the line, and which run faster than the maximum freight traffic speed, additional checks starting on the basis of the maximum freight traffic speed shall be taken into account for the classification of engineering structures (see 5.1) and other relevant infrastructure elements (see 5.2).

For speeds over 120 km/h and up to the maximum line speed, the different combinations of line categories-with speed shall be in accordance with general technical and operational requirements or restrictions.

NOTE Line Categories as classification information for speeds over 120 km/h may be related to vehicle types or types of traffic. Additional compatibility checks at different speed levels for different vehicle types may be required to demonstrate compatibility (see 5.1.2 and Annex F).

2) European Train Control System.