

SVENSK STANDARD


SS-EN 13201-2:2016

Fastställt/Approved: 2016-01-11
Publicerad/Published: 2016-01-15
Utgåva/Edition: 2
Språk/Language: engelska/English
ICS: 12.020; 93.080.40



Vägbelysning – Del 2: Krav på prestanda

Road lighting – Part 2: Performance requirements



Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Europastandarden EN 13201-2:2015 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 13201-2:2015.

Denna standard ersätter SS-EN 13201-2, utgåva 1.

The European Standard EN 13201-2:2015 has the status of a Swedish Standard. This document contains the official English version of EN 13201-2:2015.

This standard supersedes the Swedish Standard SS-EN 13201-2, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Ljus och belysning, SIS/TK 380/AG 3.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

EUROPEAN STANDARD

EN 13201-2

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2015

ICS 93.080.40

Supersedes EN 13201-2:2003

English Version

Road lighting - Part 2: Performance requirements

Eclairage public - Partie 2: Exigences de performance

Straßenbeleuchtung - Teil 2: Gütemerkmale

This European Standard was approved by CEN on 6 June 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword	3
Introduction	4
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Requirements for motorized traffic	8
5 Requirements for conflict areas	10
6 Requirements for pedestrians and pedal cyclists	11
6.1 General requirements	11
6.2 Additional requirements	12
7 Appearance and environmental aspects	13
Annex A (informative) Installed classes for glare restriction and control of obtrusive light	15
Annex B (informative) Lighting of pedestrian crossings	19
Annex C (informative) Evaluation of disability glare for C and P classes	20
Bibliography	21

European foreword

This document (EN 13201-2:2015) has been prepared by Technical Committee CEN/TC 169 “Light and lighting”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2016 and conflicting national standards shall be withdrawn at the latest by June 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13201-2:2003.

In comparison with EN 13201-2:2003, the following significant changes have been made:

- restructuring of the document;
- addition of an introduction including background information;
- updating of terms and definitions;
- combination of several classes;
- replacement of the abbreviation TI with the symbol f_{TI} ;
- change of several class designations;
- change of the designations of the luminous intensity classes;
- addition of a new informative Annex C on evaluation of disability glare for C and P classes.

This document EN 13201-2 has been worked out by the Joint Working Group of CEN/TC 169 “Light and lighting” with CEN/TC 226 - “Road Equipment”, the secretariat of which is held by AFNOR.

EN 13201, *Road lighting* is a series of documents that consists of the following parts:

- *Part 1: Guidelines on selection of lighting classes* [Technical Report];
- *Part 2: Performance requirements* [present document];
- *Part 3: Calculation of performance*;
- *Part 4: Methods of measuring lighting performance*;
- *Part 5: Energy performance indicators*.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

A lighting class is defined by a set of photometric requirements aiming at the visual needs of certain road users in certain types of road areas and environment. The needs can vary at different periods during the night and also in different seasons of the year, thus the recommendations may vary during these periods.

The purpose of introducing lighting classes is to make it easier to develop and use road lighting products and services in CEN member countries. The lighting classes have been defined with consideration of road lighting standards in these countries and the lighting classes defined in CIE 115:2010 (2nd Edition) aiming at harmonization of requirements where possible. However, specific circumstances concerned with the road layout, use and national approaches based on traditional, climatic or other conditions could require different values of the uniformities. Not all the classes describe in this standard should be applied in a given country.

The M classes are intended for drivers of motorized vehicles for use on traffic routes, and in some countries also residential roads, allowing medium to high driving speeds.

The main lighting criteria of these classes are based on the road surface luminance of the carriageway and include the average luminance, the overall uniformity and the longitudinal uniformity for the dry road surface condition. Additional criteria relate to disability glare quantified by the Threshold Increment TI and the lighting of the surrounding areas quantified by the Edge Illuminance Ratio EIR. An additional criterion, used in some countries, is the overall uniformity of luminance in a wet condition.

The C classes are also intended for drivers of motorized vehicles, but for use on conflict areas such as shopping streets, road intersections of some complexity, roundabouts and queuing areas, where the conventions for road surface luminance calculations do not apply or are impracticable. The lighting criteria are based on the horizontal illuminance and are expressed by the average and the overall uniformity. These classes have applications also for pedestrians and pedal cyclists.

The P classes or the HS classes are intended for pedestrians and pedal cyclists on footways, cycleways, emergency lanes and other road areas lying separately or along the carriageway of a traffic route, and for residential roads, pedestrian streets, parking places, schoolyards, etc.

The lighting criteria of the P classes are based on the horizontal illuminance on the road area and are expressed by the average and the minimum illuminance.

The lighting criteria of the HS classes are based on the hemispherical illuminance of the road area and are expressed by the average hemispherical illuminance and the overall uniformity of this illuminance.

The SC classes are intended as an additional class in situations where public lighting is necessary for the identification of persons and objects and in road areas with a higher than normal crime risk.

The EV classes are intended as an additional class in situations where vertical surfaces need to be seen in such road areas as toll stations, interchange areas, etc.

The requirements of the lighting classes reflect the category of road user in question or the type of road area. Thus the M classes are based on the road surface luminance, while the C, P and HS classes are based on the illuminance of the road area. The SC classes are based on semi-cylindrical illuminance, while the EV classes are based on the vertical plane illuminance.

Each series of lighting classes presents decreasing requirements in their order and form steps of lighting level.

The specified lighting levels are maintained levels which are defined as the design levels reduced by a maintenance factor to allow for depreciation (refer to 3.10). The required maintenance factor, or a maintenance regime that allows deduction of the maintenance factor, should be included in tender specifications.

It should be taken into account that the light output of some light sources is sensitive to temperature. As photometric data are generally published considering a reference temperature of 25 °C, a correction factor should be considered for these light sources, if ambient temperatures are different.

Environmental aspects of road lighting are considered in Clause 7 in terms of day time appearance, night time appearance and light emitted in directions, where it is neither necessary nor desirable. The purpose is to highlight criteria that can be included in tender specifications or similar, where relevant.

Installed luminous intensity classes for the restriction of disability glare and control of obtrusive light G*1, G*2, G*3, G*4, G*5 and G*6 are introduced in the informative Annex A. The use of G* classes is mentioned in Clause 5 for conflict areas and in Clause 7 on appearance and environmental aspects.

Installed glare index classes for the restriction of discomfort glare D0, D1, D2, D3, D4, D5 and D6 are introduced in the informative Annex A as well. These classes are intended mainly for road areas lighted for the benefit of pedestrians and pedal cyclists.

Additional items considered in the Annex A are the use of installed luminous intensity classes and obtrusive lighting.

Local lighting of pedestrian crossings is considered in the informative Annex B. The intention of local lighting is to attract the attention of drivers of motorized vehicles to the presence of the pedestrian crossing and to illuminate pedestrians in or at the crossing area.

For the C and P classes, disability glare conditions considering the TI are described in the informative Annex C.

All photometric quantities are based on photopic photometry.

From an energy efficiency and environmental perspective a lighting installation should have a lighting level that matches the minimum required value of the relevant lighting class, and should meet all other relevant requirements, for instance uniformity, lighting of surrounding areas or additional classes (SC or EV). In that sense, the lighting levels specified in the tables are target values for minimum maintained levels.

Maximum lighting levels may be provided in tender specifications or national regulations.

When designing new road lighting installations, all the lighting requirements specified in Clauses 4, 5 and 6 are relevant, and also requirements on environmental aspects as considered in Clause 7, should be complied with.

When modifying the optical components or the geometry of existing lighting installations (for instance by changing the luminaires), it should be attempted to comply with all requirements. However, this may be highly impractical or expensive in some cases, while deviations from one or more of the requirements may lead to more practicable and less expensive solutions. In such cases, decisions should only be taken after careful consideration of all the aspects.

1 Scope

This part of this European Standard defines *performance requirements which are specified as lighting classes for road lighting aiming at the visual needs of road users*, and it considers environmental aspects of road lighting.

NOTE Installed luminous intensity classes for the restriction of disability glare and control of obtrusive light and installed glare index classes for the restriction of discomfort glare are defined in the informative Annex A. Lighting of pedestrian crossings is discussed in the informative Annex B. Disability glare evaluation for conflict areas (C classes) and pedestrian and pedal cyclists (P classes) is discussed in the informative Annex C.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13201-3, *Road lighting — Part 3: Calculation of performance*

EN 13201-4, *Road lighting — Part 4: Methods of measuring lighting performance*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 average road surface luminance (of a carriageway of a road)

$$\bar{L}$$

luminance of the road surface averaged over the carriageway

Note 1 to entry: Unit is candelas per square metre (cd·m²).

3.2 longitudinal uniformity (of road surface luminance of a carriageway)

$$U_l$$

lowest of the ratios determined for each driving lane of the carriageway as the ratio of the lowest to the highest road surface luminance found in a line in the centre along the driving lane

3.3 threshold increment TI (of an object at the road surface)

$$f_{TI}$$

percentage increase of contrast of an object that is needed to make it stay at threshold visibility in presence of disability glare generated by luminaires of a road lighting installation.

Note 1 to entry: TI is a measure of the effect of disability glare, described as an equivalent veiling luminance caused by scattering of light in the human eye. TI values are calculated in accordance with EN 13201-3 by means of an equation for the equivalent veiling luminance which represents a young person. When setting requirements for the limitation of the TI, or when evaluating calculated TI values, it should be taken into account that the scattering in the eye tends to increase with the age of the person. The increase is individual and may be low for some, by a factor of two for others and can be high for persons suffering from untreated cataract conditions.

3.4**edge illuminance ratio EIR (of illumination of a strip adjacent to the carriageway of a road)** R_{EI}

average horizontal illuminance on a strip just outside the edge of a carriageway in proportion to the average horizontal illuminance on a strip inside the edge, where the strips have the width of one driving lane of the carriageway

Note 1 to entry: Separate values apply for each of the two sides of a carriageway, and for each of the two sides of both carriageways of a dual carriageway. When a minimum requirement is made for the EIR of a lighting installation, each of the separate values shall meet the requirement.

3.5**average illuminance (on a road area)** \bar{E}

horizontal illuminance averaged over a road area

Note 1 to entry: Unit is lux (lx).

3.6**minimum illuminance (on a road area)** E_{\min}

lowest illuminance on a road area

Note 1 to entry: Unit is lux (lx).

3.7**hemispherical illuminance (at a point on a road area)** E_{hs}

luminous flux on a small hemisphere with a horizontal base divided by the surface area of the hemisphere

Note 1 to entry: Unit is lux (lx).

3.8**average hemispherical illuminance (on a road area)** \bar{E}_{hs}

hemispherical illuminance averaged over a road area

Note 1 to entry: Unit is lux (lx).

3.9**overall uniformity (of road surface luminance, illuminance on a road area or hemispherical illuminance)** U_o

ratio of the lowest to the average value

3.10**maintained level (of average road surface luminance, average or minimum illuminance on road area, average hemispherical illuminance, minimum semi-cylindrical illuminance or minimum vertical plane illuminance)**

design level reduced by a maintenance factor to allow for depreciation