

SVENSK STANDARD

SS-ISO 3864-4:2016

Fastställt/Approved: 2016-03-29
Publicerad/Published: 2016-03-31
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 01.080.10; 01.080.20

Grafiska symboler – Varselmärkning och varselskyltar – Del 4: Kolorimetriska och fotometriska materialegenskaper hos varselskyltar (ISO 3864-4:2011, IDT)

Graphical symbols – Safety colours and safety signs – Part 4: Colorimetric and photometric properties of safety sign materials (ISO 3864-4:2011, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8019678>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 3864-4:2011 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 3864-4:2011.

The International Standard ISO 3864-4:2011 has the status of a Swedish Standard. This document contains the official English version of ISO 3864-4:2011.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Symboler, SIS/TK 493.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Requirements	3
4.1 General	3
4.2 Object colour under external illumination	4
4.3 Object colour of powered internally illuminated safety signs	4
5 Test methods	8
5.1 General	8
5.2 Object colour under external illumination	9
5.3 Object colour of powered internally illuminated safety signs	10
Annex A (informative) Object colour of different types of safety sign and material	11
Annex B (normative) Classification of emission colour of phosphorescent material	13
Annex C (normative) Specification of colour and photometric instrumentation	16
Annex D (informative) Guidance on photometric relationships between and within safety and contrast colours of graphical symbols	18
Annex E (informative) Examples of safety colours and contrast colours for object colours of ordinary materials	19
Annex F (informative) Consideration of defective colour vision	21
Bibliography	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

ISO 3864-4 was prepared by Technical Committee ISO/TC 145, *Graphical symbols*, Subcommittee SC 2, *Safety identification, signs, shapes, symbols and colours*.

This part of ISO 3864, together with ISO 3864-1:—, cancels and replaces ISO 3864-1:2002, which has been technically revised.

ISO 3864 consists of the following parts, under the general title *Graphical symbols — Safety colours and safety signs*:

- *Part 1: Design principles for safety signs and safety markings*
- *Part 2: Design principles for product safety labels*
- *Part 3: Design principles for graphical symbols for use in safety signs*
- *Part 4: Colorimetric and photometric properties of safety sign materials*

Introduction

This part of ISO 3864 has been prepared to provide manufacturers/suppliers of safety signs and test laboratories and instrument manufacturers with specifications of the colorimetric and photometric properties of safety signs comprising different types of material and with test methods.

Consistent use of this part of ISO 3864 will assist in improving knowledge of safety-sign requirements and in furthering understanding of the performance of various types of safety signs in everyday use.

This part of ISO 3864 is intended to be used by all Technical Committees within ISO charged with developing specific safety signing for their industry, to ensure that there is only one set of colorimetric and photometric requirements and test methods for safety signs.

Note that some countries' statutory regulations may differ in some respect from those given in this part of ISO 3864.

Graphical symbols — Safety colours and safety signs —

Part 4: Colorimetric and photometric properties of safety sign materials

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This part of ISO 3864 establishes the colorimetric and photometric requirements and test methods for the colours of safety signs to be used in workplaces and public areas. It provides the colorimetric and photometric specifications for the named safety and contrast colours prescribed in ISO 3864-1.

The physical requirements that safety signs have to meet are primarily related to daytime colour and normally lit environments. This part of ISO 3864 also includes the colorimetric requirements and test methods for safety signs and phosphorescent material which also operate in unlit environments.

This part of ISO 3864 is applicable to all locations where safety issues related to people need to be addressed. However, it is not applicable to signalling used for guiding rail, road, river, maritime and air traffic and, generally speaking, to those sectors subject to a regulation that may differ.

The colorimetric and photometric properties of retroreflective safety signs, retroreflective materials combined with fluorescent or phosphorescent materials, or luminous safety signs activated by a radioactive source are not specified in this part of ISO 3864.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3864-1: —¹⁾, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 17724:2003, *Graphical symbols — Vocabulary*

CIE 15, *Colorimetry*

CIE 69, *Methods of characterizing illuminance meters and luminance meters: Performance, characteristics and specifications*

1) To be published. (Revision of ISO 3864-1:2002)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17724 and the following apply.

3.1 colour region
boundary values of x , y chromaticity coordinates of the CIE 2° standard colorimetric observer and luminance factor or luminance for the named colour

3.2 contrast
 C
difference in luminance factors of the graphical symbol and its background, divided by the larger luminance factor β_a , where β_b is the smaller luminance factor

$$C = (\beta_a - \beta_b) / \beta_a$$

3.3 contrast colour
colour that contrasts with the safety colour in order to make the safety colour more conspicuous

3.4 externally illuminated safety sign
safety sign that is illuminated, when required, by an external source

3.5 internally illuminated safety sign
safety sign that is illuminated, when required, by an internal source

3.6 luminance contrast
 k
luminance of the contrast colour, L_1 , divided by the luminance of the safety colour, L_2 , where L_1 is greater than L_2

$$k = L_1 / L_2$$

[ISO 17724:2003, definition 43]

3.7 luminance factor
 β
ratio of the luminance of the surface element in a given direction to that of a perfect reflecting or transmitting diffuser identically illuminated

[ISO 17724:2003, definition 44]

3.8 maintained safety sign
sign in which the integral lamps are energized at all times when normal or emergency mode of operation is required

3.9 non-maintained safety sign
sign in which the integral lamps are in operation only when the power supply to the normal lighting fails

3.10

object colour

named colour of safety sign elements specified in terms of chromaticity coordinates x, y of the CIE 2° standard colorimetric observer and either luminance factor or luminance

3.11

ordinary material

material which is neither retroreflecting nor fluorescent nor phosphorescent nor involves powered light emission nor is activated by a radioactive source

3.12

phosphorescent material

material incorporating phosphors that, if excited by UV or visible radiation, store energy, which is emitted as light over a period of time

3.13

safety colour

specific colour with special properties to which a safety meaning is attributed

[ISO 17724:2003, definition 66]

4 Requirements

4.1 General

All colorimetric and photometric requirements apply to the materials as used in the finished sign.

The safety colours and contrast colours for the geometric shape of safety signs and the graphical symbols for particular types of safety signs are given in ISO 3864-1.

The requirements are based on the CIE 2° standard colorimetric observer, as specified in CIE 15.

Where the requirement involves the colour of the sign material under external illumination, the requirements are based on CIE Standard illuminant D65 at either an angle of 45° with the normal to the surface and the observation made in the direction of the normal (45°a:0° geometry) or normal to the surface and observation made in the direction of 45° to the surface (0°:45°a geometry).

Requirements and test methods are given for safety signs in lit and unlit conditions.

NOTE Information on colour characteristics of externally illuminated, internally illuminated and phosphorescent materials is given in Annex A.

Safety signs without an integral source of light are required to be externally illuminated for their intended function.

Internally illuminated safety signs are classified as “maintained” (integral light source is powered) or “non-maintained” (sign is externally illuminated when the integral light source is unpowered, but in an emergency condition the integral light source is powered). If the sign is intended to be dimmed, the requirements need to be met under this condition as well.

Phosphorescent safety signs have applications in both lit and unlit environments. For example, during an emergency, the excited phosphorescent materials emit light over a period of time.

Requirements are specified in terms of colour region for each named colour.

Requirements for safety signs comprised of ordinary materials are specified in 4.2.1. Requirements for non-maintained internally illuminated safety signs are specified in 4.2.2 (when the integral light source is not powered) and in 4.3 (when the integral light source is powered). Requirements for maintained internally