

SVENSK STANDARD

SS-ISO 12647-2:2016



Fastställt/Approved: 2016-04-26
Publicerad/Published: 2016-05-02
Utgåva/Edition: 3
Språk/Language: engelska/English
ICS: 37.100.01

Grafisk teknik – Processtyrning vid framställning av färgseparationer, provtryck och upplagetryck – Del 2: Offsettryckning (ISO 12647-2:2013, IDT)

Graphic technology – Process control for the production of half-tone colour separations, proof and production prints – Part 2: Offset lithographic processes (ISO 12647-2:2013, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8020234>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 12647-2:2013 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 12647-2:2013.

Denna standard ersätter SS-ISO 12647-2:2004/Amd 1:2007, utgåva 1.

The International Standard ISO 12647-2:2013 has the status of a Swedish Standard. This document contains the official English version of ISO 12647-2:2013.

This standard supersedes the Swedish Standard SS-ISO 12647-2:2004/Amd 1:2007, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Grafisk teknik, SIS/TK 434.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

| Contents | Page |
|--|-----------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 Requirements | 2 |
| 4.1 General..... | 2 |
| 4.2 Data files and printing formes..... | 2 |
| 4.3 Proof or production print..... | 4 |
| 5 Measurement methods | 18 |
| 5.1 Computation of densities, CIELAB colour coordinates and CIELAB colour differences..... | 18 |
| 5.2 Control strip..... | 18 |
| Annex A (informative) Grey reproduction and grey balance | 19 |
| Annex B (informative) Handling differences in paper colour | 23 |
| Bibliography | 25 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 130, *Graphic Technology*.

This third edition cancels and replaces the second edition which has been extensively revised. The revisions include the following:

- a) deletion of film-based requirements;
- b) changes in proof requirements;
- c) changes in printing conditions;
- d) changes in the colouration of the primary and secondary solids;
- e) introduction of new tone value increase curves;
- f) general clean up.

ISO 12647 consists of the following parts, under the general title *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints*:

- *Part 1: Parameters and measurement methods*
- *Part 2: Offset lithographic processes*
- *Part 3: Coldset offset lithography on newsprint*
- *Part 4: Publication gravure printing*
- *Part 5: Screen printing*
- *Part 6: Flexographic printing*
- *Part 7: Proofing processes working directly from digital data*
- *Part 8: Validation print processes working directly from digital data*

Introduction

This part of ISO 12647 lists values or sets of values of the primary process parameters specified in ISO 12647-1 and related technical properties of a half-tone offset lithographic print. Primary parameters constitute a general printing condition and are defined here as the substrate description, the colorant description, the screening description, the tone value increase and the ink sequence. Since the printing ink to be used in this International Standard is to conform to ISO 2846-1, it is in general not necessary to name it as a primary process parameter.

Conformance to the specified values in proof and production printing ensures, in principle, a good visual match between specimens produced. A visual and in part measurement-wise “proof-to-print match” is essential for globally consistent printing and publishing workflows in general. A press proof print might be necessary when using specific printing conditions that use different types of surface finishing.

As the printing and publishing world has accepted former editions of this International Standard, it has struggled to implement the different paper types. The paper type specifications by means of tristimulus values, originally defined as a guideline for press proof prints, have been wrongly interpreted as an exclusive prerequisite for papers to be “in conformance with ISO 12647-2”. In addition, it has become evident that the paper types defined by this International Standard reflect market papers poorly. Therefore, some industry groups, while using the general principles of this International Standard, have established additional printing conditions with different paper specifications.

When revising this International Standard a new paper categorization was established. This was necessary since there is no agreed upon method to predict the printing behaviour based on colorimetric readings of the unprinted print substrate. When the visual printing characteristics of typical printed papers were analysed, different sets of colorant descriptions were identified. A closer look revealed that these sets corresponded to the surface (CIE whiteness, gloss, and coating) and mass per area characteristics (opacity).

A print is therefore in conformance with this International Standard when:

- the colorimetric aims of the process colours, defined by the general printing conditions and using typical means of inking, are achievable;
- by agreement between all parties, an additional printing condition is established and aim values for this printing condition are clearly communicated, for example by exchanging a characterization.

This International Standard addresses typical industrial printing under feasible economical constraints. The tolerance values have therefore been chosen to provide a reasonable balance between customer expectations (meaning small variations), technical production limits and production costs. Assuming agreements between all parties concerned, tolerances might be tightened especially when primary or secondary process parameters (e.g. paper) can be fixed in the planning stage.

Graphic technology — Process control for the production of half-tone colour separations, proof and production prints —

Part 2: Offset lithographic processes

1 Scope

This part of ISO 12647 specifies a number of process parameters and their values to be applied when producing colour separations, printing formes and print production for four-colour sheet-fed and web-fed offset printing presses excluding coldset offset lithography on newsprint.

The parameters and values are chosen in view of the typical process covering the process stages “colour separation”, “proof production”, “making of the printing forme”, “OK print” and “production printing” on all kinds of commercially available production substrates.

This part of ISO 12647:

- is directly applicable to press proof prints and printing processes that use colour separation printing formes as input;
- is applicable to press proof prints and printing processes with more than four process colours as long as direct analogies to four-colour printing are maintained, such as for data and screening, for print substrates and printing parameters;
- is applicable to printing on cardboard material for packaging;
- is applicable for all kinds of drying methods such as heat-set, infrared, and ultraviolet;
- provides references for quality assurance and quality management.

This part of ISO 12647 is not applicable to processes other than offset such as printing directly from digital data where there is no intermediate image carrier, or where the image carrier can be refreshed for each impression and thus each impression can be different in content.

2 Normative references

The following referenced documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2846-1, *Graphic technology — Colour and transparency of printing ink sets for four-colour printing — Part 1: Sheet-fed and heat-set web offset lithographic printing*

ISO 8254-1, *Paper and board — Measurement of specular gloss — Part 1: 75 degree gloss with a converging beam, TAPPI method*

ISO 8254-2, *Paper and board — Measurement of specular gloss — Part 2: 75 degree gloss with a parallel beam, DIN method* [alternative to ASTM D7163]

ISO/TS 10128, *Graphic technology — Methods of adjustment of the colour reproduction of a printing system to match a set of characterization data*

ISO 11475, *Paper and board — Determination of CIE whiteness, D65/10 degrees (outdoor daylight)*

ISO 12647-1, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 1: Parameters and measurement methods*

ISO 12647-7, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 7: Proofing processes working directly from digital data*

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ASTM D7163, *Standard Test Method for Specular Gloss of Printed Matter* [alternative to ISO 8254-2]

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12647-1 and the following apply.

3.1 area coverage

ratio of the area covered with ink to the entire area in an ink zone

3.2 calibration

adjustment based on a comparison between a standard and a unit under test

3.3 characterization data

set of tone values and associated colorimetric values that fully describe a given printing process

3.4 tone value

(printing forme) percentage of surface area that is covered by printing ink

4 Requirements

4.1 General

Digital data files delivered for printing should be accompanied by a digital proof print, a press proof print, or an OK print from a previous print run.

NOTE Press proof prints are test prints of the data files on a printing press which may serve as a reference for subsequent printing. While most proofs are digital proofs, for colour- or content-critical work there is a need for press proof prints with the same setup as the production print.

4.2 Data files and printing formes

4.2.1 Data delivery

Data delivered for printing shall be in the colour formats CMYK or three-component and should be exchanged using PDF/X [6][7] data formats.

The intended printing condition shall be indicated. In case of PDF/X the mechanisms provided by the specified data format shall be used. In case of other data formats a printing condition description, a characterization data set [3][4] or an International Colour Consortium (ICC) output profile [5] shall be communicated.

If the data are other than CMYK, the data shall be defined by colorimetric descriptions using an ICC profile or another mechanism and an ICC CMYK output profile shall be included. The rendering intent to be used for each data element shall be communicated.

If the characterization data or ICC output profile provided conflicts with the printing conditions defined in this part of ISO 12647 one of the methods defined in ISO/TS 10128 shall be used for data adjustment

prior to print production. The aims for process control should be taken from characterization data, if agreed between all parties. Where this is done, densitometric tone values are not usually available and colorimetric tone values should be used. Further information on the relationship between colorimetric and densitometric tone values can be found in ISO/TS 10128.

NOTE 1 A printing condition is defined here as a print substrate description, a colorant description, a screening description, an ink set and a printing sequence.

NOTE 2 Quality control of the content of a print job prior to final production checks is recommended since PDF/X conformance does not necessarily ensure a suitable image resolution or other production dependent criteria.

NOTE 3 Additional spot colours are allowed but this part of ISO 12647 does not make provisions for tolerances.

4.2.2 Printing forme quality

The resolution of the plate setter should be selected to ensure that at least 150 tone value steps are reproduced.

EXAMPLE If, for a screen employing single half-tone cell modulation, the intended nominal screen ruling is 80 cm^{-1} , the resolution of the plate setter should not be less than $1\,000 \text{ cm}^{-1}$. For a screen with super-cell technology, it is possible to set the resolution to a smaller value.

4.2.3 Screen frequency (periodic screens)

For four-colour work, the screen frequency (screen ruling) for periodic screens should be within the range from 48 cm^{-1} to 80 cm^{-1} .

Preferred nominal screen frequencies are:

- a) 48 cm^{-1} to 80 cm^{-1} for coated paper; and
- b) 48 cm^{-1} to 70 cm^{-1} for uncoated paper.

NOTE 1 Outside of the range 48 cm^{-1} to 80 cm^{-1} , the general principles specified in ISO 12647-1 remain valid but specific values might differ.

NOTE 2 The screen frequency is often varied slightly from one process colour to another in order to minimize moiré patterns. For example, there might be a difference of up to 6 % of the nominal screen frequency between the colours C, M, Y.

NOTE 3 For the black or yellow colour half-tone, a screen frequency is sometimes used which is substantially finer than the nominal screen ruling of the remaining colours, for example, 84 cm^{-1} versus 60 cm^{-1} .

NOTE 4 Screen frequencies are often required or given in lpi (lines per inch). To convert between screens per cm and lines per inch a conversion factor of 2,54 should be used.

EXAMPLE The requirement 4.2.3 given in lpi will read as follows (rounded to commonly used integral numbers): for four-colour work, the screen frequency (screen ruling) for periodic screens should be within the range from 120 lpi to 200 lpi. Preferred nominal screen frequencies are a) 120 lpi to 200 lpi for coated paper; and b) 120 lpi to 175 lpi for uncoated paper.

4.2.4 Dot size (non-periodic screens)

For four-colour work, the screen dot size for non-periodic screens should be within the range $20 \mu\text{m}$ to $40 \mu\text{m}$.

Preferred nominal screen dot sizes are:

- a) $20 \mu\text{m}$ to $30 \mu\text{m}$ for coated paper; and
- b) $30 \mu\text{m}$ to $40 \mu\text{m}$ for uncoated paper.

NOTE Outside of the range $20 \mu\text{m}$ to $40 \mu\text{m}$, the general principles specified in ISO 12647-1 remain valid but specific values might differ.