

SVENSK STANDARD

SS-EN 16727-2-2:2016

Fastställt/Approved: 2016-05-16
Publicerad/Published: 2016-05-18
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 45.060.01; 93.100

**Järnvägar – Spår – Bullerbarriärer och andra arrangemang som motverkar utbredningen av luftburet buller – Icke-akustiska egenskaper –
Del 2-2: Mekaniska egenskaper vid dynamiska belastningar orsakade av passerande tåg – Beräkningsmetod**

**Railway applications – Track – Noise barriers and related devices acting on airborne sound propagation – Non-acoustic performance –
Part 2-2: Mechanical performance under dynamic loadings caused by passing trains – Calculation method**

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8020472>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.



Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Europastandarden EN 16727-2-2:2016 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 16727-2-2:2016.

The European Standard EN 16727-2-2:2016 has the status of a Swedish Standard. This document contains the official English version of EN 16727-2-2:2016.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Järnvägar, SIS/TK 254.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

EUROPEAN STANDARD

EN 16727-2-2

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2016

ICS 93.100

English Version

Railway applications - Track - Noise barriers and related devices acting on airborne sound propagation - Non-acoustic performance - Part 2-2: Mechanical performance under dynamic loadings caused by passing trains - Calculation method

Applications ferroviaires - Voie - Écrans antibruit et dispositifs connexes influant sur la propagation aérienne du son - Performances non acoustiques - Partie 2-2: Tenue mécanique sous charges dynamiques dues à la circulation ferroviaire - Méthode de calcul

Bahnanwendungen - Oberbau - Lärmschutzwände und verwandte Vorrichtungen zur Beeinflussung der Luftschallausbreitung - Nicht akustische Eigenschaften - Teil 2-2: Mechanische Eigenschaftsanforderungen unter dynamischen Belastungen infolge Zugverkehr - Berechnungsverfahren

This European Standard was approved by CEN on 12 March 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Symbols and abbreviations	6
5 Quasi-static equivalent load model	7
5.1 Application requirements	7
5.2 Air pressure wave	7
5.3 Quasi-static equivalent load	7
5.4 Length factor	7
5.5 Height factor	8
5.6 Dynamic factor	9
6 Relevant load model position of the air pressure wave at noise barriers	11
6.1 Load q_{DS}	11
6.2 Mid-post	11
6.3 End-post	12
6.4 Corner-post	13
6.5 Panel	14
7 Internal forces on a post	15
7.1 General	15
7.2 Static system	16
7.3 Internal forces on a post	16
8 Calculation report	16
Annex A (informative) Natural frequency of the wall system	17
Annex B (informative) Example of use	20
Bibliography	22

European foreword

This document (EN 16727-2-2:2016) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2016, and conflicting national standards shall be withdrawn at the latest by November 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

This European Standard is one of the series EN 16727, *Railway applications — Track — Noise barriers and related devices acting on airborne sound propagation — Non-acoustic performance*, as listed below:

- *Part 1: Mechanical performance under static loadings — Calculation and test methods* [currently at Enquiry stage];
- *Part 2-1: Mechanical performance under dynamic loadings due to passing trains — Resistance to fatigue* [currently at Enquiry stage];
- *Part 2-2: Mechanical performance under dynamic loadings caused by passing trains — Calculation method* [published];
- *Part 3: General safety and environmental requirements* [currently at Enquiry stage].

It should be read in conjunction with:

- EN 1990, *Eurocode — Basis of structural design*;
- EN 1991-2, *Eurocode 1: Actions on structures — Part 2: Traffic loads on bridges*;
- EN 1992 series, *Eurocode 2: Design of concrete structures*;
- EN 1993 series, *Eurocode 3: Design of steel structures*;
- EN 1997 series, *Eurocode 7: Geotechnical design*;
- EN 1999 series, *Eurocode 9: Design of aluminium structures*;
- EN 14067-4, *Railway applications — Aerodynamics — Part 4: Requirements and test procedures for aerodynamics on open track*.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

Passing trains generate pressure variations in the shape of air pressure waves which impact on noise barriers installed alongside the track. Noise barriers need to withstand this impact without any part of them becoming detached or displaced in a way that creates a safety hazard for passing trains or people. This European standard presents a calculation method to assess the capacity of noise barriers having a post-and-panel structure with piled foundations to resist this pressure variation including an allowance for dynamic response of the structure.

The air pressure wave generated by a passing train is described in terms of two block loads in EN 1991-2:2003, 6.6.2. For calculating realistic static and dynamic actions on noise barriers, it is necessary to consider also the shape of the air pressure wave and the dynamic effects.

1 Scope

This European standard defines the loading, the relevant load model positions and the internal forces acting on noise barriers, due to the air pressure wave set out in EN 1991-2:2003, 6.6.2. The vertical and horizontal shapes of the air pressure wave and the dynamic effects have been taken into account. The calculation method described in this European standard has been developed for noise barriers having a post-and-panel structure with piled foundations. It can also be used where cladding is attached to a rigid structure. For structures with piled foundations, an empirical formula for determination of the natural frequency is given in Annex A. Annex B contains an example of application of the calculation method for determination of internal forces and moments acting on a mid-post. The design of noise barriers (e.g. to fatigue resistance) is not part of this standard.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1991-2:2003, *Eurocode 1: Actions on structures - Part 2: Traffic loads on bridges*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

noise barrier

noise reducing device, which obstructs the direct transmission of airborne sound emanating from railways and which will typically span between posts and also may overhang the railway

Note 1 to entry: Noise barriers are generally made of acoustic and structural elements (3.3 and 3.4).

3.2

cladding

noise reducing device, which is attached to a wall or other structure and reduces the amount of sound reflected

Note 1 to entry: Claddings are generally made of acoustic and structural elements (3.3 and 3.4).

3.3

acoustic element

element whose primary function is to provide the acoustic performance of the device

3.4

structural element

element whose primary function is to support or hold in place acoustic elements

Note 1 to entry: In some noise barriers the acoustic function and the structural function cannot be clearly separated and attributed to different components.

3.5

added device

added component that influences the acoustic performance of the original noise-reducing device (acting primarily on the diffracted energy)

3.6 load model

simplified mathematical description of a complicated loading, such as the air pressure wave generated by a passing train

3.7 quasi-static load model

load model including dynamic effects of loading

4 Symbols and abbreviations

For the purposes of this document, the following symbols and abbreviations apply.

a_g	distance of wall system surface from the centreline of the track in m
a	spacing to a post or between two posts along track in m
f	first natural frequency of the wall system in Hz
h	wall height above rail top in m
h_m	height between the surface of the ground and the top of the rail
h_u	height between the top of the pile and the surface of the ground
L	influence length in m
l_m	effective influence length for the calculation of a mid-post
M_{\max}	maximum bending moment in kNm/m
M_{post}	bending moment of a post in kNm
q_{1k}	loading according to EN 1991-2:2003, 6.6.2, in kN/m ² without considering the factor k_2
q_{DS}	quasi-static load for the air pressure wave due to a passing train at an elevation z above rail top considering the influence length, wall height and dynamic effects in kN/m ²
q_{post}	loading for a post in kN/m with reference to post height
s_{DS}	horizontal spacing between the two relevant load model positions of the air pressure wave for maximum structural reactions, in m
V_{\max}	maximum shear force in kN/m
V_{post}	shear force of a post in kN
V_{train}	train velocity in m/s (design speed)
z	elevation above rail top in m, where the quasi-static equivalent load shall be calculated. For elevations $z < 0$ it is assumed that $z = 0$
κ_t	relation between natural and applied frequency
φ_{dyn}	dynamic factor – considering dynamic effects
φ_H	height factor – considering wall height and elevation above rail top
φ_{H1}	value of φ_H for the ratio $z/h = 1,0$
φ_L	length factor – considering the influence length of the air pressure wave

5 Quasi-static equivalent load model

5.1 Application requirements

The air pressure wave due to a passing train may be determined according to the defined quasi-static equivalent load model presented in 5.3, provided the following criteria are met:

- statically-determined post-and-panel structure;
- post spacing $\leq 7,50$ m;
- wall height above rail top $\leq 5,00$ m;
- there is negligible torsion of panels;
- there are no additional dynamic actions.

If these requirements are not fulfilled, additional data shall be obtained by numerical methods (e.g. dynamic analysis with an appropriate load model).

5.2 Air pressure wave

The air pressure wave due to a passing train given by the load model in EN 1991-2:2003, 6.6.2, shall be used in combination with the requirements of sub-Clauses 5.3, 5.4, 5.5 and 5.6.

5.3 Quasi-static equivalent load

The quasi-static equivalent load shall be calculated by the following formula:

$$\pm q_{DS} = \varphi_L \cdot \varphi_H \cdot \varphi_{dyn} \cdot q_{1k} \quad (1)$$

where

- $\pm q_{DS}$ is the quasi-static load for the air pressure wave of a passing train at an elevation z above the rail top considering the influence length, the wall height and the dynamic factor;
- φ_L is the length factor - considering the influence length of the air pressure wave;
- φ_H is the height factor - considering wall height and elevation above the rail top;
- φ_{dyn} is the dynamic factor - based on consideration of the dynamic response of statically-determined post-and-panel structures;
- q_{1k} is the loading according to EN 1991-2:2003, 6.6.2, without considering the factor k_2 . Depending on the shape of the train, q_{1k} can be multiplied by the factor k_1 as set out in EN 1991-2.

The load q_{DS} shall always be applied, as with the load q_{1k} , in the form of a line load with a horizontal length of 5 m on each side in different directions according to EN 1991-2:2003, 6.6.2, in the relevant load position for calculation of maximum forces and moments. It is important to note that, in contrast to q_{1k} , the load q_{DS} has a variable value related to the elevation above the rail top.

The relevant load model position for $\pm q_{DS}$ is given in 6.2 to 6.5.

5.4 Length factor

The length factor is presented in Table 1.

For intermediate values of L and h in Table 1, the value of φ_L shall be determined on the basis of linear interpolation.