

SVENSK STANDARD

SS-ISO 13474:2011

Fastställt/Approved: 2011-12-01
Publicerad/Published: 2011-12-09
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 17.140.01

Akustik – Regelverk för beräkning av fördelning av nivåer på ljudexponering av impuls ljud med syfte att bedöma buller till omgivningen (ISO 13474:2009, IDT)

Acoustics – Framework for calculating a distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment (ISO 13474:2009, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-82391>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 13474:2009 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 13474:2009.

Denna standard ersätter SIS-ISO/TS 13474:2003, utgåva 1.

The International Standard ISO 13474:2009 has the status of a Swedish Standard. This document contains the official version of ISO 13474:2009.

This standard supersedes the Swedish Standard SIS-ISO/TS 13474:2003, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Uppllysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna uppllysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Akustik och buller, SIS/TK 110.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Basic equations	6
4.1 General	6
4.2 Probability of occurrence	6
4.3 Band sound exposure level.....	7
4.4 Frequency-weighted sound exposure level.....	8
4.5 Long-term average single-event sound exposure level	8
4.6 Equivalent level from multiple events	10
5 Calculation of a statistical distribution	10
6 Calculation of attenuation	14
6.1 General	14
6.2 Geometric divergence.....	14
6.3 Atmospheric absorption.....	14
6.4 Insertion loss by screening objects	15
6.5 Terrain shielding.....	15
6.6 Contributions to excess attenuation	16
6.6.1 General	16
6.6.2 Refraction	16
6.6.3 Ground reflection and absorption	17
7 Classification	19
7.1 General	19
7.2 Classification of atmospheric absorption.....	19
7.3 Classification of excess attenuation	19
7.3.1 General	19
7.3.2 Lookup table requirements	20
7.3.3 Range-dependent sound speed profiles.....	21
7.3.4 Directed sound speed profiles	21
8 Probability of occurrence of sound speed profiles	22
8.1 General	22
8.2 Using direct measurements of wind and temperature profiles	22
8.3 Similarity relationships for the atmospheric surface layer.....	23
8.4 Using measurements of turbulent fluxes.....	24
8.5 Using routinely gathered weather station data	25
8.6 Using directly measured or calculated sound speed profiles as input	26
9 The source	26
9.1 General	26
9.2 Demolition and muzzle blasts	26
9.2.1 General	26
9.2.2 Source descriptors	27
9.2.3 Determination by measurement.....	27
9.2.4 Determination by estimation	28
9.3 Projectile sound.....	28
9.3.1 General	28

SS-ISO 13474:2011 (E)

9.3.2 Flat trajectories28

9.3.3 High-elevation trajectories and rocket trajectories28

10 Uncertainties28

**Annex A (informative) Example of the estimation of the statistical distribution of single-event
sound exposure levels30**

Annex B (informative) Uncertainty37

Bibliography40

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 13474 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

It cancels and replaces ISO/TS 13474:2003, which has been technically revised.

Introduction

The aim of this International Standard is to provide a framework for the evaluation of descriptor quantities for use in environmental noise assessment. Part of this framework includes an engineering method for calculating a statistical distribution of event sound exposure levels at locations which are some distance from high-energy impulsive sound sources. It is specifically intended for environmental noise assessment and not for the assessment of the risk of damage to buildings or the risk of injury to animals or people.

In ISO 9613-2, the immission level from sources such as traffic and industry is calculated for a so-called “downwind” condition. The long-term average level is estimated using a correction factor, C_{met} . This concept holds for distances where sound from such sources is assessed as environmental noise. ISO 9613-2 excludes impulses in its scope and holds only for A-weighting, for near-ground sources and receivers and for distances up to about 1 000 m. For high-energy impulsive sound sources, the impulsive sound event duration is short, and low frequencies are more prominent than for traffic and industrial sound sources. Lower-frequency sounds are generally less attenuated over a given distance in the atmosphere than higher frequencies and, as a consequence, the level-influencing effects of propagation over much larger distances need to be taken into account.

A general outline is given of a method that takes into account ground reflection, shielding by topography and the meteorological effects of refraction and turbulence. Starting from the source strength, this method calculates a distribution of immission levels for a set of replica atmospheres, each replica being a specific combination of atmospheric-absorption class and excess-attenuation class. To carry out practical calculations using the procedure, it is useful to exploit the statistical contribution of the meteorological and ground surface conditions. In particular, histograms of the frequencies of occurrence of the wind velocity, wind direction, temperature, humidity and atmospheric stability can be used to describe the classes. From the distribution of the immission levels, a number of assessment metrics can be obtained. For instance, the long-term averaged immission level can be calculated as a weighted average. The weighting factors are determined by the probability of occurrence of each replica atmosphere during the relevant time period for the location of interest.

Acoustics — Framework for calculating a distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment

1 Scope

This International Standard specifies the framework of an engineering method for calculating a statistical distribution of sound exposure levels for impulsive sound events for the purposes of environmental noise assessment. This International Standard is applicable to impulse sounds propagating over large distances (e.g. 0,5 km to 30 km) from sources such as mine blasting, artillery fire and bomb explosions, using conventional explosives of moderate charge mass (e.g. 0,05 kg to 1 000 kg of TNT equivalent). The effects of meteorological conditions and terrain upon sound propagation are considered.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1996-1, *Acoustics — Description, measurement and assessment of environmental noise — Part 1: Basic quantities and assessment procedures*

ISO 3534-1, *Statistics — Vocabulary and symbols — Part 1: General statistical terms and terms used in probability*

ISO 9613-1, *Acoustics — Attenuation of sound during propagation outdoors — Part 1: Calculation of the absorption of sound by the atmosphere*

ISO 9613-2, *Acoustics — Attenuation of sound during propagation outdoors — Part 2: General method of calculation*

ISO 17201-1, *Acoustics — Noise from shooting ranges — Part 1: Determination of muzzle blast by measurement*

ISO 17201-2, *Acoustics — Noise from shooting ranges — Part 2: Estimation of muzzle blast and projectile sound by calculation*

ISO 17201-4, *Acoustics — Noise from shooting ranges — Part 4: Prediction of projectile sound*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

VDI MSR 8/559, *Standard Method to Measure the Sound Exposure Emissions and Immissions from Large Weapons (Standardmethode zur Messung der Geräuschemissionen und -immissionen von schweren Waffen)*, Edmund Buchta (ed.), in *Meß-, Steuerungs- und Regelungstechnik*, No. 8/559, Fortschritt-Berichte, VDI Verlag, Düsseldorf, 1996 (in English and German)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 atmospheric absorption
attenuation of sound by air, resulting from viscous molecular processes, molecular rotation and molecular vibration

3.2 atmospheric-absorption class
range of meteorological parameters yielding approximately the same attenuation of sound by air, all within a specified uncertainty

NOTE See also atmospheric absorption.

3.3 atmospheric stability
tendency of the atmosphere to reduce or enhance vertical motion of the air

NOTE Enhanced (or reduced) vertical motion of the air usually implies enhanced (or reduced) atmospheric turbulence.

3.4 atmospheric-stability class
subset formed from partitioning the set of atmospheres according to stability

NOTE See also atmospheric stability.

3.5 direct path
position displacement vector, in metres, originating at the source and describing a straight trajectory terminating at the receiver

NOTE The direct path may intercept objects such as buildings or terrain.

3.6 directed sound speed
algebraic sum of the adiabatic sound speed and the horizontal component of the wind velocity along the direct path

NOTE Directed sound speed is expressed in metres per second.

3.7 directed sound speed profile
sound speed along the direct path, expressed as a function of height

NOTE See directed sound speed.

3.8 event
single short burst, or rapid sequence of bursts, associated with a sound source

NOTE A single activity, such as firing a gun, could produce multiple sound events. In the case of firing an explosive projectile from a high-velocity gun, sound events are associated with each of the following sound sources: the muzzle blast, the ballistic shock and the projectile impact.

3.9 event duration

T

time interval starting just before immission, at time t_1 , and ending just after immission, at time t_2 , to encompass all significant sound of a single short blast or rapid sequence of blasts

NOTE The time interval $t_2 - t_1$ is expressed in seconds.

3.10 exceedance level

sound level of a stated type, in decibels, exceeded by no more and no less than a stated percentage of samples

NOTE The sampling set shall be identified, e.g. percentage of times during a stated time interval or percentage of firing events from an exercise.

3.11 excess attenuation

that part of sound attenuation not included when accounting for geometric divergence (from a small sound source in non-refracting and non-moving air), atmospheric absorption of sound waves along the direct path from source to receiver and attenuation of screens and/or barriers

NOTE Excess attenuation is expressed in decibels.

3.12 excess-attenuation class

range of combined directed sound speed profiles and ground types yielding approximately the same attenuations, all within a specified uncertainty

3.13 ground condition

sound reflection and absorption properties of outdoor surface(s) along the sound path(s) between source and receiver

3.14 impulsive sound event

occurrence of a single short blast or series of blasts of sound in which the pressure-time history, close to the source, includes a rapid rise to the peak sound pressure followed by decay of the pressure

3.15 sound pressure

p

difference between instantaneous total pressure and static pressure

[ISO 80000-8:2007, 8-9.2]

NOTE 1 Sound pressure is expressed in pascals.

NOTE 2 The symbol p is often used without modification to represent a root-mean-square sound pressure. However, root-mean-square values should preferably be indicated by the subscript "eff".

[ISO/TR 25417:2007, 2.1]

3.16 open-air explosion

blast, taking place out-of-doors, in which no part of the exploding material or gaseous products is limited by a container or any other obstructing surface