

INTERNATIONAL STANDARD

ISO 12232

Second edition
2006-04-15

Photography — Digital still cameras — Determination of exposure index, ISO speed ratings, standard output sensitivity, and recommended exposure index

*Photographie — Appareils de prises de vue numériques —
Détermination de l'indice d'exposition, des régimes de vitesse ISO, de
la sensibilité normale de sortie et de l'indice d'exposition recommandé*



Reference number
ISO 12232:2006(E)

© ISO 2006

ISO 12232:2006(E)

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Exposure index values	3
4.1 General.....	3
4.2 Focal plane measurement.....	3
4.3 Scene luminance measurement	3
5 Test conditions	4
5.1 General.....	4
5.2 Illumination.....	4
5.2.1 Daylight illumination	4
5.2.2 Tungsten illumination	4
5.3 Temperature and relative humidity	5
5.4 White balance.....	5
5.5 Infrared (IR) blocking filter.....	5
5.6 Photosite integration time	5
5.7 Compression.....	5
5.8 Other DSC user settings	5
6 Determination of ISO speed.....	5
6.1 General.....	5
6.2 Saturation-based speed	5
6.2.1 Focal plane measurement.....	6
6.2.2 Scene luminance measurement	6
6.3 Noise-based speed	6
6.3.1 Focal plane method	6
6.3.2 Scene luminance method	7
6.3.3 Colour cameras.....	7
6.3.4 Quantization effects.....	8
6.4 Method of reporting.....	8
7 Determination of standard output sensitivity (SOS)	8
7.1 Method for calculating SOS.....	9
7.2 Method of reporting.....	9
8 Specification of recommended exposure index (REI)	9
8.1 Method for calculating recommended exposure index	9
8.2 Method of reporting.....	10
Annex A (informative) Recommended procedure for determining the noise-based ISO speed.....	11
Annex B (informative) Scene luminance and focal plane exposure	13
Annex C (informative) Recommended procedure for determining SOS values	14
Annex D (normative) Removing low frequency variations from the image data.....	15
Annex E (informative) Calculation of noise-based minimum illumination level.....	16
Bibliography	17

ISO 12232:2006(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12232 was prepared by Technical Committee ISO/TC 42, *Photography*.

This second edition cancels and replaces the first edition (ISO 12232:1998), which has been technically revised.

Introduction

The ISO speed rating, standard output sensitivity (SOS) and recommended exposure index (REI) are important attributes of digital still cameras (DSCs). Standardization assists users and manufacturers in obtaining proper exposures and in determining the low light capability of DSCs.

The exposure level of a DSC is determined by the exposure time, the lens aperture, the lens transmittance, the level and spectral distribution of the scene illumination, and the scene reflectance. When an image from a DSC is obtained using an insufficient exposure, proper tone reproduction can generally be maintained by increasing the electronic or digital gain, but the image will contain an unacceptable amount of noise. As the exposure is increased, the gain can be decreased, and, therefore, the image noise can normally be reduced to an acceptable level. If the exposure is increased excessively, the resulting signal in bright areas of the image may exceed the maximum signal level capacity of the image sensor or camera signal processing. This can cause the image highlights to be clipped to form a uniformly bright area, or to bloom into surrounding areas of the image. Therefore, it is important to guide the user in setting proper exposures. An ISO speed rating is intended to serve as such a guide. The methods for assigning an ISO speed rating to a DSC harmonize with current film-based photographic standards. In order to be easily understood by photographers, the ISO speed rating for a DSC should directly relate to the ISO speed rating for photographic film cameras. For example, if a DSC has an ISO speed rating of ISO 100, then the same exposure time and aperture should be appropriate for an ISO 100 rated film/process system.

The ISO speed ratings described in this International Standard are intended to harmonize with film ISO speed ratings. However, there are differences between electronic and film-based imaging systems that preclude exact equivalency. DSCs can include variable gain and can provide digital processing after the image data has been captured, enabling desired tone reproduction to be achieved over a range of camera exposures. It is therefore possible for DSCs to have a range of speed ratings. This range is defined as the ISO speed latitude. To prevent confusion, a single value is designated as the ISO speed, with the ISO speed latitude upper and lower limits indicating the speed range.

Photography — Digital still cameras — Determination of exposure index, ISO speed ratings, standard output sensitivity, and recommended exposure index

1 Scope

This International Standard specifies the method for assigning and reporting ISO speed ratings, ISO speed latitude ratings, standard output sensitivity values, and recommended exposure index values, for digital still cameras. This International Standard is applicable to both monochrome and colour digital still cameras.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 554, *Standard atmospheres for conditioning and/or testing — Specifications*

ISO 7589, *Photography — Illuminants for sensitometry — Specifications for daylight, incandescent tungsten and printer*

ISO 14524, *Photography — Electronic still-picture cameras — Methods for measuring opto-electronic conversion functions (OECFs)*

IEC 61966-2-1, *Multimedia systems and equipment — Colour measurement and management — Part 2-1: Colour management — Default RGB colour space — sRGB*

ITU-R BT.709, *Parameter values for the HDTV standards for production and international programme exchange*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

digital still camera

DSC

device which incorporates an image sensor and which produces a digital signal representing a still picture

NOTE A digital still camera is typically a portable, hand-held device. The digital signal is usually recorded on a removable memory, such as a solid-state memory card or magnetic disk.

3.2

exposure index

EI

numerical value that is inversely proportional to the exposure provided to an image sensor to obtain an image

NOTE Images obtained from a DSC using a range of exposure index values will normally provide a range of image quality levels.

ISO 12232:2006(E)

- 3.3**
exposure series
series of images of the same subject taken using different exposure index values
- 3.4**
image sensor
electronic device that converts incident electromagnetic radiation into an electronic signal
- EXAMPLE A charge coupled device (CCD) array.
- 3.5**
ISO speed
numerical value calculated from the exposure provided at the focal plane of a DSC to produce specified camera output signal characteristics using the methods described in this International Standard
- NOTE The ISO speed is usually the highest exposure index value that still provides peak image quality for normal scenes. However, a DSC does not necessarily use the ISO speed value as the exposure index value when capturing images.
- 3.6**
ISO speed latitude
set of two numerical values calculated from the exposure provided at the focal plane of a DSC to produce specified camera output signal characteristics using the methods described in this International Standard
- NOTE The ISO speed latitude needs to correlate with the range of exposure index values that provide acceptable image quality for normal scenes.
- 3.7**
photosite integration time
total time period during which the photosites of an image sensor are able to integrate the light from the scene to form an image
- 3.8**
recommended exposure index
REI
specific exposure index value recommended by a DSC provider as a reference for adjusting photographic accessories, as defined in this International Standard
- NOTE REI provides a practical exposure index value for setting the reference exposure index of light meters, studio lighting, etc., but images taken using this exposure index value do not necessarily provide the best image quality.
- 3.9**
signal processing
operations performed by electronic circuits or algorithms that convert or modify the output of an image sensor
- 3.10**
standard output sensitivity
SOS
specific exposure index value for a DSC that provides a still image with a specified digital output signal value under specified test conditions, as defined in this International Standard
- NOTE SOS provides a practical exposure index value based on the signal level of images captured with a DSC, but images taken using this exposure index value do not necessarily provide the best image quality.